TECHNICAL DATA SHEET 1 May 2023



ENGINEERED EUROPEAN OAK

PRODUCT SPECIFICATIONS

Туре	Timber Flooring	Style	Single Plank
Description	Engineered multi layer Core with 2.5mm European Oak Timber Veneer		
Board Construction	11mm multi layer Core, 2.5mm European Oak Timber Veneer		
Installation Method	Direct Stick	Finish	Light Wire Brush
Profile	Micro-Bevel	Timber Grade	ABCD
Dimensions	1900 x 190 x 14/3mm	Boards per Pack	6
m ² per Pack	2.888m²	Underlay	

TEST DATA

Fire Rating	Critical Heat Flux: 3.6kW/m ² Smoke Value: 19%	Slip Resistance	P3
Acoustic Rating	38 LnTW 6 Star (With 2mm Evaylay underlay) refer to Terra Mater Evaylay underlay		

Warranty	20 Year Residential Warranty Life Time Structural Warranty
Variations in Timber	Timber is a natural material and variations in colour, texture and other naturally occurring features occur between pieces and batches of the same species. Timber flooring, whilst dried during production, continues to take up and give up moisture during its life, depending on weather, aspect and local conditions. In so doing, some movement and changes to the surface of your floor are to be expected and will be apparent. This is normal and may include fine cracks on and between boards and changes in colour.