

## ENGINEERED EUROPEAN OAK

### PRODUCT SPECIFICATIONS

<b>Type</b>	Timber Flooring	<b>Style</b>	Single Plank
<b>Description</b>	Engineered 3 layer construction with 3mm European Oak Timber Veneer		
<b>Board Construction</b>	3 layer constructions SPF , 3mm European Oak Timber Veneer		
<b>Installation Method</b>	Direct Stick	<b>Finish</b>	Light Wire Brush
<b>Profile</b>	Micro-Bevel	<b>Timber Grade</b>	ABCD
<b>Dimensions</b>	1900 x 190 x 14/3mm	<b>Boards per Pack</b>	6
<b>m<sup>2</sup> per Pack</b>	2.888m <sup>2</sup>	<b>Underlay</b>	

### TEST DATA

<b>Fire Rating</b>	Critical Heat Flux: 3.6kW/m <sup>2</sup> Smoke Value: 19%	<b>Slip Resistance</b>	P3
<b>Acoustic Rating</b>	38 LnTW 6 Star (With 2mm Evaylay underlay) refer to Terra Mater Evaylay underlay		

<b>Warranty</b>	20 Year Residential Warranty   Life Time Structural Warranty
<b>Variations in Timber</b>	<p>Timber is a natural material and variations in colour, texture and other naturally occurring features occur between pieces and batches of the same species.</p> <p>Timber flooring, whilst dried during production, continues to take up and give up moisture during its life, depending on weather, aspect and local conditions. In so doing, some movement and changes to the surface of your floor are to be expected and will be apparent. This is normal and may include fine cracks on and between boards and changes in colour.</p>