



<b>Product:</b>	High Visibility Mat	<b>Standard widths with borders:</b>	60 cm, 75 cm, 85 cm, 115 cm, 150 cm and 200 cm
<b>Customs tariff number:</b>	57032098	<b>Standard widths without borders:</b>	3 cm smaller than for mats with borders (e.g. 57 cm)
<b>Product details:</b>	<ul style="list-style-type: none"> <li>» Printed safety message</li> <li>» Highly visible graphics</li> <li>» Custom designs</li> <li>» Dust, dirt and moisture control</li> <li>» Skid resistant rubber back</li> <li>» PVC-free</li> <li>» Suitable for underfloor heating</li> <li>» 5 years Manufacturers Guarantee*</li> <li>» Made in Europe</li> </ul>	<b>Standard lengths:</b>	all lengths up to 400 cm
<b>Burning behaviour:</b>	EN 13501-1 / Cfl-s1	<b>Bespoke lengths:</b>	up to 700 cm
<b>Static electrical propensity:</b>	EN 14041 Antistatic	<b>Colouration:</b>	Chromojet printing process
<b>Slip resistance:</b>	NFSI High-Traction	<b>Pile:</b>	100 % High-Twist Nylon (HTN) Polyamide 6.6
<b>Total mat weight:</b>	2.48 kg/sqm	<b>Pile height:</b>	approx. 8 mm
<b>Overall height:</b>	approx. 9 mm	<b>Pile weight:</b>	without substrate: 680 g/sqm with substrate: 780 g/sqm
<b>Dirt absorption:</b>	600 g/sqm	<b>Backing:</b>	100 % Nitrile rubber Available with kleeled or smooth backing
<b>Moisture absorption:</b>	3 - 4 l/sqm	<b>Rubber thickness:</b>	1.40 mm
<b>Application areas:</b>	<ul style="list-style-type: none"> <li>» Indoor placement</li> <li>» Workplaces</li> <li>» Factory</li> <li>» Offices</li> </ul>	<b>Rubber weight:</b>	1.70 kg/sqm
		<b>Border width:</b>	20 mm
		<b>Border thickness:</b>	Available with or without borders 2.40 mm
		<b>Cleaning:</b>	» Washable up to 60 °C » Tumble dry up to 60 °C