



LENGTH: "A"	3FT	4FT	5FT	6FT	7FT	8FT	9FT	10FT
	915±30	1220±50	1530±50	1830±50	2135±50	2440±50	2745±50	3050±50
P/N BLACK	P-3212-03BLK-14	P-3212-04BLK-14	P-3212-05BLK-14	P-3212-06BLK-14	P-3212-07BLK-14	P-3212-08BLK-14	P-3212-09BLK-14	P-3212-10BLK-14
P/N WHITE(RAL9010)	P-3212-03WHT-14	P-3212-04WHT-14	P-3212-05WHT-14	P-3212-06WHT-14	P-3212-07WHT-14	P-3212-08WHT-14	NA	P-3212-10WHT-14
P/N RED(GY-49)	P-3212-03RED-14	P-3212-04RED-14	P-3212-05RED-14	P-3212-06RED-14	P-3212-07RED-14	P-3212-08RED-14	NA	P-3212-10RED-14
P/N BLUE(PT293C)	P-3212-03BLU-14	P-3212-04BLU-14	P-3212-05BLU-14	P-3212-06BLU-14	P-3212-07BLU-14	P-3212-08BLU-14	NA	P-3212-10BLU-14

NO.	SPECIFICATION	QTY	REMARK
1	SJT 14/3C 105°C	1PC	
2	YP-32 PVC PLASTIC:50P	15g/PC	
3	TER:98672BS-1	3PCS	
4	INNER BODY: 2X4	1PC	
5	TER:97740	3PCS	
6	YC-12 INNER BODY	1PC	
7	YC-12 PVC PLASTIC:50P	18g/PC	
8	LABEL: (40+30)*30mm	1PC	

Packing: Bundled to ease installation.

Sample Drawing No.: SP211018-05

Tolerance	Approved	Date	SIGNAL+POWER				
	>0±0.30	Checked	Date				
>1.0±0.50	Drawn	SUKI	Date	21.10.18	Customer		
>10.0±1.0	Cat. No.	UL YP-32/YC-12		P/N.	P-3212-XXYYY-14		
>20.0±2.0	Drawing No.	Rev.	B	Material	P.V.C	Unit	mm
Angle: ±1°				Scale			