



- 1. HEAT IS PROVIDED BY A 60WATT, 120V SINGLE PHASE HEAT TRACE TAPE. FOR UNHEATED VERSION REPLACE THE PREFIX "H" WITH AN "L".
- 2. FOUR INTERNAL BRACKETS AND CONCRETE ANCHORS ARE SUPPLIED WITH THE ENCLOSURE.
- 3. FOR RECOMMENDED SLAB SIZE ADD 9" [229] TO THE ENCLOSURE EXTERIOR.
- 4. THIS ENCLOSURE IS DESIGNED WITH A FLIP UP LID & A FOLDABLE/REMOVABLE FRONT FOR EASE OF MAINTENANCE AND TESTING.
- 5. OLD P/N: DF1TH

	-, -, -, -, -, -, -, -, -, -, -, -, -, -										
	DIMENSIONS ARE IN INCHES OR MILLIMETERS IN BRACKETS UNLESS OTHERWISE NOTED.										
			WEIGHT				® 924	LAN	E AVENUE	LOC	
	BY	DATE	66# 30kg	HU	BĖ		JAC	KSON	WILLE, FL 32254 0-0204	LC	
DRN	КРЕ	9/25/09	SCALE	www.hot-box.com						S	
СНК	<i>4339</i>	9/9/10		DRAWING DESCRIPTION					REV		
ENG			1 1/2"=1"	HOT BOX [®] ALUMINUM ENCLOSURE						A	
APR			SIZE								
APR			В								
PROJ	ECT NU						DRAWING NUMBE	R			
	08	SHEET	1	OF	1		HD013027035				