



- 1. HEAT IS PROVIDED BY A 60WATT, 120V SINGLE PHASE HEAT TRACE TAPE. FOR UNHEATED VERSION REPLACE THE PREFIX "H" WITH AN "L".
- 2. FOUR INTERNAL BRACKETS AND CONCRETE ANCHORS ARE SUPPLIED WITH THE ENCLOSURE.
- 3. FOR RECOMMENDED SLAB SIZE ADD 9" [229] TO THE ENCLOSURE EXTERIOR.
- 4. THIS ENCLOSURE IS DESIGNED WITH A FLIP UP LID & A FOLDABLE/REMOVABLE FRONT FOR EASE OF MAINTENANCE AND TESTING.
- 5. OLD P/N: DF1.5H

			-,								
	DIMENSIONS ARE IN INCHES OR MILLIMETERS IN BRACKETS UNLESS OTHERWISE NOTED.										
			WEIGHT						E AVENUE	LOC	
	BY	DATE	69# 31kg	HÚBE	3ÈĻ	ĊĹ	JAC	KSON	VILLE, FL 32254 -0204	LC	
DRN	КРЕ	8/19/09	SCALE					.hot-box.com		S	
снк				DRAWING DESCRIPTION HOT BOX® ALUMINUM ENCLOSURE						REV	
ENG			1 1/2"=1"							A	
APR			SIZE								
APR			В								
PRO		MBER	1					DRAWING NUMBE	R		
	0:	9814	SHEET	1 0)F	1		HD021033024			