

P/N 15-1711 RIFE G Series Shock Travel Sensor Data Calibration 11.5"

Calibration - 32 points:	
Length (in)	Voltage [V]
0.00	0.13
0.37	0.28
0.74	0.44
1.11	0.59
1.48	0.75
1.85	0.90
2.23	1.05
2.60	1.21
2.97	1.36
3.34	1.51
3.71	1.67
4.08	1.82
4.45	1.98
4.82	2.13
5.19	2.28
5.56	2.44
5.94	2.59
6.31	2.75
6.68	2.90
7.05	3.05
7.42	3.21
7.79	3.36
8.16	3.52
8.53	3.67
8.90	3.82
9.27	3.98
9.65	4.13
10.02	4.28
10.39	4.44
10.76	4.59
11.13	4.75
11.50	4.90

Calibration - 16 points:	
Length (in)	Voltage [V]
0.00	0.13
0.77	0.45
1.53	0.77
2.30	1.08
3.07	1.40
3.83	1.72
4.60	2.04
5.37	2.36
6.13	2.67
6.90	2.99
7.67	3.31
8.43	3.63
9.20	3.95
9.97	4.26
10.73	4.58
11.50	4.90

Calibration - 8 points:	
Length (in)	Voltage [V]
0.00	0.13
1.64	0.81
3.29	1.49
4.93	2.17
6.57	2.86
8.21	3.54
9.86	4.22
11.50	4.90

Calibration - 2 points:	
Length (in)	Voltage [V]
0.00	0.13
11.50	4.90