

P/N 15-1703 RIFE G Series Shock Travel Sensor Data Calibration 3.75"

Calibration - 32 points:	
Length (in)	Voltage [V]
0.00	0.13
0.12	0.28
0.25	0.44
0.37	0.59
0.50	0.75
0.62	0.90
0.75	1.05
0.87	1.21
1.00	1.36
1.12	1.51
1.25	1.67
1.37	1.82
1.50	1.98
1.62	2.13
1.75	2.28
1.87	2.44
2.00	2.59
2.12	2.75
2.25	2.90
2.37	3.05
2.50	3.21
2.62	3.36
2.75	3.52
2.87	3.67
3.00	3.82
3.12	3.98
3.25	4.13
3.37	4.28
3.50	4.44
3.62	4.59
3.75	4.75
3.87	4.90

Calibration - 16 points:	
Length (in)	Voltage [V]
0.00	0.13
0.26	0.45
0.52	0.77
0.77	1.08
1.03	1.40
1.29	1.72
1.55	2.04
1.81	2.36
2.06	2.67
2.32	2.99
2.58	3.31
2.84	3.63
3.10	3.95
3.35	4.26
3.61	4.58
3.87	4.90

Calibration - 8 points:	
Length (in)	Voltage [V]
0.00	0.13
0.55	0.81
1.11	1.49
1.66	2.17
2.21	2.86
2.76	3.54
3.32	4.22
3.87	4.90

Calibration - 2 points:	
Length (in)	Voltage [V]
0.00	0.13
3.87	4.90