

## P/N 15-1707 RIFE G Series Shock Travel Sensor Data Calibration 7.5"

<b>Calibration - 32 points:</b>	
<b>Length (in)</b>	<b>Voltage [V]</b>
0.00	0.13
0.25	0.28
0.49	0.44
0.74	0.59
0.98	0.75
1.23	0.90
1.47	1.05
1.72	1.21
1.97	1.36
2.21	1.51
2.46	1.67
2.70	1.82
2.95	1.98
3.20	2.13
3.44	2.28
3.69	2.44
3.93	2.59
4.18	2.75
4.42	2.90
4.67	3.05
4.92	3.21
5.16	3.36
5.41	3.52
5.65	3.67
5.90	3.82
6.15	3.98
6.39	4.13
6.64	4.28
6.88	4.44
7.13	4.59
7.37	4.75
7.62	4.90

<b>Calibration - 16 points:</b>	
<b>Length (in)</b>	<b>Voltage [V]</b>
0.00	0.13
0.51	0.45
1.02	0.77
1.52	1.08
2.03	1.40
2.54	1.72
3.05	2.04
3.56	2.36
4.06	2.67
4.57	2.99
5.08	3.31
5.59	3.63
6.10	3.95
6.60	4.26
7.11	4.58
7.62	4.90

<b>Calibration - 8 points:</b>	
<b>Length (in)</b>	<b>Voltage [V]</b>
0.00	0.13
1.09	0.81
2.18	1.49
3.27	2.17
4.35	2.86
5.44	3.54
6.53	4.22
7.62	4.90

<b>Calibration - 2 points:</b>	
<b>Length (in)</b>	<b>Voltage [V]</b>
0.00	0.13
7.62	4.90