



- Basic or DALI-2 Recessed Exit Sign
- Recessed Mounting
- White Polycarbonate body
- Extra Long Life LiFePO4 cells
- 25m viewing distance
- ISO 7010 legends as standard
- Operates the DALI-2 Protocol
- Samsung LED's
- Operates with LiteMesh Wireless Systems

A stylish and compact Double Sided LED Exit Sign suitable for ceiling recess mount applications. The unit is available in either a Switchable Maintained/Non-Maintained, DALI-2 Self-Test, or a LiteMesh Ready wireless version. The fitting is supplied with a PMMA screen printed legend plate which offers an impressive 25m viewing distance. The legend panels are available in either Arrow Up (AU), Arrow Down (AD) or Arrow Left/Right (ALAR). Please note that all legends are single sided, apart from the ALAR which are double sided. The batteries used with this unit not only offer double the life of traditional emergency lighting batteries, but consume far less power during their operation.

Order Codes

CE1R/M/**	Switchable Maintained
CE1R/DA/**	DALI-2 Type B, Switched Maintained Non-Dimmable, or Self-Test M3/NM3
CE1R/M/LMEM/**	LiteMesh Ready Wireless Maintained/Non-Maintained Self-Test

** Please specify legend required AU, AD, or ALAR

Technical Details:

	CE1R/M/**	CE1R/DA/**
Mains Supply	230-240V AC 50/60 Hz	
Power Rating - Charging M-Mode *	5.7W 34mA $\lambda = 0.71$	5.4W 30mA $\lambda = 0.75$
Power Rating - Charged NM-Mode *	0.2W 11mA $\lambda = 0.07$	0.3W 8mA $\lambda = 0.15$
Duration	3-Hours	
Recharge Period	24-Hours	
Battery Size & Type	3.2V 3.8Ah LiFePO4 Cells	
Charge Current	225mA Nominal	
Ingress Protection Rating	IP20	
Weight	0.9Kg	0.9Kg

* Following its initial charge, the control gear will spend 90% of its operational life in standby mode