

QT-ECO 1X4...16 L

QUICKTRONIC ECONOMIC | ECG for FL 7 mm and CFL



Areas of application

- Public buildings

Product family benefits

- Compact housing
- Automatic restart after lamp replacement
- Large input voltage range

Product family features

- Supply voltage: 220...240 V
- Line voltage: 198...264 V
- Line frequency: 50 Hz
- Energy Efficiency Index EEI: A2 / A3 (depending on lamp)
- Automatic shutdown of defective lamps and at end of life (EoL)

Product datasheet

Technical data

Electrical data

Nominal voltage	220...240 V
Mains frequency	50 Hz
Input voltage DC	176...254 V
Operating frequency	40 kHz ¹⁾
Max. ECG no. on circuit breaker 10 A (B)	68
Max. ECG no. on circuit breaker 16 A (B)	112
Inrush current	10 A


¹⁾ Approximately

Light technical data

Starting time	1.0 s ¹⁾
---------------	---------------------

¹⁾ Preheat start: After a switch off, the lamps should remain switched off for 2 minutes to ensure an optimum preheat start

Dimensions & weight



Length	150.0 mm
Width	22.0 mm
Height	22.0 mm
Mounting hole spacing, length	140.0 mm
Product weight	50.00 g

Temperatures & operating conditions

Ambient temperature range	-15...+50 °C
Permitted rel. humidity during operation	5...85 % ¹⁾

¹⁾ Maximum 56 days/year at 85 %

Lifespan

Product datasheet

ECG lifetime	30000 h ¹⁾
---------------------	-----------------------

¹⁾ T_c = 70°C, with max. 10% failure rate

Additional product data

Suitable for lamp power (1 lamp)	4...16 W
---	----------

Capabilities

Suitable for fixtures with prot. class	I / II
End of lamp life safety shutdown	EOL T.2
Dimmable	No

Certificates & standards


Approval marks – approval	VDE
EEI – Energy Label	A2/A3 ¹⁾
Standards	Acc. to EN 61347-2-3/Acc. to EN 55015:2006 + A1:2007/Acc. to EN 61000-3-2/Acc. to EN 61547
Protection class	I
Type of protection	IP20

¹⁾ For detailed information please see Lamp-ECG combinations

Logistical data











Commodity code	850410809000
-----------------------	--------------

Wiring Diagram



Wiring diagram

Download Data

File	
	Addon Technical Information 58010_ADDON TECHNICAL INFORMATION QT-ECO 1x... L S (G+GB)
	Certificates 334955_VDE-Marks approval
	Certificates 334983_VDE-Marks approval
	Certificates 335154_Manufacturer's declaration – EN 55015:2006+A1:2007 (300 MHz)
	Certificates 683440_VDE-Marks approvals
	Declarations of conformity 334801_Declaration of conformity
	Operating instructions 592501_EAC QT-ECO
	CAD data 3-dim 313426_150x22x22 9900013
	CAD data 3-dim 313486_150x22x22 9900013
	CAD data 3-dim 313493_150x22x22 9900013

Product datasheet



CAD data PDF
313395_150x22x22 9900013

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4050300660370	QT-ECO 1X4...16 L	Shipping carton box 50	232 mm x 148 mm x 163 mm	5.60 dm ³	2802.50 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

QT-ECO 1X4...16 L

QUICKTRONIC ECONOMIC | ECG for FL 7 mm and CFL

Product name	Lamp group	Nominal current	Nominal wattage + Power loss	Luminous flux at 25 °C	Number of lighting outlets	EEL – Energy Label	Luminous flux at 35 °C
QT-ECO 1X4...16 L	DULUX D/E 10 W	0.08 A	11.50 W	600 lm	1	A3	
	DULUX D/E 13 W	0.10 A	14.00 W	850 lm	1	A2	
	DULUX S/E 11 W	0.09 A	13.00 W	900 lm	1	A3	
	DULUX S/E 7 W	0.06 A	9.00 W	400 lm	1	A3	
	DULUX S/E 9 W	0.07 A	10.00 W	600 lm	1	A3	
	DULUX T/E 13 W	0.10 A	14.00 W	800 lm	1	A2	
	HE 14 W	0.10 A	15.00 W		1	A2	1150 lm
	L 10 W	0.10 A	12.00 W		1		650 lm
	L 13 W BASIC	0.08 A	15.00 W		1		950 lm
	L 16 W	0.11 A	16.00 W		1		1100 lm
	L 6 W BASIC	0.06 A	8.50 W		1		270 lm
	L 8 W BASIC	0.07 A	10.50 W		1		450 lm