

# AV PRO CFexpress MK2

CFexpress™ 2.0 | TYPE B




SUSTAINED HIGH-SPEED CFEXPRESS PERFORMANCE  
FOR RAW 12K+ VIDEO AND PHOTO PRODUCTION



ANGELBIRD.COM

1 TB | 2 TB | 4 TB



# FEATURES



**CFexpress™ 2.0 | Type B**



**Guaranteed Sustained Write Speed of 1300 MB/s**  
for RAW 12K+ Production



**Y2 Processor**  
Exceptional Processing Power for RAW Video and Photo Production



**Stable Stream™**  
Uninterrupted Read/Write Performance throughout the Card's Capacity



**Rock-Solid Build**



**Advanced Thermal Management**  
Protects the Card against Overheating



**Adaptive Power Management**  
Improved Run Time of the Camera's Battery




**Host Power Loss Protection**



**Free Engraving Option**



**Data Recovery Service<sup>1</sup>**  
on Hard- and Software Level



C  
F  
e  
X  
p  
r  
e  
s  
s  
  
M  
K  
2

# MEMORY CARDS

# SPECIFICATIONS | ORDERING

# CFexpress MK2

## General

### FORM FACTOR

CFexpress™ Type B

### CAPACITIES

1 TB | 2 TB | 4 TB

### UNIT DIMENSIONS

38.5 × 3.8 × 29.8 mm  
(1.52 × 0.15 × 1.17 in)

### UNIT WEIGHT

~ 7 g | 0.25 oz

## Technical

### INTERFACE

CFexpress™ 2.0 | Type B  
PCIe 3.0 × 2

### FEATURES

Temperature Sensor, TRIM<sup>2</sup>, ECC,  
EMS Protection, SMART<sup>2</sup>, Power  
Management

## Performance<sup>3</sup>

### MAXIMUM SPEEDS

Read: 1785 MB/s  
Write: 1550 MB/s

### MIN. SUSTAINED SPEEDS

Read: 1785 MB/s  
Write: 1300 MB/s

## Reliability

### DATA RELIABILITY

Built-In EDC / ECC Function

### CERTIFICATIONS

RoHS, CE, FCC, REACH, KC,  
UKCA, RCM

## Electrical

### DC INPUT VOLTAGE

3.3 V ± 5 %

### POWER USAGE

Sleep < 50mW  
Idle 0.45 W  
Max 2.40 W

## Environmental

### SHOCK RESISTANCE

Operating: 50 G

### VIBRATION RESISTANCE

Operating: 15 G

### TEMPERATURE RESISTANCE

Operating:  
-10 °C | 70 °C  
14 °F | 158 °F

### Storage:

-20 °C | 85 °C  
-4 °F | 185 °F

### OPERATING HUMIDITY

5 % to 95 % Non-Condensing

## Warranty<sup>4</sup>

3-Year Limited Warranty

## Package Content

- AV PRO CFexpress MK2 | Type B

## Retail Packaging Details

### BOX DIMENSIONS

113 × 23 × 132 mm  
(4.45 × 0.91 × 5.2 in)

### BOX WEIGHT

~ 60 g | 2.12 oz

<sup>1</sup> Data recovery service exclusively provided by Angelbird in Austria.

<sup>2</sup> TRIM and SMART support depending on the OS used.

<sup>3</sup> Speeds based on internal testing. Actual transfer rates and capacity may vary depending on system hardware and other factors. 4K, 6K, 8K, 12K+ and Full HD support may vary depending on host device, file attributes, and other factors.

<sup>4</sup> Visit [angelbird.com/warranty-activation](https://angelbird.com/warranty-activation) and activate your 3-year warranty within 30 days of purchase.

© 2022 Angelbird Technologies GmbH  
Angelbird is a registered trademark of Angelbird Technologies. All rights reserved.

Other product names used herein are for identification purposes only and may be trademarks of their respective owners. Angelbird disclaims any and all rights in those marks.

Specifications are subject to change without notice.  
Specifications are provided „as is“ without warranty of any kind.

## ORDERING INFORMATION

Capacity	SKU	EAN	UPC
● 1 TB	AVP1T0CFXBMK2	9120056585892	812937024710
● 2 TB	AVP2T0CFXBMK2	9120056585908	812937024727
● 4 TB	AVP4T0CFXBMK2	9120056585915	812937024734

# MEMORY CARDS

