
# LIQUID-SPECIFIC PRODUCT LINE

SERIES: 34
CAST IRON CONSTRUCTION











PRESSURE to 100 PSI (7 BAR)



TEMPERATURE -60°F to +450°F (-50°C to +230°C)



VISCOSITY 28 to 250,000 SSU (1 to 55,000 cSt)








### **PERFORMANCE**

MODELS	SPECIFICATIONS				
Jacketed	Performance			Standard Ports	
Packing	Max Speed, RPM	GPM	m³/h	Size, Inches	Туре
LQ34	420	90	20	2.5	Flange
Q34	350	200	45	3	Flange
M34	280	280	64	4	Flange
N34	280	450	102	5	Flange

## **CURVES**



#### **PORTING**

- Right Angle (90°)
- Flanged

# **SEALING**

Packing

#### MOUNTING

Foot Mount

## **OPTIONS**

- · Jacketed Internal Relief Valve
- · Hardened Part Options
- Plain Head for Externally Lubricated Idler Pin

# **DRIVES**

- R Offset Gear Reducer Drive
- Purchased Gear Reducer Drive
- V-Belt Drive

## **TYPICAL APPLICATIONS**

- Asphalt
- Bitumen
- Tar

- Pitch
- Bunker Oils
- · Residual Oils

# **VIKING PUMP®**

VIKING PUMP, INC.

A Unit of IDEX Corporation 406 State Street Cedar Falls, Iowa 50613 U.S.A.

vikingpump.com

United States

Cedar Falls, Iowa Phone: (319) 266-1741 Canada vikingpumpcanada.com

Windsor, Ontario Shannon Phone: (519) 256-5438 Phone: +353

Europe & Africa vikingpump.com

China - Shanghai 3 Phone: +86-21-5241-5599 Singapore Phone: +65-6684-7305

Asia-Pacific idexfmt-asia.com

India - Mumbai Phone: +91-22-6643-5563 Middle East vikingpump.com

**Dubai, UAE** Phone: +971 4 2600300

Contact Your Stocking Distributor Today
Distributed By:

Latin America

Australia & New Zealand vikingpump.com

