

# ROGERS® KR Series

## Performance Data and Dimensions

Model	Motor (HP)	Max Pressure (PSIG)	Flow (ACFM)	RPM (NOMINAL)	Length (IN)	Width (IN)	Height (IN)	A/C Weight (LBS)	W/C Weight (LBS)
KR-20-100	20	110	94	3600	72	40	48	1900	1800
KR-20-125	20	135	74	3600	72	40	48	1800	1700
KR-20-150	20	160	72	3600	72	40	48	1800	1700
KR-25-100	25	110	113	3600	72	40	51	2000	1900
KR-25-125	25	135	89	3600	72	40	51	2000	1900
KR-25-150	25	160	84	3600	72	40	51	2000	1900
KR-30-100	30	110	135	3600	72	40	51	2070	1970
KR-30-125	30	135	112	3600	72	40	51	2000	1900
KR-30-150	30	160	111	3600	72	40	51	2000	1900
KR-40-100	40	110	157	3600	77	52	53	3055	2855
KR-40-125	40	135	154	3600	77	52	53	3000	2800
KR-40-150	40	160	147	3600	77	52	53	3000	2800
KR-50-100	50	110	253	3600	77	52	53	3080	2880
KR-50-125	50	135	206	3600	77	52	53	3055	2855
KR-60-100	60	110	299	3600	91	58	68	4025	3825
KR-60-125	60	135	247	3600	91	58	68	4025	3825
KR-75-100	75	110	364	1800	91	58	68	5000	4800
KR-75-125	75	135	322	1800	91	58	68	5000	4800
KR-75-150	75	160	289	3600	91	58	68	4800	4600
KR-100-100	100	110	519	1800	99	62	72	6000	5800
KR-100-125	100	135	428	1800	99	62	72	6000	5800
KR-100-150	100	160	343	1800	91	58	68	5200	5000
KR-125-100	125	110	608	1800	120	70	81	6200	6000
KR-125-125	125	135	508	1800	99	62	72	6200	6000
KR-125-150	125	160	498	1800	99	62	72	6100	5900
KR-150-100	150	110	784	1800	120	70	81	6500	6300
KR-150-125	150	135	701	1800	120	70	81	6500	6300
KR-150-150	150	160	599	1800	120	70	81	6300	6100
KR-200-100	200	110	1033	1800	120	70	81	7200	7000
KR-200-125	200	135	935	1800	120	70	81	7200	7000
KR-200-150	200	160	724	1800	120	70	81	6700	6500
KR-250-100	250	110	1231	1800	140	83	87	8700	8400
KR-250-125	250	135	1160	1800	140	83	87	8700	8400
KR-250-150	250	160	1012	1800	120	70	81	7500	7200
KR-300-100	300	110	1453	1800	140	83	87	9000	8700
KR-300-150	300	160	1206	1800	140	83	87	8900	8600
KR-350-150	350	160	1402	1800	145	83	88	9500	9100



 [rogers-kseries.com](http://rogers-kseries.com)

Air delivery in accordance with ISO-9300 and ISO-1217. All data subject to change without notice.  
Allow at least 36" service clearance around assembly and 42" of clearance in front of electrical panels.

# ROGERS® KRV Series

## Performance Data and Dimensions

Model	Motor (HP)	Flow (ACFM)		Max Pressure (PSIG)	Length (IN)	Width (IN)	Height (IN)	A/C Weight (LBS)	W/C Weight (LBS)
		(MAX)	(MIN)						
KRV-20-100	20	94	17	110	72	40	48	2050	1850
KRV-20-125	20	74	31	135	72	40	48	2050	1850
KRV-20-150	20	69	31	160	72	40	48	1950	1850
KRV-25-100	25	113	31	110	72	40	51	2150	1950
KRV-25-125	25	102	31	135	72	40	51	2150	1950
KRV-25-150	25	92	40	160	72	40	51	2150	1950
KRV-30-100	30	135	36	110	72	40	51	2220	2020
KRV-30-125	30	126	44	135	72	40	51	2220	2020
KRV-30-150	30	111	40	160	72	40	51	2150	1950
KRV-40-100	40	186	46	110	77	52	53	3050	2850
KRV-40-125	40	167	45	135	77	52	53	3050	2850
KRV-40-150	40	142	43	160	77	52	53	3050	2850
KRV-50-100	50	246	60	110	77	52	53	3130	2930
KRV-50-125	50	206	63	135	77	52	53	3105	2905
KRV-50-150	50	176	60	160	77	52	53	3105	2905
KRV-60-100	60	299	68	110	91	58	68	4400	4300
KRV-60-125	60	286	65	135	91	58	68	4400	4300
KRV-60-150	60	231	71	160	91	58	68	4400	4300
KRV-75-100	75	375	77	110	91	58	68	4600	4500
KRV-75-125	75	350	74	135	91	58	68	4600	4500
KRV-75-150	75	289	71	160	91	58	68	4600	4500
KRV-100-100	100	509	111	110	99	62	72	5000	4850
KRV-100-125	100	463	105	135	99	62	72	5000	4850
KRV-100-150	100	387	113	160	91	58	68	4950	4800
KRV-125-100	125	553	108	110	99	62	72	5300	5150
KRV-125-125	125	545	105	135	99	62	72	5300	5150
KRV-125-150	125	465	144	160	99	62	72	5300	5150
KRV-150-100	150	727	165	110	120	70	81	6100	5850
KRV-150-125	150	718	166	135	120	70	81	6000	5750
KRV-150-150	150	656	221	160	120	70	81	6000	5750
KRV-200-100	200	1030	238	110	120	70	81	7200	6800
KRV-200-125	200	925	238	135	120	70	81	7200	6800
KRV-200-150	200	756	200	160	120	70	81	5625	5425
KRV-250-100	250	1242	285	110	142	76	86	9000	6800
KRV-250-125	250	1146	277	135	142	76	86	9000	8600
KRV-250-150	250	965	228	160	120	70	81	7600	7200
KRV-300-100	300	1476	355	110	142	76	86	9200	8800
KRV-300-125	300	1269	321	135	142	76	86	9200	8800
KRV-300-150	300	1215	267	160	142	76	86	9100	8700
KRV-350-100	350	1604	480	110	154	86	90	9600	9200
KRV-350-125	350	1477	463	135	154	86	90	9600	9200
KRV-350-150	350	1447	337	160	154	86	90	9500	9100



rogers-kseries.com

Air delivery in accordance with ISO-9300 and ISO-1217. All data subject to change without notice.  
Allow at least 36" service clearance around assembly and 42" of clearance in front of electrical panels.