


JAPANESE NATA TOOL

Handle Replacement Guide

BAREBONES

WHAT'S IN THE BOX?



KEY

- A. (1) Left Wooden Handle
- B. (1) Right Wooden Handle
- C. (2) Female Bolts
- D. (2) Male Bolts
- E. (1) Copper Sleeve
- F. (1) 3mm Hex Key Wrench

REMOVING THE ORIGINAL HANDLE

1. Using the 3mm Hex Key Wrench **F**, remove the bolts from the handle.

The handle is secured by a factory adhesive. Additional tools may be necessary to remove original parts.

INSTALLING THE REPLACEMENT HANDLE

(Optional) Apply a polyurethane-based adhesive on the flat side of the wooden handles. This helps secure the wood to the steel while also reducing vibration.

1. Insert both Female Bolts **C** into the rounded side of the Left Wooden Handle **A**.
2. Align bolts with holes on the left side of the blade.
3. Align Right Wooden Handle **B** on the right side of the blade.
4. Insert Male Bolts **D** and partially tighten.
(Recommended) Apply Loctite to the bolt threading.
5. Lightly apply adhesive to the outside of the Copper Sleeve **E** and insert it through the handle.
Wipe away any excess adhesive.
6. Tighten bolts until the handle is secured tightly. Do not overtighten or strip the bolts.

BAREBONES

Customer Service
1-855-895-7040

Email
info@barebonesliving.com

082620

Scan the QR code with your smartphone's camera for further instructions.



[BAREBONESLIVING.COM/INSTRUCTIONS](https://www.barebonesliving.com/instructions)