

Fitting Instructions for AIC0005 AIR INTAKE COVERS YAMAHA MT-09 '17-





<u>In This Kit There Should Be</u> 2x Air Intake Covers (1x Left & 1x Right)













Picture 4





Picture 5

Picture 6

TOOLS REQUIRED

• Socket set to include 3, 4mm A/F socket & wrench.

FITTING INSTRUCTIONS

- To fit the Air Intake Cover on the left side of the bike, the plastic bodywork around the air duct needs to be removed. To do this, remove the bolt shown in picture 1, along with the two push rivets on the back side, as arrowed in picture 2 and gently pull away, as shown in picture 3.
- With the plastic cover removed, the OEM grille can be accessed. To remove this, undo the two button head bolts that secure it in place, as shown in picture 4.
- Now fit the R&G Air Intake Cover, making sure the brushed side with the logo is facing towards the front of the motorcycle before refitting using the OEM bolts.
- Re-fit the plastic cover and then the two push rivets and bolt that secure the right side air duct in place.



• To fit the left sided Air Intake Cover in place, follow the same procedure on the other side of the bike.

ISSUE 1 29/06/2017 (AR)

CONSUMER NOTICE

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect. Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

R&G RACING RETURNS POLICY (NON-FAULTY GOODS)

Returns must be pre-authorised (if not pre-authorised the return will be rejected). Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor. Goods must be in re-sellable condition, in the opinion of R&G Racing. All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P – at the prevailing price at time of purchase). The customer must pay any and all carriage charges. No returns of discontinued products, unless within 14 days of purchase. This policy does not affect your statutory rights and does not refer to faulty goods.



NOTICE DE MONTAGE AIC0005 PROTECTIONS PRISES D'AIR YAMAHA MT-09 '17-





<u>Le kit doit contenir :</u> 2x Protections Prises d'air (1x Gauche & 1x Droite)






Photo 1 Photo 2







Photo 3

Photo 4





Photo 5

Photo 6

OUTILS REQUIS

• Clé à cliquet + douilles 3, 4mm.

NOTICE DE MONTAGE

- Pour monter la protection du côté gauche de la moto, le cache plastique autour du conduit d'air doit être enlevé. Pour cela, enlever le boulon indiqué sur la photo 1, avec les 2 rivets à l'arrière, comme indiqué sur la photo 2 puis tirer, voir photo 3.
- Une fois le cache plastique enlevé, la grille d'origine est accessible. Pour l'enlever, défaire les 2 boulons qui le fixent en place, voir photo 4.
- A présent, monter le cache de prise d'air R&G, en veillant à ce que le côté brossé avec le logo soit orienté vers l'avant de la moto avant de serrer à l'aide des boulons d'origine.
- Réinstaller le cache plastique puis les 2 rivets et le boulon qui fixent le côté droit du conduit d'air en place.



• Pour monter le cache de prise d'air du côté gauche en place, suivez la même procédure de l'autre côté de la moto.

ISSUE 1 29/06/2017 (AR)

CONSUMER NOTICE

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect. Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

R&G RACING RETURNS POLICY (NON-FAULTY GOODS)

Returns must be pre-authorised (if not pre-authorised the return will be rejected). Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor. Goods must be in re-sellable condition, in the opinion of R&G Racing. All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P – at the prevailing price at time of purchase). The customer must pay any and all carriage charges. No returns of discontinued products, unless within 14 days of purchase. This policy does not affect your statutory rights and does not refer to faulty goods.