

NEW RAGE CYCLES

INSTALLATION INSTRUCTIONS

BMW S1000R/RR

FENDER ELIMINATOR

- 1 Remove stock signal lenses with Philips head screw driver (picture 1)
- 2 Slide housing out and disconnect spade connectors (picture 2)
- 3 With a T20 torx, unbolt license plate light housing (picture 3)
- 4 Cut wires to plate light bulb, disconnecting plate light wires (picture 4)
- 5 Slide stock harness out and route underneath passenger seat
- 6 Unbolt stock fender with T25 torx bit (picture 5)
- 7 Remove 2 rubber grommets and slide over 2 studs on bike (picture 6)
- 8 Take new fender eliminator and with supplied hardware, bolt adjustable license plate bracket to it (picture 7/8)



NEW RAGE CYCLES

INSTALLATION INSTRUCTIONS

FENDER ELIMINATOR

- 9 Slide wires up underneath passenger seat and bolt new tail plate to bike with supplied M5 bolts (picture 9)
- 10 Make your connection for license plate light as follows, then shrink tube connections: (picture 10)
 - LH signal: Blue/Red Tracer NRC Red wire
 - LH Signal: Brown NRC Black wire
 - RH Signal: Blue NRC Red wire
 - RH Signal: Brown NRC Black Wire
 - Plate Light: Green NRC Red Wire
 - Plate Light: Brown NRC Black Wire
- 11 Zip tie wires neatly and put passenger seat back on bike

