


FITTING INSTRUCTIONS FOR ECC0366R RHS - ENGINE CASE COVER



THIS KIT CONTAINS THE ITEMS PICTURED AND LABELLED OVER PAGE.

SOME PARTS MAY BE SHOWN FOR CLARITY OF INSTRUCTIONS ONLY.

DO NOT PROCEED UNTIL YOU ARE SURE ALL PARTS ARE PRESENT.

PLEASE READ ALL INSTRUCTIONS BEFORE PROCEEDING.

IF IN ANY DOUBT WHEN FITTING OUR PRODUCTS, CONSULT ONE OF OUR DEALERS OR HAVE FITTED BY A QUALIFIED TECHNICIAN.

PLEASE NOTE THAT THE WAY THE KIT IS PACKED DOES NOT NECESSARILY REPRESENT THE WAY OF MOUNTING TO THE BIKE.

IN THE EVENT OF RUBBER WASHERS BEING USED TO HOLD COMPONENTS ONTO BOLTS,

THESE RUBBER WASHERS CAN BE THROWN AWAY.

DIGITAL COPIES OF THESE INSTRUCTIONS ARE AVAILABLE FROM:

WWW.RG-RACING.COM

R&G Racing

Tel: +44 (0)1420 89007 Fax: +44 (0)1420 87301 www.rg-racing.com Email: info@rg-racing.com



TOOLS REQUIRED

- 3mm ALLEN BIT (MONSTER 950/937)
 - T30 TORX BIT
 - 5mm ALLEN BIT

GENERAL TORQUE SETTINGS

M4 BOLT = 8Nm

M5 BOLT = 12Nm

M6 BOLT = 15Nm

M8 BOLT = 20Nm

M10 BOLT = 40Nm

M12 BOLT = 40Nm

LEGEND

ITEM NO.	DESCRIPTION	QTY
ITEM 1	ECC0366R ENGINE CASE COVER INCLUDING FITTED SPACERS	1
ITEM 2	M6 x 1.00 x 35mm CAP HEAD BOLTS	2
ITEM 3	M6 x 1.00 x 45mm CAP HEAD BOLTS	4
ITEM 4	M6 PENNY WASHERS	2

FITTING DIAGRAM 1



R&G Racing



FITTING DIAGRAM 2



FITTING INSTRUCTIONS

Ducati Monster 950 (PLUS)

- Please make sure the engine is cold before proceeding with the fitting of the R&G cover.
- Remove the OEM plastic engine case shroud.
- Replace the stand-offs which attach the OEM plastic shroud to the engine case cover with the 2 x provided M6 x 35mm bolts (ITEM 2) and 2 x M6 washers (ITEM 4), please refer to highlighted holes shown in <u>FITTING DIAGRAM 1</u>.
- To fit the R&G engine case cover remove the corresponding engine M6 engine case bolts as shown
 in <u>FITTING DIAGRAM 2</u>. Hold the Engine Case Cover loosely over the case to help identify the
 correct ones. DO NOT REMOVE ALL OF THE CASE BOLTS.
- Ensure the pre-fitted threaded spacers in the casing are hand tight against the inside of the **ECC0366R** Engine Case Cover (**ITEM 1**).
- Offer up the R&G cover to the engine and carefully fit it over the casing. Ensure that the three R&G bolt holes are lined up with the holes in the engine casing, and then push on as far as it will go.
- Fit the 4 x supplied M6 cap head bolts (**ITEM 3**) according to **FITTING DIAGRAM 2** through the Engine Case Cover and into the engine casing.
- Finally use a torque wrench set at 10 N/m (7 Lb/ft) to fully tighten each bolt.
- It is suggested that you check the tightness of the mounting bolts on a regular basis i.e. when cleaning or once a month.
- NOTE, for the cleaning of this product you should only use a soft polishing cloth and a mild general cleaning agent.
- AVOID HARMFUL CHEMICALS. IF IN DOUBT DO NOT USE AS THEY COULD ALTER THE STRENGTH OF THE COVER.
- R&G will accept no liability if the above procedure and torque settings are not followed.
- Check all components are secure and all bolts are tight before riding.



Ducati Multistrada V2 (S)

- To fit the R&G engine case cover remove the corresponding engine M6 engine case bolts as shown in **FITTING DIAGRAM 2**. Hold the Engine Case Cover loosely over the case to help identify the correct ones. DO NOT REMOVE ALL OF THE CASE BOLTS.
- Ensure the pre-fitted threaded spacers in the casing are hand tight against the inside of the **ECC0366R** Engine Case Cover (**ITEM 1**).
- Offer up the R&G cover to the engine and carefully fit it over the casing. Ensure that the three R&G bolt holes are lined up with the holes in the engine casing, and then push on as far as it will go.
- Fit the 4 x supplied M6 cap head bolts (**ITEM 3**) according to **FITTING DIAGRAM 2** through the Engine Case Cover and into the engine casing.
- Finally use a torque wrench set at 10 N/m (7 Lb/ft) to fully tighten each bolt.
- It is suggested that you check the tightness of the mounting bolts on a regular basis i.e. when cleaning or once a month.
- NOTE, for the cleaning of this product you should only use a soft polishing cloth and a mild general cleaning agent.
- AVOID HARMFUL CHEMICALS. IF IN DOUBT DO NOT USE AS THEY COULD ALTER THE STRENGTH OF THE COVER.
- R&G will accept no liability if the above procedure and torque settings are not followed.
- Check all components are secure and all bolts are tight before riding.

See more R&G products for your Motorcycle in the link below:

R&G Racing | All Products for <u>Ducati - Monster 950 PLUS (2021) (rg-racing.com)</u>

ISSUE 1 - 05/01/2022 (AO)

CONSUMER NOTICE


The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect. Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

R&G RACING RETURNS POLICY (NON-FAULTY GOODS)

Returns must be pre-authorised (if not pre-authorised the return will be rejected). Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor. Goods must be in re-sellable condition, in the opinion of R&G Racing. All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P – at the prevailing price at time of purchase). The customer must pay any and all carriage charges. No returns of discontinued products, unless within 14 days of purchase. This policy does not affect your statutory rights and does not refer to faulty goods.



NOTICE DE MONTAGE POUR ECC0366R PROTECTION CARTER MOTEUR CÔTÉ DROIT



CE KIT CONTIENT LES ARTICLES ILLUSTRES ET ETIQUETES SUR LA PAGE.

CERTAINES PARTIES PEUVENT ETRE PRESENTES UNIQUEMENT POUR LA CLARTE DES INSTRUCTIONS.

NE PAS PROCEDER AU MONTAGE TANT QUE VOUS N'ETES PAS SUR QUE TOUTES LES PIECES SOIENT PRESENTES.

VEUILLEZ LIRE TOUTES LES INSTRUCTIONS AVANT DE CONTINUER.

EN CAS DE DOUTE LORS DU MONTAGE DE NOS PRODUITS, CONSULTEZ UN DE NOS REVENDEURS OU FAITES APPEL A UN TECHNICIEN QUALIFIÉ.

VEUILLEZ NOTER QUE LA FAÇON DONT LE KIT EST EMBALLE NE REPRESENTE PAS NECESSAIREMENT LA MANIERE DE LE MONTER SUR LA MOTO.

SI DES RONDELLES EN CAOUTCHOUC SONT UTILISEES POUR MAINTENIR LES COMPOSANTS SUR LES BOULONS, ELLES PEUVENT ETRE JETEES.

NOTICE DISPONIBLE AU TELECHARGEMENT SUR:

WWW.RG-RACING.COM



OUTILS REQUIS

- CLÉ ALLEN 3mm (MONSTER 950/937)
 CLÉ TORX T30

 - CLÉ ALLEN 5mm

VALEURS DE SERRAGE

M4 BOULON = 8Nm

M5 BOULON = 12Nm

M6 BOULON = 15Nm

M8 BOULON = 20Nm

M10 BOULON = 40Nm

M12 BOULON = 40Nm

LÉGENDE

ARTICLE NO.	DESCRIPTION	QTÉ
ARTICLE 1	ECC0366R PROTECTION CARTER MOTEUR INCLUANT ENTRETOISES	1
ARTICLE 2	M6 x 1.00 x 35mm BOULONS	2
ARTICLE 3	M6 x 1.00 x 45mm BOULONS	4
ARTICLE 4	M6 PETITES RONDELLES	2

SCHÉMA DE MONTAGE 1



R&G Racing



SCHÉMA DE MONTAGE 2



NOTICE DE MONTAGE

Ducati Monster 950 (PLUS)

- Please make sure the engine is cold before proceeding with the fitting of the R&G cover.
- Remove the OEM plastic engine case shroud.
- Replace the stand-offs which attach the OEM plastic shroud to the engine case cover with the 2 x provided M6 x 35mm bolts (ITEM 2) and 2 x M6 washers (ITEM 4), please refer to highlighted holes shown in <u>FITTING DIAGRAM 1</u>.
- To fit the R&G engine case cover remove the corresponding engine M6 engine case bolts as shown
 in <u>FITTING DIAGRAM 2</u>. Hold the Engine Case Cover loosely over the case to help identify the
 correct ones. DO NOT REMOVE ALL OF THE CASE BOLTS.
- Ensure the pre-fitted threaded spacers in the casing are hand tight against the inside of the **ECC0366R** Engine Case Cover (**ITEM 1**).
- Offer up the R&G cover to the engine and carefully fit it over the casing. Ensure that the three R&G bolt holes are lined up with the holes in the engine casing, and then push on as far as it will go.
- Fit the 4 x supplied M6 cap head bolts (**ITEM 3**) according to **FITTING DIAGRAM 2** through the Engine Case Cover and into the engine casing.
- Finally use a torque wrench set at 10 N/m (7 Lb/ft) to fully tighten each bolt.
- It is suggested that you check the tightness of the mounting bolts on a regular basis i.e. when cleaning or once a month.
- NOTE, for the cleaning of this product you should only use a soft polishing cloth and a mild general cleaning agent.
- AVOID HARMFUL CHEMICALS. IF IN DOUBT DO NOT USE AS THEY COULD ALTER THE STRENGTH OF THE COVER.
- R&G will accept no liability if the above procedure and torque settings are not followed.
- Check all components are secure and all bolts are tight before riding.



Ducati Multistrada V2 (S)

- To fit the R&G engine case cover remove the corresponding engine M6 engine case bolts as shown in **FITTING DIAGRAM 2**. Hold the Engine Case Cover loosely over the case to help identify the correct ones. DO NOT REMOVE ALL OF THE CASE BOLTS.
- Ensure the pre-fitted threaded spacers in the casing are hand tight against the inside of the **ECC0366R** Engine Case Cover (**ITEM 1**).
- Offer up the R&G cover to the engine and carefully fit it over the casing. Ensure that the three R&G bolt holes are lined up with the holes in the engine casing, and then push on as far as it will go.
- Fit the 4 x supplied M6 cap head bolts (**ITEM 3**) according to **FITTING DIAGRAM 2** through the Engine Case Cover and into the engine casing.
- Finally use a torque wrench set at 10 N/m (7 Lb/ft) to fully tighten each bolt.
- It is suggested that you check the tightness of the mounting bolts on a regular basis i.e. when cleaning or once a month.
- NOTE, for the cleaning of this product you should only use a soft polishing cloth and a mild general cleaning agent.
- AVOID HARMFUL CHEMICALS. IF IN DOUBT DO NOT USE AS THEY COULD ALTER THE STRENGTH OF THE COVER.
- R&G will accept no liability if the above procedure and torque settings are not followed.
- Check all components are secure and all bolts are tight before riding.

Voir plus de produits R&G pour votre moto via ce lien :

R&G Racing | All Products for Ducati - Monster 950 PLUS (2021) (rg-racing.com)

ISSUE 1 - 05/01/2022 (AO)

CONSUMER NOTICE

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect. Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

R&G RACING RETURNS POLICY (NON-FAULTY GOODS)

Returns must be pre-authorised (if not pre-authorised the return will be rejected). Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor. Goods must be in re-sellable condition, in the opinion of R&G Racing. All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P – at the prevailing price at time of purchase). The customer must pay any and all carriage charges. No returns of discontinued products, unless within 14 days of purchase. This policy does not affect your statutory rights and does not refer to faulty goods.