



FITTING INSTRUCTIONS FOR R&G ARROWS EXHAUST (125cc) CAN COVER
(Code EP0013BK)

The R&G can cover is designed to fit in your preferred position on the exhaust muffler.

Open the jubilee clip completely, so that it is no longer continuous.

Place black “rubber” strip around the can, in the position intended for the jubilee clip of the can cover.

Cut the strip to size.

Locate the jubilee clip around the strip.

Check that the position of the can cover is as required. Re-tighten the jubilee clip in order to secure the can cover.

Cut off excess part of the jubilee clip to keep things neat, safe and tidy.

Please note that it is your responsibility to ensure that no part of the exhaust protector assembly fouls or comes into contact with other parts of the machine. Do not ride the motorcycle until this aspect has been verified and you have compressed the rear suspension (if appropriate to the design of the motorcycle) to test this thoroughly.

Consumer Insert

The catalogue description and any exhibition of samples are only broad indications of the Products and R & G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order.

The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R & G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes.

Where R & G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R & G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R & G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect.

Other than identified above and subject to R & G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned.

These terms do not affect the Buyer's statutory rights.

R&G RACING RETURNS POLICY (NON-FAULTY GOODS)

Returns must be pre-authorized (if not pre-authorized the return will be rejected)

Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor.

Goods must be in re-sellable condition, in the opinion of R&G Racing

All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P – at the prevailing price at time of purchase)

The customer must pay any and all carriage charges

No returns of discontinued products, unless within 14 days of purchase

This policy does not affect your statutory rights and does not refer to faulty goods

R&G Racing

Unit 5K, Blacknest Industrial Park, Blacknest Road, Alton, Hampshire, GU34 4PX

Tel: +44 (0)870 2206380 Fax: 01420 521101 www.rg-racing.com Email: info@rg-racing.com



Référence : EP0013BK

Protection de pot pour échappement 125cc ("Arrows" échappement)



Conseils de montage:

La protection de pot d'échappement R&G se place à l'endroit de votre choix (sur l'avant, au milieu, ou à l'arrière voir photos)

- 1- Desserrer complètement le collier de serrage.
 - 2- Positionner la protection sur le pot
 - 3- Serrer le collier légèrement
 - 4- Positionner la bande de caoutchouc à l'endroit désiré
 - 3- Couper éventuellement le surplus de caoutchouc et repositionner la bande entre le collier et le pot.
 - 4- Positionner la protection
 - 5- Serrer le collier de serrage
- ATTENTION de ne pas mettre en contact le collier de serrage directement sur votre échappement, car risque de rayures**
- 6- Vérifier la position de votre protection
 - 7- Ajuster ensuite la longueur du collier en coupant l'extrémité du collier non utilisé (Laisser environ 15-20 mm, ceci afin d'envisager le démontage et le remontage de votre protection)

R&G Racing

Unit 5K, Blacknest Industrial Park, Blacknest Road, Alton, Hampshire, GU34 4PX

Tel: +44 (0)870 2206380 Fax: 01420 521101 www.rg-racing.com Email: info@rg-racing.com