

FITTING INSTRUCTIONS FOR MBP0021BK MIRROR BLANKING PLATE YAMAHA YZF-R1 '15-



Please note that the way the kit is packed does not necessarily represent the way of mounting to the bike

THE PARTS SHOWN MAY BE REPRESENTATIVE ONLY (FOR CLARITY OF INSTRUCTIONS ONLY)

Please note that in cases where kits are packed with rubber washers holding the components onto the bolt – the rubber washers should be thrown away!

TOOLS REQUIRED


• 3 & 4mm A/F Allen key.











Picture 3

Picture 4

FITTING INSTRUCTIONS

- Remove the bolt and push rivet that secure the plastic cover in place, as arrowed in picture 1, before gently removing the plastic cover.
- Undo the plastic cable clip and disconnect the grey wiring connector for the indicator, as arrowed in picture 2.
- Remove the two nuts that secure the wing mirror in place from the underside of the front fairing, as shown in picture 3.
- Gently pull the wing mirror away and feed the wiring out through the hole, as shown in picture 4. Please note that disconnecting the front indicator may make the rear indicators flash twice as fast and may not be suitable for road use.
- Take one R&G blanking plate and position it in place on the front fairing and fit two M6 button head bolts and washers through the subframe mounting holes and into each threaded hole on the blanking plate from the underneath.
- Take the rubber bung supplied and push fit into the round hole beside the blanking plate.
- Re-fit the plastic cover along with the bolt and push rivet.
- Repeat the above for the opposite side.

ISSUE 1 12/08/2013 (AR)

R&G Racing

Unit 1, Shelley's Lane, East Worldham, Alton, Hampshire, GU34 3AQ



CONSUMER NOTICE


The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its apply to the Products other than those in R&O s order of confirmation and the Buyer confirms it has chosen the Products as being of merchantable quanty and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect. Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

R&G RACING RETURNS POLICY (NON-FAULTY GOODS)

Returns must be pre-authorised (if not pre-authorised the return will be rejected). Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor. Goods must be in re-sellable condition, in the opinion of R&G Racing. All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P – at the prevailing price at time of purchase). The customer must pay any and all carriage charges. No returns of discontinued products, unless within 14 days of purchase. This policy does not affect your statutory rights and does not refer to faulty goods.



INSTRUCTIONS DE MONTAGE POUR MBP0021BK PLAQUES OBTURATION RETROVISEURS YAMAHA YZF-R1 '15-



<u>La façon dont le kit est emballé ne correspond pas forcément à la façon de monter les pièces sur la moto.</u>

LES PARTIES PRESENTEES PEUVENT ETRE UNIQUEMENT REPRESENTATIVES (POUR LA CLARTE DES INSTRUCTIONS UNIQUEMENT

Notez que si les kits sont emballés avec des rondelles en caoutchouc servant à tenir les composants, ces rondelles doivent être jetées!

OUTILS REQUIS

• Jeu de clés Allen 3 et 4mm.












Photo 3

<u>INSTRUCTIONS DE MONTAGE</u>

- Enlever le boulon et le rivet qui fixe le cache plastic en place, voir photo 1, avant d'enlever le cache plastic.
- Enlever le clip cable et déconnectez le connecteur de fil gris du clignotant, voir photo 2.
- Enlever les 2 écrous qui fixent le rétroviseur en place au dessous de l'avant du carénage, voir photo 3.
- Enlevez délicatement le rétroviseur et passez les fils dans le trou, voir photo 4. Notez que déconnecter le clignotant avant va doubler l'éclairage des clignotants arrière, ce qui les rendra inutilisables sur la route, car cela peut être très dangereux pour les autres usagers.
- Prendre une plaque d'obturation R&G et positionnez la en place sur le carénage avant puis insérez 2 boulons M6 et des rondelles dans les trous de fixation du sous-cadre puis dans chaque trou fileté sur la plaque d'obturation, par dessous.
- Prendre le bouchon en caoutchouc fourni puis poussez le dans le trou à côté de la plaque d'obturation
- Remettre le cache plastic avec le boulon et le rivet.
- Répétez le processus pour le coté opposé.



ISSUE 1 12/08/2013 (AR)

CONSUMER NOTICE

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect. Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

R&G RACING RETURNS POLICY (NON-FAULTY GOODS)

Returns must be pre-authorised (if not pre-authorised the return will be rejected). Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor. Goods must be in re-sellable condition, in the opinion of R&G Racing. All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P – at the prevailing price at time of purchase). The customer must pay any and all carriage charges. No returns of discontinued products, unless within 14 days of purchase. This policy does not affect your statutory rights and does not refer to faulty goods.