

#### **Kit Contents**

Description	Part No	Pcs
Shock absorber	TR964	1
Sticker set Öhlins		1
Washer	03118-01	4
Owner's manual	07241-02	1
Tool preload adj.	03199-01	1

#### Note!

Please note that this image is a general representation of the product and may differ slightly from your product.

#### Note!

Please note that during storage and transportation, especially at high ambient temperature, some of the oil and grease used for assembling may leak and stain the packaging. This is in no way detrimental to the product, wipe off the excessive oil/grease with a cloth.

#### Note!

Before installing this product, check the contents of the kit. If anything is missing, please contact an Öhlins dealer

### **Marning!**

Before installing this product, read the Öhlins Owner's Manual. The shock absorber/front fork/steering damper is an important part of your vehicle and will affect the stability.

# **Shock absorber for Triumph**

TR 964

# **Mounting Instructions**



# MOUNTING INSTRUCTIONS

## **⚠** Warning!

It is advisable to have an Öhlins dealer install the shock absorber/front fork/steering damper.

## **▲** Warning!

If working on a raised vehicle, ensure it is securely supported so that it will not tip.

#### Note!

Before mounting this product clean the vehicle thoroughly.

#### Note!

When working on this product, always see the Vehicle Service Manual for vehicle specific procedures and important data.

#### 1

Put the motorcycle on a workstand so that the rear wheel barely touches the ground.

#### 2

Loosen and remove the original shock absorbers.

#### 3


Install the Öhlins shock absorbers in the same way as the original units, with the cylinder head up. If necessary, use the washers provided in this kit.

#### Note!

Lower the vehicle so that the suspension is slightly compressed before tightening the screws.

## Caution!

Ensure that all screws are tightened to the correct torque and that nothing fouls or restricts movement of the shock absorber/front fork/steering damper when the suspension is fully compressed or extended.



# MOUNTING INSTRUCTIONS


## **ADJUSTMENTS**

## ▲ Warning!

Before riding, always make sure that the basic settings made by Öhlins are according to recommended Setup Data. Read about adjustments and setting up in the Öhlins Owner's Manual before you make any adjustments. Contact an Öhlins dealer if you have any questions about setting up the shock absorber.

# Caution!

The drive belt tension shall only be adjusted when the original shock absorber is installed on the vehicle.



## **SET-UP DATA**

Length	369 +10/0	mm
Stroke	100	mm
Free spring length	230	mm
Rebound	20	clicks
Compression	15	clicks
Spring preload	17	mm

Ohlins products are subject to continuous improvement and development, therefore, although these instructions include the most up-to-date information available at the time of printing, minor updates may occur.

© Öhlins Racing AB. All rights reserved. Any reprinting or unauthorized use without the written permission of Öhlins Racing AB is prohibited.

To find the latest information contact an Öhlins distributor. Please contact Öhlins if you have any questions regarding the contents in this document.

Part no. MI\_TR964\_5 Issued 2017-01-01

Öhlins Racing AB Box 722 S-194 27 Upplands Väsby, Sweden Phone +46 8 590 025 00 fax +46 8 590 025 80





