



**Fitting Instructions for RAD0126BK Radiator Guard**  
**BMW F800GS 2008-**



**In This Kit There Should Be**  
**1x Radiator Guard (RAD0126BK)**  
**2x 100mm Lengths of self-adhesive Foam**

**TOOLS REQUIRED**

- T25 Torx bit.

**FITTING INSTRUCTIONS**

- To fit the radiator guard to the bike cut the foam strip provided into 10mm wide pieces and stick them to the back of the radiator guard frame, so that they sit between the radiator guard and the radiator.
- Remove the original plastic radiator guard by removing the two Torx 25 bolts from the top and sliding it upwards to release the two lower tabs.
- Fit the R&G Radiator Guard by locating the bottom tabs and re-fitting the original Torx 25 bolts to the two top mounts. Tighten bolts evenly.

ISSUE 1 26/06/2012 (AR)



**Instructions de montage**  
RAD0126BK Grille de protection radiateur  
BMW F800GS 2008-



**Le kit doit contenir:**

1x Grille de protection radiateur (RAD0126BK)  
2x 100mm Longueurs de mousse autocollante

**Outils requis**

- T25 Torx

**Instructions de montage:**

- Pour poser la protection sur la moto, couper la mousse autocollante fournie en pièces de 10mm puis collez ces pièces sur le cadre de radiateur, de façon à ce que la mousse soit située entre le radiateur, et la protection radiateur.
- Enlever la grille de protection radiateur d'origine en enlevant les 2 boulons Torx 25 du haut et en la glissant pour libérer les 2 onglets inférieurs.
- Poser la nouvelle grille de protection R&G en localisant les onglets du bas et en réutilisant les boulons Torx 25 d'origine pour les 2 supports du haut. Serrer les boulons de façon égale.

ISSUE 1 26/06/2012 (AR)



**Montageanleitung für den RAD0126BK Kühlerschutz**  
**BMW F800GS 2008-**



**Dieser Kit beinhaltet:**  
**1x Kühlerschutz (RAD0126BK)**  
**2x 100mm selbstklebende Schaumstoffstreifen**

**SIE BENÖTIGEN FOLGENDES WERKZEUG:**

- T25 Torx-Schlüssel

**MONTAGEANLEITUNG**

- Um den Kühlerschutz am Motorrad zu montieren, schneiden Sie zuerst die mitgelieferten Schaumstoffstreifen in 10 mm breiten Streifen und kleben Sie die auf der Rückseite des Kühlerschutz-Rahmens, so dass sie zwischen dem Kühlerschutz und dem Kühler angebracht sind.
- Entfernen Sie die Plastikverkleidung des Kühlers indem Sie die zwei Torx 25 Schrauben von oben lösen und den Kühler nach oben schieben, um die zwei unteren Laschen zu lösen.
- Montieren Sie den R&G Kühlerschutz – die unteren Laschen wieder einführen und die Originalschrauben (Torx 25 Schrauben) wieder an den Halterungen anbringen. Befestigen Sie alle Schrauben gleichmäßig.

AUSGABE 1 26/06/2012 (AR)

R&G Racing  
Unit 1, Shelley's Lane, East Worldham, Alton, Hampshire, GU34 3AQ  
Tel: +44 (0)1420 89007 Fax: +44 (0)1420 87301 [www.rg-racing.com](http://www.rg-racing.com) Email: [info@rg-racing.com](mailto:info@rg-racing.com)



#### **CONSUMER NOTICE**

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect. Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

#### **R&G RACING RETURNS POLICY (NON-FAULTY GOODS)**

Returns must be pre-authorised (if not pre-authorised the return will be rejected). Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor. Goods must be in re-sellable condition, in the opinion of R&G Racing. All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P – at the prevailing price at time of purchase). The customer must pay any and all carriage charges. No returns of discontinued products, unless within 14 days of purchase. This policy does not affect your statutory rights and does not refer to faulty goods.

R&G Racing

Unit 1, Shelley's Lane, East Worldham, Alton, Hampshire, GU34 3AQ

Tel: +44 (0)1420 89007 Fax: +44 (0)1420 87301 [www.rg-racing.com](http://www.rg-racing.com) Email: [info@rg-racing.com](mailto:info@rg-racing.com)