

# NEW RAGE CYCLES

## INSTALLATION INSTRUCTIONS

### SUZUKI GSXR 600/750

#### TAIL TIDY 2011-2017

- 1 Pop both side panels off (picture 1)
- 2 Remove seat bolts with 5mm allen key or socket (picture 2)
- 3 Remove phillips head screw and (4) push pins to remove side panel (pictures 3/4/5)
- 4 Find white plate light connector and unplug (picture 6)
- 5 With a 10mm socket, unbolt (4) bolts and remove stock fender (picture 7)

#### If installing standard mount:

- 1 With provided 1/4" spacers and M6x25 bolts, thread into lower holes but leave loose (pictures 8/9)
- 2 Take remaining (4) spacers and (2) bolts and thread into upper holes using 2 spacers below the bracket and 2 above (picture 10)
- 3 Run plate light wire through hole on tail tidy and up underneath seat and plug into OEM connector (picture 11)



# NEW RAGE CYCLES

## INSTALLATION INSTRUCTIONS

### TAIL TIDY 2011-2017

#### If installing tucked mount:

- 1 With provided 1/4" spacers and M6x25 bolts thread into lower holes but leave loose (pictures 8/9)
- 2 Take remaining (2) spacers and (2) bolts and thread into upper holes sandwiching license plate bracket and tail tidy bracket (picture 12)
- 3 Tighten all (4) bolts
- 4 Turn key on and test light
- 5 Reinstall side pods and seat

