



Fitting Instructions for OCG0020BK Oil Cooler Guard
DUCATI MULTISTRADA 1200 '10-



In This Kit There Should Be
1x Oil Cooler Guard (OCG0020)
1x 100mm Length of self-adhesive foam



Picture 1



Picture 2



Picture 3



Picture 4



Picture 5



Picture 6



Picture 7



Picture 8



Picture 9



Picture 10

TOOLS REQUIRED

- Socket set to include 3 & 4mm A/F socket & wrench.
 - 8mm spanner or socket & wrench.

FITTING INSTRUCTIONS

- To fit the oil cooler guard to the bike cut the foam strip provided into 10mm wide pieces and stick them to the back of the oil cooler guard frame, so that they sit between the oil cooler guard and the radiator.
- Remove the two bolts that mount the plastic under the nose of the bike, as arrowed in picture 1.
- Remove the two 4mm headed bolts that sit within the nose of the bike, as shown in picture 2.
- Remove the four 3mm head bolts that secure the black fairing panel in place on both sides of the bike, as shown in picture 3.
- The front nose of the bike should now pull apart, as shown in picture 4, giving access to the oil cooler.
- Remove the bolt in the top left corner of the oil cooler, as shown in picture 5.
- Offer the R&G oil cooler guard (OCG0020BK) into place on the oil cooler radiator, ensuring the mount in the top right is located over the metal boss first, as shown in picture 6 & 7.
- The mount on the top left of the oil cooler should now align with the rubber mount of the oil cooler. Re-fit the original bolt through the oil cooler guard mount and tighten into the oil cooler, as shown in picture 8. With the top two mounts located, the lower mount should align over the rubber mount on the oil cooler, as shown in picture 9.
- Re-fit the bodywork together, paying particular attention that the plastic boss on the underside cover locates through the lower mount on the oil cooler guard and sits inside the rubber mount on the oil cooler.
- Ensure the oil cooler guard is correctly mounted before re-fitting all the bolts that secure the bodywork in place before tightening.

ISSUE 1 14/05/2014 (AR)

Digital copies of these instructions are available to download from www.rg-racing.com

CONSUMER NOTICE

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or

R&G Racing
Unit 1, Shelley's Lane, East Worldham, Alton, Hampshire, GU34 3AQ
Tel: +44 (0)1420 89007 Fax: +44 (0)1420 87301 www.rg-racing.com Email: info@rg-racing.com



warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect. Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

R&G RACING RETURNS POLICY (NON-FAULTY GOODS)

Returns must be pre-authorised (if not pre-authorised the return will be rejected). Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor. Goods must be in re-sellable condition, in the opinion of R&G Racing. All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P – at the prevailing price at time of purchase). The customer must pay any and all carriage charges. No returns of discontinued products, unless within 14 days of purchase. This policy does not affect your statutory rights and does not refer to faulty goods.



INSTRUCTIONS DE MONTAGE POUR OCG0020BK
Grille de protection du refroidisseur d'huile
DUCATI MULTISTRADA 1200 '10-



Le kit doit contenir :
1x Grille de protection (OCG0020)
1x 100mm Longueur de mousse autocollante



Photo 1



Photo 2



Photo 3



Photo 4



Photo 5



Photo 6



Photo 7



Photo 8



Photo 9



Photo 10

OUTILS REQUIS

- Clés à douille 3 & 4mm.
- Clé à molette 8mm.

Instructions de montage :

- Couper la mousse en bandeaux de 10mm puis collez ces bandeaux au bas du support de refroidisseur d'huile, de façon à ce que ces bandeaux se situent entre la protection refroidisseur d'huile et le refroidisseur d'huile
- Enlever les 2 boulons qui fixent le plastic sous le nez de la moto (photo 1).
- Enlever les 2 boulons 4mm qui se placent dans le nez de la moto (photo 2).
- Enlever les 4 boulons 3mm qui fixent le carénage noir en place des 2 cotés de la moto (photo 3).
- Le nez de la moto doit maintenant pouvoir se séparer du reste, comme sur la photo 4, libérant l'accès au refroidisseur d'huile.
- Enlever le boulon sur le coin supérieur gauche du refroidisseur d'huile, comme sur la photo 5.
- Mettre la protection refroidisseur d'huile R&G en place (OCG0020BK) sur le radiateur refroidisseur d'huile, en veillant à ce que le support en haut à droite soit d'abord placé autour du patron en métal comme sur les photos 6 & 7.
- Le support en haut à gauche du refroidisseur d'huile doit maintenant s'aligner avec le support en caoutchouc du refroidisseur d'huile. Remettre le boulon d'origine à travers le support de protection refroidisseur d'huile puis serrer dans le refroidisseur d'huile, comme sur la photo 8. Une fois les 2 supports positionnés, le support inférieur doit



s'aligner autour du support de caoutchouc sur le refroidisseur d'huile, comme sur la photo 9.

- Remettre les carénages, en faisant particulièrement attention à ce que le patron en plastic sur la partie inférieure du cache se place à travers le support inférieur sur la protection refroidisseur d'huile mais également à l'intérieur du support de caoutchouc sur le refroidisseur d'huile.
- Veiller à ce que la protection du refroidisseur d'huiles soit correctement positionnée avant de resserrer tous les boulons qui fixent le carénage en place.

ISSUE 1 14/05/2014 (AR)

Ces instructions de montage sont disponibles en téléchargement sur www.rg-racing.com

CONSUMER NOTICE

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect. Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

R&G RACING RETURNS POLICY (NON-FAULTY GOODS)

Returns must be pre-authorized (if not pre-authorized the return will be rejected). Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor. Goods must be in re-sellable condition, in the opinion of R&G Racing. All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P – at the prevailing price at time of purchase). The customer must pay any and all carriage charges. No returns of discontinued products, unless within 14 days of purchase. This policy does not affect your statutory rights and does not refer to faulty goods.

R&G Racing

Unit 1, Shelley's Lane, East Worldham, Alton, Hampshire, GU34 3AQ

Tel: +44 (0)1420 89007 Fax: +44 (0)1420 87301 www.rg-racing.com Email: info@rg-racing.com