# SAFETY DATA SHEET

### Section 1 - Chemical Product and Company Information

Product Name: ORANGE Product Code: GPCX-6230

Manufactured By:

General Color, LLC 350 Bridge Street Minerva, OH 44657

Emergency Phone: 330-868-4161

#### Section 2 - Hazards Identification

#### **GHS Ratings:**

There are no GHS ratings that apply to this product at this time

#### **GHS Hazards**

There are no GHS hazards that apply to this product at this time

#### **GHS Precautions**

P281

Use personal protective equipment as required

P501

Dispose of contents/container in accordance with Federal, State & Local regulations.

#### Section 3 - Composition Information on Ingredients

Chemical Name	CAS number	Weight Concentration %
Kaolin	1332-58-7	
Polyethylene	9002-88-4	

#### Section 4 - First Aid Measures

Inhalation - If symptoms are experienced, move victim to fresh air.

Eye Contact - Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention if irritation occurs.

Skin Contact - In case of skin contact, remove contaminated clothing. Flush the skin with large amounts of water to cool the affected tissue and polymer. Do not attempt to peel polymer from skin.

Ingestion - Adverse health effects due to ingestion are not anticipated.

Notes to Physician: Treat symptomatically.

#### Section 5 - Fire Fighting Measures

Flash Point; No Data Available

LEL: N/A

UEL: N/A

Flammable Limits: N/A

Extinguishing Media: Use carbon dioxide (CO2), "alcohol" foam, dry chemical, or water spray/water fog

extinguishing systems.

SDS for: GPCX-6230

Page 1 of 4

Printed: 4/20/2023 at 12:20:33PM

Unusual Fire or Explosion Hazards: No specific fire or explosion hazard.

Hazardous Combustion Products: Carbon Dioxide, Carbon Monoxide, Monomer Fragments Fire Fighting: If evacuation of personnel is necessary, evacuate to an upwind area. Decontaminate personnel and equipment with a water wash-down after fire and smoke exposure.

Fire Fighting Equipment: Firemen and emergency responders: wear full turnout gear or Level A equipment, including positive-pressure, self-contained breathing apparatus (SCBA).

#### Section 6 - Accidental Release Measures

SPILL AND LEAK PROCEDURES: Sweep or vaccuum up spill and place in drums for recovery or disposal.

Dispose of the waste in compliance with all Federal, State, Regional, and Local regulations.

#### Section 7 - Handling and Storage

Handling Precautions: Keep material off walking surfaces, it may create a slipping hazard. Use in well ventilated area. Control spilled material to prevent runoff to the sewers and the environment.

Storage Requirements: Protect containers against physical damage, store in dry area away from feed and food products. Keep containers sealed to avoid contamination.

Regulatory Requirements: No data found.

# Section 8 - Exposure Controls / Personal Protection

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
Kaolin 1332-58-7	15 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable fraction)	2 mg/m3 TWA (particulate matter containing no asbestos and <1% crystalline silica, respirable particulate matter)	NIOSH: 10 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable dust)
Polyethylene 9002-88-4	Not Established	Not Established	Not Established

Engineering Controls: Ensure adequate ventilation.

Ventilation: Use only with adequate ventilation, i.e., ventilation in compliance with occupational exposure limits.

Administrative Controls: No data found. Protective Gloves: Wear Protective Gloves.

Eye Protection: Wear Eye Protection.

Contaminated Equipment: Dispose of the waste in compliance with all Federal, State, Regional and Local regulations.

#### Section 9 - Physical and Chemical Properties

This mixture typically exhibits the following properties under normal circumstances:

Appearance: Color	Odor: Slight

SDS for: GPCX-6230

Printed: 4/20/2023 at 12:20:33PM

Vapor Pressure: N/A Vapor Density: N/A Specific Gravity: 2.09

Freezing point: Not Available

Boiling range: N/A

Evaporation rate: Not Available

Explosive Limits: N/A

Autoignition temperature: 349°C

Viscosity: Not Available

Odor threshold: Not Available

pH: Not Available

Melting point: Not Available

Solubility: Not Available

Flash point: No Data Available

Flammability: Not Available

Partition coefficient (n- Not Available

octanol/water):

**Decomposition temperature:** Not Available

Lbs VOC/Gallon Less Water 0.00

#### Section 10 - Stability and Reactivity

Stability:

**UNSTABLE** 

Hazardous polymerization will not occur.

#### Section 11 - Toxicological Information

# Mixture Toxicity Component Toxicity

1332-58-7

Kaolin

Oral LD50: 5,000 mg/kg (Rat) Dermal LD50: 5,000 mg/kg (Rat)

9002-88-4

Polyethylene

Oral LD50: 8 g/kg (Rat)

Specific Target Organ Toxicity: No specific data.

Respiratory System

#### **Effects of Overexposure**

Carcinogenicity: Not classified.

**CAS Number** 

Description

% Weight

Carcinogen Rating

Acute Toxicity: Not classified

No known significant effects or critical hazards.

Short Term Exposure Immediate or Delayed Effects: No specific data.

Long Term Exposure Immediate or Delayed Effects: No specific data.

# Section 12 - Ecological Information

Ecological Information: No additional information available

#### **Component Ecotoxicity**

#### Section 13 - Disposal Considerations

Disposal must be made in accordance with Federal, State, and Local regulations.

SDS for: GPCX-6230

Page 3 of 4

Printed: 4/20/2023 at 12:20:33PM

## Section 14 - Transport Information

<u>Agency</u> DOT

**Proper Shipping Name** 

UN Number Packing Grou Hazard Class

None

None

None

Section 15 - Regulatory Information

Not Regulated

Country

Regulation

All Components Listed as Active

#### Section 16 - Other Information

For Manufacturing Use Only.

This information is believed to be accurate at the time of preparation; however it is not guaranteed to be so and no liability is assumed by General Color, LLC regarding its use.

Reviewer Revision

Date Prepared: 4/20/2023

SDS for: GPCX-6230