



3529 SyntiSOL™ PP Film w/EasyTack™ Satin 13 mil

PRODUCT DESCRIPTION

3529 SyntiSOL™ PP Film with EasyTack™ is a tear resistant, smooth polypropylene display film with a “low glare” satin, water resistant, scratch resistant coating and a proprietary low tack self-adhesive. The special low-tack glue allows for easy, 100% bubble-free application and residue-free removal on glass and other flat surfaces. The SyntiSOL™ family of products lay extremely flat, both on the printer and final application. Sihl 3529 is compatible with solvent and UVC.



ADVANTAGES

- EasyTack™ - Proprietary Removable Adhesive
- Tear Resistant Polypropylene Base
- Kiss-Cut Liner
- Water Resistant & Scratch Resistant
- Fast Drytime
- Alternative to Scrim Banner and PSA Vinyl

TECHNOLOGIES

 Solvent

APPLICATIONS

- Print and Contour Cut for Window or Wall Graphics
- “Fathead” type graphics

PHYSICAL PROPERTIES

Caliper	13 mil (8 mil polypro / 5 mil liner)
Basis Weight	220 g/m ²
Gloss (60°)	15
Opacity	>96%

*All values listed are target values

ADDITIONAL INFORMATION

- Available widths: 36”/ 42”/ 50” - 3” core
- For additional product information please call **1-800-366-7393** or visit our website **www.sihlinc.com** where you can also find an authorized Sihl reseller near you.