

PRISMJET 109 FLOOR OVERLAMINATION

TECHINCAL DATA SHEET

PrismJET 109 is a 5.0 mil, scratch-resistant, clear overlaminate with a textured matte finish.

PrismJET 109 has a permanent acrylic pressure sensitive adhesive formulated for exceptional clarity. Produced on a 1.5 mil polyester clear liner, the laminate has an extremely smooth adhesive coating. *PrismJET 109* has been rated for slip resistance based on multiple testing methods.*

FILM	
Face Film	Clear Polymeric
Film Finish	Textured Matte
Film Thickness	5.0 mil / 127 µm
ADHESIVE	
Adhesive Type	Permanent Solvent Acrylic
Adhesive Thickness	1.4-1.6 / 36 - 41 µm
Adhesive Color	Clear
LINER	
Liner Weight	N/A
Liner Type	Clear Polyester
PERFORMANCE GUIDANCE	
Shelf Life	1 Year
Storage Temp/Rel. Humidity	70°F / 50%



PrismJET 109 is available in sizes of 51-inch and 54-inch.

*The PrismJET 109 slip-resistance certification is for dry conditions only. Laminated media may still be slippery when wet

SUBSTRATES	APPLICATIONS
<ul style="list-style-type: none"> Printed Graphics 	<ul style="list-style-type: none"> Point of Purchase/Retail Signage Floor Graphics Social Distancing Directional Signage Use with PrismJET 210 and 212

* In every application where a "sealant" is called for, the floor finish (sealers, coating, paint, etc.) must be firmly attached to the subfloor.