

PRISMJET 210 MATTE PRINTABLE FLOOR VINYL TECHINCAL DATA SHEET

PrismJET 210 is a 3.4 mil, matte, intermediate calendered printable vinyl engineered for floor graphics.

PrismJET 210 has a removable, high-performance, pressure-sensitive acrylic adhesive on a 90# layflat release liner. For floor graphics, lamination with a UL rated slip-resistant film is recommended.*

FILM	
Face Film	Polymeric Calendered
Film Finish	Matte
Film Thickness	3.4 mil / 86 µm
ADHESIVE	
Adhesive Type	Removable Emulsion Acrylic
Adhesive Thickness	0.8-1.0 / 20-25 µm
Adhesive Color	Clear
LINER	
Liner Weight	90#
Liner Type	White 2-Sided PE-Coated Kraft
PERFORMANCE GUIDANCE	
Shelf Life	1 Year
Storage Temp/Rel. Humidity	70°F / 50%
Indoor Durability	Up to 5 years
Removability	Up to 6 months



PrismJET 210 is available in sizes of 48-inch and 54-inch.

*The PrismJET 109 slip-resistance certification is for dry conditions only. Laminated media may still be slippery when wet

SUBSTRATES*	APPLICATIONS	INK TYPE
<ul style="list-style-type: none"> • Tile (Smooth) • Concrete (Smooth) • Vinyl (Smooth) • Cement (Smooth) • Stone/Marble (Smooth) • Wood (Smooth) 	<ul style="list-style-type: none"> • Point of Purchase/Retail Signage • Floor Graphics • Social Distancing Directional Signage • Arena and Event Floor Graphics 	<ul style="list-style-type: none"> • Solvent • Eco-Solvent • Latex • UV Curable • Screenprinting

* In every application where a "sealant" is called for, the floor finish (sealers, coating, paint, etc.) must be firmly attached to the subfloor.