



100% Cotton	100% Polyester	Poly/Cotton Blends	Nylon	Lycra®/Spandex	Leather	Sublimated Polyester	Home Iron Compatible	CPSIA Certified	Temperature (EasyPress® users add approximate 30°)	Pressure	Time (Seconds)	Peel Carrier
-------------	----------------	--------------------	-------	----------------	---------	----------------------	----------------------	-----------------	--	----------	----------------	--------------

SISER® HEAT TRANSFER VINYL REFERENCE

EasyWeed®	🔴	🔴	🔴			🔴	🔴	🔴	305° F / 150° C	medium	10-15	hot or cold
EasyWeed® EcoStretch™	🔴	🔴	🔴		🔴	🔴		🔴	250° F / 121° C	medium	5-15	hot
EasyWeed® Electric	🔴	🔴	🔴			🔴		🔴	305° F / 150° C	medium	10-15	hot or cold
EasyWeed® Extra		🔴	🔴	🔴		🔴		🔴	305° F / 150° C	light/medium	10-15	hot or cold
EasyWeed® Sub Block		🔴				🔴	🔴	🔴	265° F / 130° C	medium/firm	10-15	warm
EasyWeed® Adhesive	🔴	🔴	🔴					🔴	275° F / 135° C	medium	5-10	hot
EasyReflective®	🔴	🔴	🔴	🔴				🔴	305° F / 150° C	medium	15	warm
Easy® Puff	🔴	🔴	🔴					🔴	280° F / 138° C	medium	6-8	hot
Easy® Puff Metallic	🔴	🔴	🔴					🔴	280° F / 138° C	medium	10 (2x)	hot or warm
Easy® Glow	🔴	🔴	🔴					🔴	305° F / 150° C	medium	15	cold or warm
Aurora™	🔴	🔴	🔴					🔴	305° F / 150° C	medium	15	cold
BlackBoard®	🔴	🔴	🔴					🔴	275° F / 135° C	medium	15	warm
Brick® 600	🔴	🔴	🔴					🔴	310° F / 155° C	medium/firm	15-20	cold
Glitter	🔴	🔴	🔴			🔴		🔴	320° F / 160° C	medium	15-20	warm
Holographic	🔴	🔴	🔴			🔴		🔴	320° F / 160° C	medium	10-15	cold
Metal	🔴	🔴	🔴					🔴	305° F / 150° C	medium	10-15	cold
Sparkle™	🔴	🔴	🔴					🔴	305° F / 150° C	medium	15	hot or cold
StripFlock® Pro	🔴	🔴	🔴			🔴		🔴	310° F / 155° C	medium	15	warm
Twinkle™	🔴	🔴	🔴					🔴	305° F / 150° C	medium/firm	15	warm
EasySubl®	🔴	🔴	🔴					🔴	310° F / 155° C	medium	15	warm
EasyPatterns® Plus	🔴	🔴	🔴			🔴		🔴	305° F / 150° C	medium	10-15	hot or cold



CPSIA certified means that this product has been tested in a CPSC approved independent lab and is certified Phthalate & Lead Free and is safe for application on children's products.



Ceramic	Drywall	Glass	Metal	Plastic	Wood	CPSIA Certified	Surface Characteristics	Thickness	Durability	Cutting Blade Recommendation
---------	---------	-------	-------	---------	------	-----------------	-------------------------	-----------	------------	------------------------------

SISER® EASYPSV® REFERENCE

EasyPSV® Starling™	🔴		🔴	🔴	🔴	🔴	matte/gloss	3 mils / 76.2 microns	3-6 year	45°
EasyPSV® Glitter	🔴		🔴	🔴	🔴	🔴	smooth gloss	3 mils / 76.2 microns	5 year	45°
EasyPSV® Etch	🔴		🔴	🔴	🔴	🔴	matte	3 mils / 76.2 microns	5-7 year	45°
EasyPSV® Glow	🔴		🔴	🔴	🔴	🔴	gloss	4.2 mils / 107 microns	indoor usage only	45°
EasyPSV® Brushed	🔴		🔴	🔴	🔴	🔴	gloss	6.9 mils / 175 microns	indoor/outdoor	45°
EasyPSV® BlackBoard®	🔴	🔴	🔴	🔴	🔴	🔴	matte	5 mils / 127 microns	3 year Outdoor 5 year Indoor Removable	45°
EasyPSV® Holographic	🔴	🔴	🔴	🔴	🔴	🔴	pearlescent	3.15 mils / 80 microns	1 yr. Removable indoor use only	45°
EasyPSV® Patterns	🔴		🔴	🔴	🔴	🔴	patterned	3.94 mils / 100 microns	3 year	45°

Please test for compatibility on your surface before committing to decoration. Not recommended for use with dishwasher (except for Starling) or microwave.