

ATT 450

Adhesive power:
MEDIUM-STRONG
Thickness:
100 microns

This medium-strong tack application tape makes light work of transferring most of our printable media.

The backing on the adhesive surface protects logos during storage and stacking.

ATT 500L

Adhesive power:
LOW
Thickness:
110 microns

This application tape has a low tack and allows you to transfer most of our printable products without difficulty.















The product does not come on a liner/ carrier and is therefore faster and easier to use since it is not necessary to remove the carrier before applying it on the printed design.

ATT 600

Adhesive power:
STRONG
Thickness:
170 microns

This application tape has a very high tack and allows you to transfer all our printable products without difficulty. It perfectly resists to heat pressing and avoids bubbles of air to be trapped.

In addition, the sticky part is protected by a polyester carrier thus, you make sure logos made from printable products are not stuck one to the other when stored or piled.

Printable HTV	Reference	Low Tack ATT500L	Medium Tack ATT450	High Tack ATT600	No Tape Needed
HotmarkPrint Revolution	1798				
Hotmarkprint	1792				
Hotmarkprint Sir	1795				
Bestprint	1722				
Bestprint Sir	1723				
Clearprint Matte	1690				
Alljet Dark	803				
Newjet	804				
Subliflok	1602				
Sublitex	1603				

 The most appropriate tape  Alternative tape  Use without tape

NOTE: We highly recommend that you perform tests before production.