GOTENNO PRO DEPLOYMENT KIT 2^{°°} Data Sheet

Introducing the goTenna Pro Deployment Kit 2[™] (goKit 2[™]). Now featuring a ruggedized Samsung tablet, the goKit 2[™] is a portable charging kit for up to 30 Pro X and Pro X2 devices that can be used as an off-grid mobile command center to provide unprecedented situational awareness at the tactical edge without cell service or satellite connectivity. Made in USA.

New Features

Tablet Operation

Device management, deployment tools, and other apps hosted on an included and removable Samsung Android Tablet.

Mobile Command Functionality

Deploy ATAK or goTenna Pro app within the goKit for mission control from anywhere. Tablet provides capability to enable connectivity of nodes to a centralized TAK server for relaying critical information to central command.

Key Benefits

Scalable

Fully equip up to 30 users from a single kit.

Rapidly Deployable

Configure and deploy within minutes, 100% off-grid.

Portable

Less than 25 lbs. Flight-ready as a carry-on or checked item. Internal battery meets IATA and TSA regulations.

Charging Station -

Charge Pro X and X2 devices, tablets, phones, and other USB devices.

Portal Sync

Seamlessly updates configurations, apps, and more with your goTenna Portal account.



Distribute mission information and device configuration over a WiFi hotspot through a single deployment pack, including encryption keys, frequency sets, map files, and more.

Security and Durability

Enhanced security and AES256 encryption via Android. The Samsung Android Tab Active 3 is IP68-rated and MIL-STD 810H ruggedized.





goTenna pro deployment kit 2^{°°}

Specifications

General	
Case Dimensions WxHxD	19.75 x 16 x 7.62 in / 50.16 x 40.64 x 18.36 cm
Weight	goKit base unit only: 20.9 lb / 9.48 kg goKit with 30 Radios and Tablet: 33.0 lb / 14.9 kg
CE	Approved
Capacity	Up to 30 Pro X Devices
goKit Internal Battery Capacity	Li-Ion 14.8V, 4 cell, 99 Wh
Interfaces	
Tablet	Samsung Galaxy Tab Active 3
Display	8″ 1920 x 1200 Capacitive Touch Screen
Internet Connectivity	WiFi, Cellular (customer supplied)
Internal Storage	64GB
External Storage	microSD
Connectors	
AC Power Input (US, EU, AU/NZ)	110/220V AC (IEC Standard Connector)
DC Auxiliary Power Input	10 - 18V DC (Car Charger Port)
USB Ports (for peripheral charging needs)	4x USB 2.0

