SAFETY DATASHEET LEMONADE WASH

SDS No. VR-1001-2 Date 06/02/2022

Section 1 – Identification of the Mixture and Supplier

Product Name: Voodoo Ride® Lemonade Foam-N-Wash

Part Numbers: VR-1001, VR-1001-GAL

SDS Number: VR-1001-2

CAS Number: Mixture – Not Established **Product Use**: Automotive Detailing

Manufacturer/Supplier's Details:

Voodoo Ride Inc. 13000 Temple Ave.

City of Industry, CA 91746

TEL: 1-800-237-7560 | (626)937-6988

Email: <u>info@VoodooRide.com</u> **Web:** www.VoodooRide.com

Section 2 - Hazard Identification

Note: This product is a consumer product and is labeled in accordance with the Consumer Product Safety Commission regulations and not OSHA regulations. The requirements for the labeling of consumer products take precedence over OSHA labeling so the actual product label may be different from what is shown.

GHS Classification of the Substance or Mixture				
Health	Environmental	Physical		
Eye Irritant – Category 2B Acute Toxicity/Oral- Category 5	None Known	None Known		

GHS Label Elements

None Signal Word: Warning

Hazard Statements:

H200s = Physical H300s = Health H400s = Environmental

H303 - May be harmful if swallowed

H320 - Causes eye irritation

HMIS Health -0 Fire -0 React -0 PPE† Sec.8

Precautionary Statements:

P200s = Prevention P300s = Response P400s = Storage P500s = Disposal

P26 - Wash hands thoroughly after handling

P281 – Use personal protective equipment as required

P301+312 – If swallowed: Call a poison center or doctor/physician if you feel unwell/rinse mouth with plenty of water

P305+351+338 – If in the eyes: rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue

P337+313 - If eye irritation persists: Get medical advice/attention

Section 3 – Composition/Information on Ingredients

Composition Comments:

*CANADA GHS: The exact percentage (concentration) of composition has been withheld as a trade secret.

US GHS: The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with

paragraph (i) of §1910.1200.

**Sodium C10-16 Sulfonate surfactant blend is purchased from a vendor as a mixture has many CAS numbers for the same product. The supplier holds the exact percentage composition as a trade secret, therefore the CAS values are approximate based on the supplier's datasheets, with Sodium C10-16 sulfonate being the primary ingredient of the mixture. Cocamide DEA concentration is estimated at less than 2%

weight

Section 4 - First Aid Measures

Inhalation: If breathing is difficult or irritating, move to fresh air immediately. If

symptoms persist SEEK MEDICAL ATTENTION IMMEDIATELY.

Skin Contact: Rinse thoroughly with soap and water. Seek medical attention if any redness or irritation continues.

Eye Contact: Immediately flush eyes with water for at least 15 minutes, holding back

eyelids from eyeball to ensure thorough rinsing. Seek medical attention if

any irritation or redness persists.

Ingestion: SEEK MEDICAL ATTENTION IMMEDIATELY. Do not induce vomiting

unless directed by medical personnel.

Note to Physicians: Treat Symptoms

Special Precautions/Procedures: After first-aid, get appropriate in-plant, paramedic, or

community medical support.

See Section 11 for more detailed information on health effects and symptoms.

Section 5 – Fire Fighting Measures

Extinguishing Media: Water spray, dry chemical, carbon dioxide, and alcohol foam. **Unusual Fire or Explosion Hazards:** Low hazard. This product would not be expected to burn or ignite unless most of the water is evaporated or boiled away, or the

liquid exceeds flashpoint. The remaining organic compounds may be ignitable. Heated vapors may be ignited by flames or sparks.

Health -0 Fire -0 React - 0

Hazardous Combustion Products: Hydrogen Chloride, Oxides of Nitrogen, Carbon Monoxide, and Carbon Dioxide.

Fire-Fighting Instructions: Use extinguishing media appropriate for the surrounding fire. Use water spray to cool nearby containers and structures exposed to fire. Do not release runoff from fire control methods to sewers or waterways. Keep personnel removed and upwind.

Fire-Fighting Equipment: Because fire may produce toxic thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full facepiece operated in pressure-demand or positive-pressure mode with full protective clothing.

Section 6 - Accidental Release Measures

Personal Precautions: Wear appropriate personal protective equipment as conditions warrant. (Review Section 8) Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Follow all precautions for handling the spill. (Review Section 7) Isolate spill or leak area and deny entry to all untrained personnel.

Emergency Procedures: Isolate spill or leak. Ventilate spill area if fumes are present, and keep unauthorized personnel away. Stay upwind of any fumes.

Spill/Leak Containment and Cleanup: All equipment used when handling the spill must be grounded or non-sparking tools. Stop leak if you can do it without risk. Small spills: take up with sand or other non-combustible absorbent material and place into approved containers for later disposal. Large spills: dike area with non-combustible absorbent material to contain the spill. Prevent spills from entering sewers, waterways, or low areas. Transfer spilled liquid and diking material to suitable approved containers for recovery or disposal. Do not flush spilled material into a sewer. Neutralize the remaining spilled material with a diluted solution of acid if the spilled material is alkaline or a diluted solution caustic if the spilled material is acidic. Clean up residue with soap and water. Do not flush to sewer or waterways. Prevent release to the environment.

Refer to Section 13 for Proper Disposal of Spilled Material.

Regulatory Requirements: Any environmental release of a material that could cause harm to people or the environment must be reported immediately to the National Response Center (NRC) and the appropriate state and local agencies.

Section 7 – Handling and Storage

Handling Precautions: Wear appropriate personal protective equipment as conditions warrant. (Review Section 8) Avoid eye contact. Wash thoroughly after handling. Do not breathe vapors or mists; use with adequate ventilation. Do not ingest. Do not cut, grind, puncture, drill, or weld on or near containers. Keep containers closed when not in use. Do not use pressure to empty containers. Always loosen closure cautiously when opening. Use in an area that will allow for evaporation runoff. Prevent soil contamination and entry into storm and floor drains, streams, and any body of water.

Storage Requirements: Store in a cool, dry, well-ventilated area away from direct sunlight, heat, flames, and sparks in a controlled environment. Store at ambient or lower temperatures. Keep from freezing. Do not store near combustible materials or liquids. Do not store in open, unlabeled, or mislabeled containers. Empty containers retain product vapor and residue. Follow all label warnings even after the container is empty. Keep out of reach of children

Exposure Limits / Guidelines Ingredient Name	OSHA PEL	ACGIH TLV
Water	None Established	None Established
Cocamide DEA	None Established	None Established
Sodium Sulfonate	None Established	None Established

Engineering Controls for Ventilation: Ensure good general ventilation. Use local exhaust ventilation to draw spray, mists, and vapors away from the work area to prevent inhalation of product fumes. Provide general or local exhaust ventilation systems using corrosive resistant materials to maintain airborne contaminants below any recommended or standard occupational exposure limits. Local exhaust ventilation is preferred because it prevents contamination dispersion into the work area by controlling it at its source. Ventilation guidelines may be found in OSHA Regulations (29CFR 1910.94) or publications such as the American Conference of Governmental Industrial Hygienists.

PERSONAL PROTECTIVE EOUIPMENT

Respiratory Protection: None required under normal circumstances of use if maintaining airborne contaminant concentrations below standard occupational exposure limits. If using in a confined area and fumes are present, use a respirator. Seek professional advice before respirator selection and use. Follow OSHA respirator regulations (29 CFR 1910.34) and if necessary, wear an MSHA/NIOSH- approved respirator. Select respirator based on its suitability to provide adequate worker protection for given working conditions, level of airborne contamination, and presence of sufficient oxygen. For emergency or non-routine operations (cleaning spills, reactor vessels, or storage tanks) wear an SCBA. **Warning! Airpurifying respirators do not protect workers in oxygen-deficient atmospheres.** If respirators are used, OSHA requires a written respiratory protection program that includes at least: medical certification, training, fit- testing, periodic environmental monitoring, maintenance, inspection, cleaning, and convenient, sanitary storage areas.

Eye Protection: None required for normal use. To avoid eye contact, wear chemical safety goggles per OSHA eye and face protection regulations. (29CFR 1910.133) Contact lenses are not eye protective devices. Appropriate eye protection must be worn instead of, or in

conjunction with contact lenses. Have an eye wash station available where eye contact can occur.

Skin Protection: None required for normal use. To avoid prolonged or repeated skin contact, if needed, wear chemically protective gloves impervious to conditions of use. Neoprene, nitrate, or butyl type rubber gloves. Additional protection may be necessary to prevent skin contact, including use of apron, face shield, boots, or full body protection. A safety shower should be in the general work area.

General Hygiene: Wash thoroughly with soap and water after handling and before eating, drinking, or using tobacco. Launder contaminated work clothes before reuse and keep personal protective equipment clean.

Section 9 – Physical and Chemical Properties

Appearance: Yellow Transparent Liquid

Odor: Lemon Scented

pH: 6-8

Freeze Point: Estimated at 20-25°F (-6°C)

Boiling Point: Estimated above 212°F

(93°C)

Odor Threshold: Not Determined Vapor Pressure: Not Determined Vapor Density (Air=1): Less than 1

Specific Gravity ($H_20=1$, at $72^{\circ}F$): 1.0-

1.08

Water Solubility: 100%

Flash Point: Estimated at above 200°F

Upper/Lower Flammability: Not Determined

Auto Ignition Temp: Not Determined **Evaporation Rate (Water=1):** Not

Determined

Partition Coefficient, N-Octanol/Water: Not

Determined

Decomposition Temp: Not Determined

Viscosity: 80-100KU @25C

VOC Content: None

Section 10 – Stability and Reactivity

Reactivity: No dangerous reactions under normal conditions of use.

Chemical Stability: Stable in a controlled environment away from direct sunlight and

stored at ambient temperatures.

Hazard Reactions: Hazardous reactions will not occur.

Conditions to Avoid: Avoid using or storing product in elevated temperatures or near

heat, sparks, open flames, or ignition sources.

Incompatible Materials: Strong oxidizers, reducing agents, and acids.

Hazardous Decomposition Products: Carbon monoxide, carbon dioxide, and other toxic

gases.

Section 11 – Toxicological Information

*Specific tests have not been conducted on this product. Our evaluations are based on information from similar products, the ingredients, and technical literature. Data for this material has been used to estimate the symptoms and effects of exposure.

Information on toxicological effects Acute toxicity

Components Species Test Results

Cocamide DEA (CAS 68603-42-9)

Acute			
Dermal	Rabbit	>2g/kg	
LD50			
Eyes	Eye contact with liquid or mists can cause irritation.		
Skin	Skin LD50: Brief contact should not cause irritation to the skin. Prolonged contact may cause skin irritation resulting in redness or dryness of the skin. This product is not known to be a sensitizer.		
Inhalation	Inhalation LC50: The product is not expected to presif the work area is properly ventilat vapors, mists, or fumes will cause is creating headaches and nausea.	ed. Prolonged inhalation of	
Ingestion	Oral LD50: Ingestion is not regarded as a signifrom normal use. Ingestion will cau and digestive tract. Abdominal pain, nausea, and vomit	ise irritation of the mouth, throat,	
Chronic Toxicity	There are no reports of long-term a attributable to the use of this type contain ingredients, or which are depotentially may affect the following respiratory system.	of product. The product does erived from components, that	
Carcinogenicity	Carcinogenicity Suspected of causing IARC Monographs. Overall Evaluation Cocamide DEA (CAS 68603-42-9) and humans OSHA Specifically Regulated Substantial Not regulated. US. National Toxicology Program (Not listed.	on of Carcinogenicity 2B Possibly carcinogenic to ances (29 CFR 1910.1001-1052)	
Mutagenicity	There are no reports of mutagenic of this type of product or from its ingr		
Reproductive Toxicity	There are no reports of reproductive this type of product or from its ingr		

Section 12 - Ecological Information

^{*}Specific tests have not been conducted on this product. Our evaluation is based on information from similar products, the ingredients, and technical literature. This information should be used only for a small truck spill and not meant to address discharges to sewers or treatment plants. Data for this material has been

used to estimate its environmental impact.

Ecotoxicological data See below

Componer	nts	Species	Test Results
Cocamide [DEA (CAS 68603-42-9)		
Aquatic			
Acute			
Algae	EC50	Algae	< 10mg/L, 72 Hours
_		Crustacea	<10mg/L, 48 Hours
Crustacea	LC50	Fish	<10mg/L, 96 hours
Fish	LC50		

Toxicity: This material has a moderate potential for toxicity. Moderate biochemical oxygen demand and moderate potential to cause oxygen depletion in aqueous systems. A moderate potential to affect aquatic organisms. Harmful to aquatic life if released directly into the environment.

Environmental Degradation: This product is readily biodegradable when diluted with large amounts of water; this material released into the environment is not expected to have a significant impact. (Minimum of 50 parts water to 1 part product). A moderate potential to persist in the environment.

Soil Absorption/Mobility: This material is expected to be mobile in soil and not expected to absorb suspended solids or sediments in the water. A moderate potential to affect plant life.

Section 13 – Disposal Considerations

Waste Disposal Methods: As sold, this product when discarded or disposed of is a non-hazardous waste. The transportation, storage, treatment, and disposal of this waste material must be conducted in compliance with (40CFR 261, 262, 263, 264, 268, 270). Do not discharge this material into lakes, streams, ponds, or other waters. Do not discharge this material into sewer systems without the approval from local sewage treatment plant authority. Care must be taken to prevent environmental contamination from the use of this material. If material is not approved to be discharged into the sewer system, contact a licensed waste management contractor for detailed recommendations for disposal. Follow all applicable Federal, state, and local regulations. This non-hazardous liquid can be incinerated if it meets all OSHA and EPA regulations. Incinerate at a licensed waste disposal site with approved environmental authority. If this product is altered, it is the responsibility of the user to determine whether the material meets the criteria for hazardous waste at the time of disposal.

Disposal Regulatory Requirements: Follow applicable NRC, CERCLA, SARA, and RCRA regulations.

Container Cleaning and Disposal: Before cleaning or disposing of the container, use caution when handling an empty container (possible combustible vapors). Do not use pressure to empty containers. Empty containers retain product vapors or residue that could be combustible. Follow all label warnings even after the container is empty. Do not cut, weld, braze, solder, drill, grind, or expose empty containers to heat, flames, or other sources of ignition. Follow applicable Federal, state, and local OSHA and EPA regulations.

Section 14 – Transport Information

Domestic US Road Transportation DOT (49 CFR 172.101):

Not Regulated as a Hazardous Material or Dangerous Goods.

Canadian Road Transportation (TDG):

Not Regulate as a Hazardous Material or Dangerous Goods.

Ocean Transportation (IMO.IMDG) (49 CFR 172.101):

Not Regulated as a Hazardous Material or Dangerous Goods.

Air Transportation (ICAO/IATA) (49 CFR 172.101):

Not Regulated as a Hazardous Material or Dangerous Goods.

Section 15 – Regulatory Information

U.S. Federal Regulations

Toxic Substance Control Act (TSCA) Inventory Status:

The components for this product are on the TSCA Inventory or are exempt from TSCA Inventory requirements.

Super Fund Amendments & Reauthorization Act (SARA) Title III:

Section 302 Extremely Hazardous Substances (40 CFR 355):

Components: Concentration:

None None

Section 311/312 Hazard Class (40 CFR 370):

Immediate Hazard:NoDelayed Hazard:NoFire Hazard:NoPressure Hazard:NoReactive Hazard:No

Section 313 Toxic Chemicals (40 CFR 372):

Components: Reporting Threshold: 1.0%

None None

Comprehensive Environmental Response and Liability Act (CERCLA): Section 304

Hazardous Substances (40 CFR 302):

Components: Reporting Oty:

None None

OSHA Air Contaminants Standard (20 CFR 1910.1000):

The following components of this product are listed as having limits for air contaminants: None

California Proposition 65

State Regulations

The product contains the following chemicals known to the state of California to cause cancer and or birth defects based on maximum impurity levels of components: California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

Diethanolamine (CAS 111-42-2)

<u>Pennsylvania, Massachusetts & New Jersey Hazardous Substance List Right to Know:</u>

The following components in this product are listed as hazardous at levels that require reporting.

None

International Regulations

Canadian Environmental Protection Act (CEPA):

The components for this product are included on the Canadian Domestic Substances List. (DSL)

Canadian Workplace Hazardous Materials Information System (WHIMS):

None

Section 16 - Other Information

Prepared By: Voodoo Ride Inc Revision Date: 06/01/2022

Disclaimer: This material safety data sheet and the information it contains are offered to you in good faith as a guide to the safe use of the product and are believed to be accurate to the best of our knowledge. Not all information in this data sheet is supported by specific testing and the evaluations are based on information from similar products, the ingredients, and technical literature. The data contained herein is provided for your guidance only when handling the specific material designated in this MSDS and does not relate to any process or to use with any other materials. We recommend testing to determine the suitability of this product for your particular purpose before use. No responsibility is accepted that the information is sufficient, correct, and complete in all circumstances, as to the safety and health of individuals, disposal of materials, and protection of the environment. The user must consider this MSDS as a supplement to other information required to make an independent determination to assure compliance with applicable laws and regulations when handling this material. The data in this document is provided without any representation or warranty expressed or implied regarding its accuracy or correctness. No warranty, either expressed or implied of merchantability or fitness or any nature is made concerning any product referred to herein. The manufacturer does not assume responsibility and expressly disclaims liability for loss, damage, or expense arising out of or in any way connected with the handling, storage, use, or disposal of the products referred to herein. Manufacturer urges persons receiving this data to make their determination as to the information's suitability and completeness for their application.