

SAFETY DATASHEET SEALANT-N-PROTECTANT

SDS No. VR-1008-1

Date: 03/03/2021

Section 1 – Identification of the Mixture and Supplier

Product Name: Voodoo Ride ® Sealant-N-Protectant

Part Numbers: VR-1008

SDS Number: VR-1008-1

CAS Number: Mixture – Not Established

Product Use: Automotive Detailing

Manufacturer/Supplier's Details:

Voodoo Ride

13000 Temple Ave.

City of Industry, CA 91746

TEL: 1-800-237-7560 | (626)937-6988

Email: info@VoodooRide.com

Web: www.VoodooRide.com

EMERGENCY PHONE NUMBER (INFOTRAC) 1-800-535-5053 or 352-323-3500

Section 2 – Hazard Identification

Note: This product is a consumer product and is labeled under the Consumer Product Safety Commission regulations and not OSHA regulations. The requirements for the labeling of consumer products take precedence over OSHA labeling, so the actual product label may be different from what is shown.

GHS Classification of the Substance or Mixture		
Health	Environmental	Physical
Eye Irritant – Category 2B Acute Toxicity/Oral- Category 5	None Known	None Known

GHS Label Elements

None **Signal Word: Warning**

Hazard Statements:

H200s = Physical H300s = Health H400s = Environmental

H303 – May be harmful if swallowed.

H320 – Causes eye irritation.

Precautionary Statements:

P200s = Prevention P300s = Response P400s = Storage P500s = Disposal

P264 – Wash hands thoroughly after handling

P281 – Use personal protective equipment as required.

P301+312 – If swallowed: Call a POISON CONTROL CENTER or doctor/physician. Rinse mouth.

P305+351+338 – If in eyes: rinse cautiously with water for several minutes. Remove contact lenses if present and if easy to do. Continue rinsing.

P337+313 – If eye irritation persists, get medical advice/attention.

P403+233 – Store in a well-ventilated place. Keep the container tightly closed.

P501 – Dispose of contents/container according to local regulations.

HMIS
Health -0
Fire -0
React -0
PPE Sec.8

Section 3 – Composition/Information on Ingredients

Ingredient Name	CAS No.	% WT.
Aluminum Oxide (non-fibrous)	25155-30-0	< 10*
Petroleum Distillates	4742-88-7	10-20*
Triethanolamine	102-71-6	.1-2*
Poly(oxy-1,2-ethanediyl),alpha-(2-propylheptyl)-omega hydroxy	160875-66-1	< 1*
Other non-hazardous Ingredients		≥ 97*

Composition Comments ***CANADA GHS:** The exact percentage (concentration) of composition has been withheld as a trade secret.
US GHS: The exact percentage (concentration) of composition has been withheld as a trade secret under paragraph (I) of §1910.1200.

Section 4 – First Aid Measures

Inhalation If breathing is difficult or irritating, move to fresh air immediately. If symptoms persist, seek medical attention.

Skin Contact Rinse thoroughly with soap and water. Seek medical attention if any redness or irritation continues.

Eye Contact Immediately flush eyes with water for at least 15 minutes, holding back eyelids from eyeball to ensure thorough rinsing. Seek medical attention if any irritation or redness persists.

Ingestion Seek medical attention immediately. Do Not Induce Vomiting unless directed by medical personnel.

Note to Physicians: Treat Symptoms

Special Precautions/Procedures: After first-aid, get appropriate in-plant, paramedic, or community medical support.

See Section 11 for more detailed information on health effects and symptoms.

Section 5 – Fire-Fighting Measures

Extinguishing Media: Water, Dry Chemical, Carbon Dioxide, and Alcohol Foam.

Unusual Fire or Explosion Hazards: Low hazard. This product would not be expected to burn or ignite unless a majority of the water is evaporated or boiled away, or liquid exceeds flashpoint. The remaining organic compounds may be ignitable. Flames or sparks may ignite heated vapors.

Hazardous Combustion Products: Hydrogen Chloride, Oxides of Nitrogen, Carbon Monoxide, and Carbon Dioxide.

Fire-Fighting Instructions: Use the appropriate Extinguishing Media to surround the fire. Spray water to cool nearby containers and structures exposed to fire. Do not release runoff from fire control methods to sewers or waterways. Keep personnel removed and upwind.

Fire-Fighting Equipment: Because fire may produce toxic thermal decomposition products, wear a self-contained

breathing apparatus (SCBA) with a full-facepiece operated in pressure-demand or positive-pressure mode with full protective clothing.

NFPA

Health -1
Fire -0
React - 0

Section 6 – Accidental Release Measures

Personal Precautions: Wear appropriate personal protective equipment as conditions warrant. (Review Section 8) Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Follow all precautions for handling the spill. (Review Section 7) Isolate spill or leak area and deny entry to all untrained personnel.

Emergency Procedures: Isolate spill or leak. Ventilate spill area if fumes are present, keep unauthorized personnel away. Stay upwind of any fumes.

Spill/Leak Containment and Cleanup: All equipment used when handling the spill must be grounded or non-sparking tools. Stop leak if you can do it without risk. Small spills: take up with sand or other non-combustible absorbent material and place into approved containers for later disposal—large spills: dike area with non-combustible absorbent material to contain the spill. Prevent spills from entering sewers, waterways, or low areas. Transfer spilled liquid and diking material to suitable approved containers for recovery or disposal. Do not flush spilled material into a sewer. Neutralize remaining spilled material with a diluted solution of acid if the spilled material is alkaline or a diluted solution caustic if the spilled material is acidic. Clean up residue with soap and water. Do not flush to sewer or waterways. Prevent release to the environment.

Refer to Section 13 for Proper Disposal of Spilled Material.

Regulatory Requirements: Any environmental release of a material that could cause harm to people or to the environment must be reported immediately to the National Response Center (NRC) and to the appropriate state and local agencies.

Section 7 – Handling and Storage

Handling Precautions: Wear appropriate personal protective equipment as conditions warrant. (Review Section 8) Avoid eye contact. Wash thoroughly after handling. Do not breathe vapors or mists; use with adequate ventilation. Do not ingest. Do not cut, grind, puncture, drill, or weld-on or near containers. Keep containers closed when not in use. Do not use pressure to empty containers. Always loosen closure cautiously when opening. Use in an area that will allow for evaporation runoff. Prevent soil contamination and entry into storm and floor drains, streams, and into any body of water.

Storage Requirements: Store in a cool, dry, well-ventilated area away from direct sunlight, heat, flames, and sparks in a controlled environment. Store at ambient or lower temperatures. Keep from freezing. Do not store near combustible materials or liquids. Do not store in open, unlabeled, or mislabeled containers. Empty containers retain product vapor and residue. Follow all label warnings even after the container is empty. Keep out of reach of children.

Section 8 – Exposure Controls/Personal Protection

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Triethanolamine	102-71-6	ACGIH	TWA:5 mg/m ³	
Aluminum Oxide (non-fibrous)	1344-28-1	OSHA	TWA(as total dust):15 mg/m ³ ;TWA(respirable fraction):5 mg/m ³	
Aluminum, insoluble compounds	1344-28-1	ACGIH	TWA(respirable fraction):1 mg/m ³	A4: Not class. as human carcin
Kerosine (petroleum)	64742-88-7	ACGIH	TWA (as total hydrocarbon vapor, non-aerosol):200 mg/m ³	A3: Confirmed animal carcin., SKIN

Engineering Controls for Ventilation: Ensure good general ventilation. Use local exhaust ventilation to draw spray, mists, and vapors away from the work area to prevent inhalation of product fumes. Provide general or local exhaust ventilation systems using corrosive resistant materials to maintain airborne contaminants below any

recommended or standard occupational exposure limits. Local exhaust ventilation is preferred because it prevents contamination dispersion into the work area by controlling it at its source. Ventilation guidelines may be found in OSHA Regulations (29CFR 1910.94) or publications such as the American Conference of Governmental Industrial Hygienists.

PERSONAL PROTECTIVE EQUIPMENT

Respiratory Protection: None required under usual circumstances of use if maintaining airborne contaminant concentrations below standard occupational exposure limits. If used in a confined area and fumes are present, use a respirator. Seek professional advice before respirator selection and use. Follow OSHA respirator regulations (29 CFR 1910.34) and, if necessary, wear an MSHA/NIOSH- approved respirator. Select respirator based on its suitability to provide adequate worker protection for given working conditions, level of airborne contamination, and presence of sufficient oxygen. For emergency or non-routine operations (cleaning spills, reactor vessels, or storage tanks), wear an SCBA. **Warning! Air-purifying respirators do not protect workers in oxygen-deficient atmospheres.** If respirators are used, OSHA requires a written respiratory protection program that includes medical certification, training, fit-testing, periodic environmental monitoring, maintenance, inspection, cleaning, and convenient, clean storage areas.

Eye Protection: None required for regular use. To avoid eye contact, wear chemical safety goggles per OSHA eye and face protection regulations. (29CFR 1910.133) Contact lenses are not eye protective devices. Appropriate eye protection must be worn instead of or in conjunction with contact lenses. Have an eyewash station available where eye contact can occur.

Skin Protection: None required for regular use. If needed, to avoid prolonged or repeated skin contact, wear chemically protective gloves impervious to conditions of use neoprene, nitrile, or butyl type rubber gloves. Additional protection may be necessary to prevent skin contact, including the use of an apron, face shield, boots, or full body protection. A safety shower should be located in the general work area.

General Hygiene: Wash thoroughly with soap and water after handling and before eating, drinking, or using tobacco. Launder contaminated work clothes before reuse and keep personal protective equipment clean.

Section 9 – Physical and Chemical Properties

<p>Appearance: Milky Liquid Odor: New Car Fragrance pH: 6-8 Freeze Point: Estimated at 20-25°F (-6°C) Boiling Point: Estimated above 212°F (93°C) Odor Threshold: Not Determined Vapor Pressure: Not Determined Vapor Density (Air=1): Less than 1 Specific Gravity (H₂O=1, at 72°F): 1.0-1.03 Water Solubility: 100%</p>	<p>Flash Point: Estimated at above 200°F Upper/Lower Flammability: Not Determined Auto Ignition Temp: Not Determined Evaporation Rate (Water=1): Not Determined Partition Coefficient, N-Octanol/Water: Not Determined Decomposition Temp: Not Determined Viscosity: 50-100KU @25C VOC Content: Volatile Organic Compounds 15.2 % weight [<i>Test Method:</i> calculated per CARB title 2] [<i>Details:</i> VOC of concentrate] Volatile Organic Compounds 149.81 g/l [<i>Test Method:</i> calculated SCAQMD rule 443.1] Percent volatile 73.8 % weight [<i>Test Method:</i> Estimated] VOC Less H₂O & Exempt Solvents 1.97 g/l [<i>Test Method:</i> calculated SCAQMD rule 443.1]</p>
---	--

Section 10 – Stability and Reactivity

Reactivity: No dangerous reactions under normal conditions of use.

Chemical Stability: Is stable in a controlled environment away from direct sunlight and stored at ambient temperatures.

Hazard Reactions: No hazardous reactions will occur.

Conditions to Avoid: Avoid storing product in elevated temperatures or near heat, sparks, open flames, or ignition sources.

Incompatible Materials: Strong oxidizers, reducing agents, and acids.

Hazardous Decomposition Products: Carbon monoxide, carbon dioxide, and other toxic gases.

Section 11 – Toxicological Information

***Specific tests have not been conducted on this product. Our evaluations are based on information from similar products, the ingredients, and technical literature. Data for this material has been used to estimate the symptoms and effects of exposure.**

Information on toxicological effects

Acute toxicity Acute Toxicity

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation- Vapor(4 hr.)		No data available; calculated ATE >50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Aluminum Oxide (non-fibrous)	Dermal		LD50 estimated to be > 5,000 mg/kg
Aluminum Oxide (non-fibrous)	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 2.3 mg/l
Aluminum Oxide (non-fibrous)	Ingestion	Rat	LD50 > 5,000 mg/kg
Petroleum Distillates	Inhalation- Vapor		LC50 estimated to be 20 - 50 mg/l
Petroleum Distillates	Dermal	Rabbit	LD50 > 3,000 mg/kg
Petroleum Distillates	Ingestion	Rat	LD50 > 5,000 mg/kg
Triethanolamine	Dermal	Rabbit	LD50 > 2,000 mg/kg
Triethanolamine	Ingestion	Rat	LD50 9,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Aluminum Oxide (non-fibrous)	Rabbit	No significant irritation
Petroleum Distillates	Rabbit	Irritant
Triethanolamine	Rabbit	Minimal irritation

Serious Eye Damage/Irritation

Name	Species	Value
Aluminum Oxide (non-fibrous)	Rabbit	No significant irritation
Petroleum Distillates	Rabbit	No significant irritation
Triethanolamine	Rabbit	Mild irritant

Skin Sensitization

Name	Species	Value
Petroleum Distillates	Guinea pig	Not classified
Triethanolamine	Human	Not classified

Respiratory Sensitization

For the component/components, either no data are currently available, or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Aluminum Oxide (non-fibrous)	In Vitro	Not mutagenic
Petroleum Distillates	In vivo	Not mutagenic
Petroleum Distillates	In Vitro	Some positive data exist, but the data are not sufficient for classification
Triethanolamine	In Vitro	Not mutagenic
Triethanolamine	In vivo	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Aluminum Oxide (non-fibrous)	Inhalation	Rat	Not carcinogenic
Petroleum Distillates	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Petroleum Distillates	Inhalation	Human and animal	Some positive data exist, but the data are not sufficient for classification
Triethanolamine	Dermal	Multiple animal species	Not carcinogenic
Triethanolamine	Ingestion	Mouse	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity

Reproductive and Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
Petroleum Distillates	Inhalation	Not classified for development	Rat	NOAEL 2.4 mg/l	During Organogenesis
Triethanolamine	Ingestion	Not classified for development	Mouse	NOAEL 1,125 mg/kg/day	During Organogenesis

Target Organ(s)

Specific Target Organ Toxicity - Single Exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Petroleum Distillates	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Petroleum Distillates	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
Petroleum Distillates	Inhalation	nervous system	Not classified	Dog	NOAEL 6.5 mg/l	4 hours
Petroleum Distillates	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	

Specific Target Organ Toxicity – Repeated Exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Aluminum Oxide (non- fibrous)	Inhalation	pneumoconiosis	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
Aluminum Oxide (non- fibrous)	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure
Petroleum Distillates	Inhalation	nervous system	Not classified	Rat	LOAEL 4.6 mg/l	6 months
Petroleum Distillates	Inhalation	kidney and/or bladder	Not classified	Rat	LOAEL 1.9 mg/l	13 weeks
Petroleum Distillates	Inhalation	respiratory system	Not classified	Multiple animal species	NOAEL 0.6 mg/l	90 days

Petroleum Distillates	Inhalation	bone, teeth, nails, and/or hair blood liver muscles	Not classified	Rat	NOAEL 5.6 mg/l	12 weeks
Petroleum Distillates	Inhalation	heart	Not classified	Multiple animal species	NOAEL 1.3 mg/l	90 days
Triethanolamine	Dermal	kidney and/or bladder	Not classified	Multiple animal species	NOAEL 2,000 mg/kg/day	2 years
Triethanolamine	Dermal	liver	Not classified	Mouse	NOAEL 4,000 mg/kg/day	13 weeks
Triethanolamine	Ingestion	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 1,000 mg/kg/day	2 years
Triethanolamine	Ingestion	liver	Not classified	Guinea pig	NOAEL 1,600 mg/kg/day	24 weeks

Aspiration Hazard

Name	Value
Petroleum Distillates	Aspiration hazard

Eyes Eye contact with liquid or mists can cause irritation.

Skin **Skin LD50:**
Brief contact should not irritate the skin. Prolonged contact may cause skin irritation resulting in redness or dryness of the skin. This product is not known to be a sensitizer.

Inhalation **Inhalation LC50:**
The product is not expected to present a significant inhalation hazard if the work area is adequately ventilated. Prolonged inhalation of vapors, mists, or fumes will cause irritation of the respiratory tract creating headaches and nausea.

Ingestion **Oral LD50:**
Ingestion is not regarded as a significant health hazard likely to arise from regular use. Ingestion will cause irritation of the mouth, throat, and digestive tract. Abdominal pain, nausea, and vomiting may occur.

Chronic Toxicity There are no reports of long-term adverse toxic effects in man attributable to the use of this type of product. The product contains ingredients, or which are derived from components that may affect the following target organs: eyes, skin, and respiratory system.

Carcinogenicity IARC, ACGIH, NTP, and OSHA do not list any of the ingredients as a potential carcinogen.

Mutagenicity There are no reports of mutagenic effects attributable to the use of this type of product or from its ingredients.

Reproductive Toxicity There are no reports of reproductive effects attributable to the use of this type of product or from its ingredients.

Section 12 – Ecological Information

***Specific tests have not been conducted on this product. Our evaluation is based on information from similar products, the ingredients, and technical literature. This information should be used only for a small truck spill and not meant to address discharges to sewers or treatment plants. Data for this material has been used to estimate its environmental impact.**

Ecotoxicological data

See below

Components	Species	Test Results
Toxicity Poly(oxy-1,2-ethanediyl),alpha-(2-propylheptyl)-omega hydroxyl		
Acute toxicity to aquatic invertebrates		
Material is slightly toxic to aquatic organisms on an acute basis (LC50/EC50 between 10 and 100 mg/L in the most sensitive species tested).		
Based on data from similar materials		
EC50, Daphnia Magna (Water flea), 48 Hour, > 10 -100 mg/l		
Acute toxicity to algae/aquatic plants		
Based on data from similar materials EC50, Desmodesmus subspicatus (green algae), 72 Hour, > 10 -100 mg/l		
Persistence and degradability		
Poly(oxy-1,2-ethanediyl),alpha-(2-propylheptyl)-omega hydroxyl		
Biodegradability: For similar material(s):Material is expected to be readily biodegradable.		
Biodegradation: > 60 %		
Exposure Time: 28 d		
Method: OECD Test Guideline 301B		
Bioaccumulative potential		
Poly(oxy-1,2-ethanediyl),alpha-(2-propylheptyl)-omega hydroxy	Bioaccumulation:	No relevant data found.
Mobility in soil		
Poly(oxy-1,2-ethanediyl),alpha-(2-propylheptyl)-omega hydroxyl		No relevant data found.

Toxicity: This material has a low potential for toxicity. Low biochemical oxygen demand and Low potential to cause oxygen depletion in aqueous systems. Low potential to affect aquatic organisms. Harmful to aquatic life if released directly to the environment.

Environmental Degradation: This product is readily biodegradable when diluted with large amounts of water; this material released into the environment is not expected to impact significantly. (Minimum of 50 parts water to 1 part product). A moderate potential to persist in the environment.

Soil Absorption/ Mobility: This material is expected to be mobile in soil and not expected to absorb suspended solids or sediments in the water. A moderate potential to affect plant life.

Section 13 - Disposal Considerations

Waste Disposal Methods: As sold, this product when discarded or disposed of as non-hazardous waste. The transportation, storage, treatment, and disposal of this waste material must be conducted in compliance with (40CFR 261, 262, 263, 264, 268, 270). Do not discharge this material into lakes, streams, ponds, or other waters. Do not discharge this material into sewer systems without approval from the local sewage treatment plant authority. Care must be taken to prevent environmental contamination from the use of this material. If material is not approved to be discharged into the sewer system, contact a licensed waste management contractor for detailed recommendations for disposal. Follow all applicable Federal, state, and local regulations. This non-hazardous liquid can be incinerated if it meets all OSHA and EPA regulations. Incinerate at a licensed waste disposal site with approved environmental authority. If this product is altered, it is the user's responsibility to determine whether the material meets the criteria for hazardous waste at the time of disposal.

Disposal Regulatory Requirements: Follow applicable NRC, CERCLA, SARA, and RCRA regulations.

Container Cleaning and Disposal: Before cleaning or disposing of a container, use caution when handling an empty container (possible combustible vapors). Do not use pressure to empty containers. Empty containers retain product vapors or residue that could be combustible. Follow all label warnings even after the container is empty. Do not cut, weld, braze, solder, drill, grind, or expose empty containers to heat, flames, or other ignition sources. Follow applicable Federal, state, and local OSHA and EPA regulations.

Section 14 – Transport Information

Domestic US Road Transportation DOT (49 CFR 172.101):

Not Regulated as a Hazardous Material or Dangerous Goods.

Canadian Road Transportation (TDG):

Not Regulated as a Hazardous Material or Dangerous Goods.

Ocean Transportation (IMO/IMDG) (49 CFR 172.101):

Not Regulated as a Hazardous Material or Dangerous Goods.

Air Transportation (ICAO/IATA) (49 CFR 172.101):

Not Regulated as a Hazardous Material or Dangerous Goods.

Section 15 – Regulatory Information

U.S. Federal Regulations

Toxic Substance Control Act (TSCA) Inventory Status:

The components for this product are on the TSCA Inventory or are exempt from TSCA Inventory requirements.

Super Fund Amendments & Reauthorization Act (SARA) Title III:

Section 302 Extremely Hazardous Substances (40 CFR 355):

Components:

None

Concentration:

None

Section 311/312 Hazard Class (40 CFR 370):

Immediate Hazard: No

Delayed Hazard: No

Fire Hazard: No

Pressure Hazard: No

Reactive Hazard: No

Section 313 Toxic Chemicals (40 CFR 372):

Components:

None

Reporting Threshold: 1.0%

None

Comprehensive Environmental Response and Liability Act (CERCLA):

Section 304 Hazardous Substances (40 CFR 302):

Components:

None

Reporting Qty:

None

OSHA Air Contaminants Standard (20 CFR 1910.1000):

The following components of this product are listed as having limits for air contaminants:

None

California Proposition 65

State Regulations

The product contains the following chemicals known to the state of California to cause cancer and or birth defects based on maximum impurity levels of components:

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain chemicals currently listed as carcinogens or reproductive toxins.

None Determined

Pennsylvania, Massachusetts & New Jersey Hazardous Substance List Right to Know:

The following components in this product are listed as hazardous at levels that require reporting.
None

International Regulations

Canadian Environmental Protection Act (CEPA):

The components for this product are included on the Canadian Domestic Substances List. (DSL)

Canadian Workplace Hazardous Materials Information System (WHIMS):

None

Section 16 – Other Information

Prepared By: Voodoo Ride

Revision Date: 03/03/2021

Disclaimer: This material safety data sheet and the information it contains is offered to you in good faith as a guide to the safe use of the product and believed to be accurate to the best of our knowledge. Not all information in this data sheet is supported by specific testing, and the evaluations are based on information from similar products, the ingredients, and technical literature. The data contained herein is provided for your guidance only when handling the specific material designated in this MSDS and does not relate to any process or to use with any other materials. We recommend testing to determine the suitability of this product for your particular purpose before use. No responsibility is accepted that the information is sufficient, correct, and complete in all circumstances, as to the safety and health of individuals, disposal of materials, and protection of the environment. The user must consider this MSDS as a supplement to other information required to make an independent determination to assure compliance to applicable laws and regulations when handling this material. The data in this document is provided without any representation or warranty expressed or implied regarding its accuracy or correctness. No warranty, either expressed or implied of merchantability or fitness or any nature, is made concerning any product referred to herein. The manufacturer does not assume responsibility and expressly disclaims liability for loss, damage, or expense arising out of or in any way connected with the handling, storage, use, or disposal of the products referred to herein. Manufacturer urges persons receiving this data to determine the information's suitability and completeness for their particular application.