



1630 E. Northfield Dr  
Brownsburg, IN 46112  
(317) 286-3694  
[www.hideaoutboardmotors.com](http://www.hideaoutboardmotors.com)

## Hidea Winterizing Checklist – 6hp

### Required - Winterizing

- Fill the fuel tank(s) and add fuel stabilizer.
- Run the motor for a few minutes to flush the water system with fresh clean water.
- Remove the rubber plug from the air box.
- While the motor is running, turn off or disconnect the fuel supply.
- Let the motor run for 1-2 minutes, then spray fogging oil into the air box towards the intake port of the carburetor. Continue to spray fogging oil into the intake until the motor stops running.
- Place the rubber plug back on the air box.
- Drain any leftover fuel out of the carburetor by removing the plug screw on the bottom of the carburetor bowl. Be sure to put the plug screw back in.
- Store the motor upright for the winter.

### Recommended - Maintenance

- Change the engine oil. Use 10w30 engine oil.
- Change the lower unit gear oil. Use 80W90 gear oil.
- Replace the anode.
- Replace the impeller and inspect the water pump housing and plate.
- Replace the fuel filter.

### Note

*If you are not comfortable with the tasks listed above, please take your motor to a professional marine service center. Improper maintenance could potentially void the warranty.*