



7cbj Yf[Ybh 7cbWfYhY HYVX bc`c[]Ygz @@7"

GdYVJU`hmi7\Ya]VVJ```7cbVfYhY` HfYUhaYbhg`

%%) 'B cfh\ '% , \$ 'K Ygh
C fYa žI hJ\ ', (\$) +
I b]hYX 'GhJhYg'cZ'5a Yf]\WJ

CZZW.', \$%'+)!&&, \$

kkk"WtbjYf[YbhWtbWfYhY"Wta

ENGINEERED WITH

THERMATROL

Extended Performance Formula with Freeze-point Altering Chemistry

PRODUCT DESCRIPTION

Pentra-Melt[™] is a fast-acting liquid de-icer for concrete driveways, sidewalks, ramps, steps, loading docks and decks. This industrial strength formula melts ice on contact as low as -40° Fahrenheit (-40°C). It also works to separate ice from the surface, allowing for easy removal. Use as a pretreatment to prevent accumulation of ice up to 36 hours before a storm or as a deicer after a storm or freezing conditions to facilitate ice removal. Pentra-Melt[™] will not damage the concrete or leave residue that can be tracked inside.

KEY BENEFITS

- Rapidly cuts through hard packed ice, breaking the bond at the surface
- Resists re-freezing and early dilution, preventing further ice formation and accumulation
- Fast acting, long-lasting formula results in fewer applications
- Non-toxic and non-hazardous to plant and animal life
- Easy to apply--no special spray equipment needed
- No mess--will not track or leave residue like common deicers
- Will not damage surface
- Does not corrode most metals

USES

Driveways, Ramps, Steps, Sidewalks, Parking Lots, Loading Docks, Decks, etc.

APPLICATION

Suggested application rates are below 0°F. Conditions with significant ice accumulation may require a heavier rate of application.

Using a sprayer, apply Pentra-Melt[™] evenly on the surface before or after snow/ice accumulation. Removal of ice/slush is required to keep the product from becoming diluted. If ice begins to accumulate, re-apply Pentra-Melt[™].

*Before application, always do a small test sample in a less-visible area to be sure there are no variables or contaminants in the substrate that may be incompatible with this product.

Pentra Melt™ 2

Customer Service:

Call 1-866-375-2280

Visit our website:

www.convergentconcrete.com

Or scan the code:



ESTIMATED COVERAGE

400-600 ft² per gallon (9.8-14.7 m² per liter)

CLEAN UP

Use soap and water to clean tools and equipment. Pentra-Melt[™] is non-toxic and environmentally safe. Use up or dry out extra material and dispose of according to local regulations. Do not pour into sewer systems or storm drains.

MAINTENANCE

Pre-treat concrete surfaces prior to the winter season with Pentra-Shield™ to harden the surface and protect against scaling and freeze-thaw damage. Promptly remove snow and ice from treated surfaces to further minimize winter weather damage. Consult a Convergent Concrete Representative for additional information.

SAFETY/HEALTH INFORMATION

KEEP OUT OF REACH OF CHILDREN.

Do not drink. If swallowed, do not induce vomiting; drink two glasses of water and call a physician. Wear goggles and gloves. If splashed in eyes, rinse eyes immediately with clean water and call a physician if irritation persists. Clean skin with soap and water. CAUTION: Surfaces wet with Pentra-Melt[™] may be slippery.

Additional precautions, safety information and first aid treatments are contained in the Safety Data Sheet.

PROPERTIES

Form: Liquid

Color: Clear to slightly tan, dries clear

Odor: Slight vinegar-like odor

Total Solids: 27.3% Specific Gravity: 1.10

pH: 5-6

VOC Content: <50g/L Flash Point: N/A

Freezing Point: -40°F (-40°C)

Shelf Life: 1 year in unopened, sealed container

PACKAGING

1-Gal Jug • 3.79 L 5-Gal Pail • 18.93 L 55-Gal Drum • 208.20 L 275-Gal Tote (IBC) • 1040 L

LIMITATIONS

Make certain the most current versions of the Pentra-Melt™ Product Data Sheet and SDS are being used. Call Customer Service (1-866-375-2280) or visit our website (www.convergentconcrete.com) to find additional tips, guidelines and specifications. Proper application is the responsibility of the user. Field visits by Convergent Concrete Personnel are for the purpose of making technical recommendations only and not for supervising or providing quality control on the job site.

Pentra Melt™ 3

Technical Service

Customer Care: Toll Free 866-375-2280 or 801 375 2280

Email:

info@convergentconcrete.com

Web:

www.convergentconcrete.com

For Chemical/Medical Emergencies:

Infotrac (800) 535-5053 Outside USA (352) 323-3500

WARRANTY

The product and application information contained herein is offered in good faith and we believe it to be accurate. However, since conditions and methods of use of our products are beyond our control, this information should not be used in substitution for customer's tests to ensure that our products are safe, effective, and fully satisfactory for the intended end use. Suggestions of use shall not be taken as inducements to infringe any patent. Convergent Concrete Technologies, LLC.'s sole warranty is that our products will meet our specifications at the time of ship-ment. Your exclusive remedy for breach of such warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted.

CONVERGENT CONCRETE TECHNOLOGIES, LLC. SPECIFICALLY DISCLAIMS ANY OTHER EXPRESS OR IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE OR MERCHANTABILITY. CONVERGENT DISCLAIMS LIABILITY FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES.



Refer to www.convergentconcrete.com for latest Technical Data Sheet and MSDS.

Convergent Concrete Technologies, LLC. ~ Specialty Chemical Concrete Treatments • 115 North 1380 West • Orem, Utah 84057 • 801-375-2280

UNIQUE STRENGTHS, UNMATCHED PERFORMANCE™

©2020 Convergent Concrete Technologies, LLC. All Rights Reserved.