


# TOP CLEAN TREND® 17

## Grooved Rubber + Scraper Bar

We recommend durable rubber profiles with anti-slip features as an efficient cleaning concept for outdoor areas. Scraper Bars installed between the profiles increase the cleaning effect even more. This Top Clean TREND® version is particularly weather-resistant and non-corrosive. Dirt and moisture are collected outside the building. Sound-absorbing, dimensionally stable, rollable and easy to clean. Available in any width and length. Special shapes at extra charge.



For outdoor use

Accessible

Recyclable

Rust-proof

1

Zone 1: Coarse Dirt Collecting Area

2

Zone 2: Intermediate Zone for heavily frequented Entrance Areas

3

Zone 3: Fine Dirt and Damp Dirt Collecting Area

### TECHNICAL DATA











<b>Aluprofile</b>	Warp resistant aluminium profile (alloy EN AW 6060)
<b>Upper</b>	Anti-slip Grooved Rubber (EPDM), with lengthwise and crosswise grooves, heavy-duty and UV-resistant conforming to <a href="#">DIN 7863</a> (German Industrial Standard) alternating with Scraper Bars made of warp resistant aluminium profile
<b>Underside</b>	Base of the mat is mechanically fitted with rubber inserts for anti-slip and noise reduction
<b>Connection</b>	Stainless steel wire rope V2A Ø 2 mm
<b>Lock</b>	Special threaded nipple with stainless steel screw (rust-proof)
<b>Profile spacing</b>	5 mm. Flexible spacers made of rubber
<b>Automatic door systems</b>	Profile spacing optional also in 3 mm for automatic door systems conforming to <a href="#">DIN 18650</a>
<b>Profile width Grooved Rubber</b>	27 mm
<b>Profile width Scraper Bar</b>	6,5 mm
<b>Mat height</b>	ca. 17 mm
<b>Wall thickness</b>	up to 1,5 mm
<b>Weight / m<sup>2</sup></b>	15,5 kg
<b>Max. profile length in one piece</b>	300 cm
<b>Max. weight in one piece</b>	50 kg
<b>Special shapes</b>	Can be custom-made to your specifications (at an extra charge)
<b>Mat division</b>	Standard = as of a profile length of 300 cm or weight of 50 kg Mat divisions into a profile length and weight according to customer requirements are possible
<b>Mat connectors</b>	High-quality connecting elements made of V2A are mounted in the factory in the case of multiple-part mats



# TOP CLEAN TREND® 17

## Grooved Rubber + Scraper Bar

### PRODUCT INFORMATION

<b>Traffic<sup>1)</sup></b>  medium	<b>Suitability for wheels<sup>2)</sup></b>  500 kg	<b>Static load<sup>3)</sup></b>  5.000 kg	<b>Load per wheel<sup>4)</sup></b>  210 kg
<b>Dirt absorption</b>  normal	<b>Moisture absorption</b>  low	<b>Slip resistance</b>  Grooved Rubber R9	<b>Fire behaviour</b>  Grooved Rubber Bfl-s1
<b>Warranty<sup>5)</sup></b>  5 years	<b>Reach<sup>6)</sup></b>  REACH-compliant		
<b>Suitability to cross over with</b>	Wheelchair, Luggage trolley, Shopping trolley, Transport trolley		
<b>Areas of application<sup>7)</sup></b>	<ul style="list-style-type: none"> <li>• Object areas</li> <li>• Public areas</li> <li>• Private areas</li> </ul>		

### ACCESSORIES

(for an additional charge)	<ul style="list-style-type: none"> <li>• Mat frame</li> <li>• T-bars (for all multiple-part Top Clean mats without connectors)</li> </ul>
----------------------------	---

### SERVICES

(on site, for an additional charge)	<ul style="list-style-type: none"> <li>• Building site advice</li> <li>• Measurement using digital measuring device</li> <li>• Fitting and laying service</li> <li>• Disposal of used mats</li> <li>• Repairs/replacement of insert types following wear</li> <li>• Cleaning</li> </ul>
-------------------------------------	---

#### Grooved Rubber



Black

1) Normal: used on foot up to approx. 2,800 times, medium: approx. 2,800 times or more, strong: approx. 5,100 times or more per day.  
 2) When laid completely supported suitable for a customary lift truck (tandem rollers) up to the specified total weight.  
 3) The static load tests to establish the load-bearing capacity of our entrance mats have been performed on a testing machine able to conduct tests with a load of up to 100 t, using a 10 x 10 cm (=100 cm<sup>2</sup>) pressure vessel. Mats with Brush Strips or Scraper Bars are only suitable for wheeled items to a limited extent. It is vital to avoid accelerating, braking or manoeuvring on the mats!

4) The specified loads refer to a polyurethane wheel with a diameter of 85 mm and width of 100 mm. When investigating our entrance matting systems, we simulated the point load that is applied to the mat by a single roller. To obtain the overall load, this value can be multiplied by the number of rollers that the means of transportation has.  
 5) Production and material defect warranty. The warranty depends on the manner of application, installation, and regular cleaning and maintenance in accordance with our recommendations. All warranties are subject to our Terms of Sale and Supply.

6) The products do not contain, in a concentration of more than 0.1 %, any substances that are currently considered to be of very high concern (SVHC) and that are included on the candidate list.  
 7) When assessing the requirements for a particular application, the performance features of the individual mat types should be taken into account.