

				
SYSTEM	<p>Drive type: Roped drum, braked gear motor drive</p> <p>Power supply: 240V single phase 15 amp</p> <p>Maximum speed: 110mm (4-5/16") / second 6.6m (21.7 ft) / min</p> <p>Maximum load: 170kg 27st 375lb</p> <p>Compliance: Machinery Directive 2006/42/EC AS 1735.15</p> <p>Structure: Not required Lift is fully self-supported</p>	<p>Drive type: Roped drum, braked gear motor drive</p> <p>Power supply: 240V single phase 15 amp</p> <p>Maximum speed: 110mm (4-5/16") / second 6.6m (21.7 ft) / min</p> <p>Maximum load: 170kg 27st 375lb</p> <p>Compliance: Machinery Directive 2006/42/EC AS 1735.15</p> <p>Structure: Not required Lift is fully self-supported</p>	<p>Drive type: Roped drum, braked gear motor drive</p> <p>Power supply: 240V single phase 15 amp</p> <p>Maximum speed: 110mm (4-5/16") / second 6.6m (21.7 ft) / min</p> <p>Maximum load: 170kg 27st 375lb</p> <p>Compliance: Machinery Directive 2006/42/EC AS 1735.15</p> <p>Structure: Not required Lift is fully self-supported</p>	<p>Drive type: Roped drum, braked gear motor drive</p> <p>Power supply: 240V single phase 15 amp</p> <p>Maximum speed: 110mm (4-5/16") / second 6.6m (21.7 ft) / min</p> <p>Maximum load: 170kg 27st 375lb</p> <p>Compliance: ASME A17.7-2007, CSA B44.7-07 ASME A18.1-2017 Machinery Directive 2006/42/EC AS 1735.15</p> <p>Structure: Not required Lift is fully self-supported</p>
CAB	<p>Configuration: Single entrance</p> <p>Cab walls: Sheetmetal (outer) Carpet (inner)</p> <p>Cab door: Half height 1100mm (43-5/16") Reversible</p> <p>Color: Signal white RAL 9003</p> <p>Cab lighting: 2x 3w LED downlights</p> <p>Operation: Continuous pressure controls</p> <p>Controls: Car operating panel, keyed switch, emergency stop</p> <p>Landing controls: 2x Wireless remote-controls</p> <p>Landing control cradles: Not available</p>	<p>Configuration: Single entrance</p> <p>Cab walls: Sheetmetal (frame) Polycarbonate (back and front panels)</p> <p>Cab door: Half height 1100mm (43-5/16") Reversible</p> <p>Color: Signal white RAL 9003</p> <p>Cab lighting: 2x 3w LED downlights</p> <p>Operation: Continuous pressure controls</p> <p>Controls: Car operating panel, keyed switch, emergency stop</p> <p>Landing controls: 2x Wireless remote-controls</p> <p>Landing control cradles: Not available</p>	<p>Configuration: Double entrance Front to back</p> <p>Cab walls: Sheetmetal (outer) Carpet (inner)</p> <p>Cab door: Half height 1100mm (43-5/16") Reversible</p> <p>Color: Signal white RAL 9003</p> <p>Cab lighting: 4x 3w LED downlights</p> <p>Operation: Continuous pressure controls</p> <p>Controls: Car operating panel, keyed switch, emergency stop</p> <p>Landing controls: 2x Wireless remote-controls</p> <p>Landing control cradles: Not available</p>	<p>Configuration: Single entrance</p> <p>Cab walls: Extrusion (frame) Polycarbonate (back and front panels)</p> <p>Cab door: Full height 1915mm (75-3/8") Reversible</p> <p>Color: Agate grey RAL 7038</p> <p>Cab lighting: Ceiling LED strip lighting Cab floor LED lights</p> <p>Operation: Continuous pressure controls</p> <p>Controls: Car operating panel, keyed switch, emergency stop</p> <p>Landing controls: 2x Wireless remote-controls</p> <p>Landing control cradles: Standard</p>
DIMENSIONS	<p>Max. travel: Up to 4500mm (177-3/16") 2 levels</p> <p>Min. upstairs: 2370mm (93-5/16") with shaft lid</p> <p>Max. total height: 5750mm (226-3/8")</p> <p>Lowest floor stop: 4" step up or 5" pit required</p> <p>Highest floor ceiling: Flat and level (sloped ceilings need modifying)</p> <p>Footprint: 1040 x 740mm (40-15/16 x 29-1/8")</p> <p>Lift cab internal: 790 x 630 x 1920mm (31-1/8 x 24-13/16 x 75-9/16")</p> <p>Cab door width: 588mm (23-1/8")</p>	<p>Max. travel: Up to 4500mm (177-3/16") 2 levels</p> <p>Min. upstairs: 2370mm (93-5/16") with shaft lid</p> <p>Max. total height: 5750mm (226-3/8")</p> <p>Lowest floor stop: 4" step up or 5" pit required</p> <p>Highest floor ceiling: Flat and level (sloped ceilings need modifying)</p> <p>Footprint: 1040 x 740mm (40-15/16 x 29-1/8")</p> <p>Lift cab internal: 790 x 630 x 1920mm (31-1/8 x 24-13/16 x 75-9/16")</p> <p>Cab door width: 588mm (23-1/8")</p>	<p>Max. travel: Up to 4500mm (177-3/16") 2 levels 3 split levels</p> <p>Min. upstairs: 2370mm (93-5/16") with shaft lid</p> <p>Max. total height: 5750mm (226-3/8")</p> <p>Lowest floor stop: 4" step up or 5" pit required</p> <p>Highest floor ceiling: Flat and level (sloped ceilings need modifying)</p> <p>Footprint: 1040 x 842mm (40-15/16 x 33-1/8")</p> <p>Lift cab internal: 790 x 670 x 1920mm (31-1/8 x 26-3/8 x 75-9/16")</p> <p>Cab door width: 588mm (23-1/8")</p>	<p>Max. travel: Up to 4500mm (177-3/16") 2 levels</p> <p>Min. upstairs: 2370mm (93-5/16") with shaft lid</p> <p>Max. total height: 5750mm (226-3/8")</p> <p>Lowest floor stop: 4" step up or 5" pit required</p> <p>Highest floor ceiling: Flat and level (sloped ceilings need modifying)</p> <p>Footprint: 1046 x 763mm (41-3/16 x 30")</p> <p>Lift cab internal: 770 x 635 x 1920mm (30-5/16 x 25 x 75-9/16")</p> <p>Cab door width: 631mm (23-7/8")</p>
SAFETIES	<p>Below cab: Safety pan with limit switches</p> <p>Above cab: Shaft lid with interrupt limits</p> <p>Battery backup: Lift can be lowered to the ground floor</p> <p>Cab entrance: Light curtain Motion sensor</p> <p>Operating panel: Emergency lighting and alarm included</p> <p>Emergency stop: Immediate stop push button</p> <p>Communication: Corded telephone to landline (by others)</p> <p>Slack rope: Limit switch with striker screw</p> <p>Overload / Out of balance: Limit switch with striker screw / bar</p>	<p>Below cab: Safety pan with limit switches</p> <p>Above cab: Shaft lid with interrupt limits</p> <p>Battery backup: Lift can be lowered to the ground floor</p> <p>Cab entrance: Light curtain Motion sensor</p> <p>Operating panel: Emergency lighting and alarm included</p> <p>Emergency stop: Immediate stop push button</p> <p>Communication: Corded telephone to landline (by others)</p> <p>Slack rope: Limit switch with striker screw</p> <p>Overload / Out of balance: Limit switch with striker screw / bar</p>	<p>Below cab: Safety pan with limit switches</p> <p>Above cab: Shaft lid with interrupt limits</p> <p>Battery backup: Lift can be lowered to the ground floor</p> <p>Cab entrance: Light curtain Motion sensor</p> <p>Operating panel: Emergency lighting and alarm included</p> <p>Emergency stop: Immediate stop push button</p> <p>Communication: Corded telephone to landline (by others)</p> <p>Slack rope: Limit switch with striker screw</p> <p>Overload / Out of balance: Limit switch with striker screw / bar</p>	<p>Below cab: Safety pan with limit switches</p> <p>Above cab: Shaft lid with interrupt limits</p> <p>Battery backup: Lift can be lowered to the ground floor</p> <p>Cab entrance: Light curtain Motion sensor</p> <p>Operating panel: Emergency lighting and alarm included</p> <p>Emergency stop: Immediate stop push button</p> <p>Communication: Corded telephone to landline (by others)</p> <p>Slack rope: Mechanical resettable roller switch</p> <p>Overload / Out of balance: Limit switch with striker screw / bar</p>
CAB OPTIONS	<p>Half door: Standard 1100mm (43-5/16") Reversible</p> <p>Full door: Option 1915mm (75-3/8") Reversible</p> <p>Handrail: Option</p> <p>Cell phone: Option</p> <p>Seat: Option Fold down seat</p>	<p>Half door: Standard 1100mm (43-5/16") Reversible</p> <p>Full door: Option 1915mm (75-3/8") Reversible</p> <p>Handrail: Option</p> <p>Cell phone: Option</p> <p>Seat: Option Fold down seat</p>	<p>Half door: Standard 1100mm (43-5/16") Reversible</p> <p>Full door: Option 1915mm (75-3/8") Reversible</p> <p>Handrail: Option</p> <p>Cell phone: Option</p> <p>Seat: Option Fold down seat</p>	<p>Half door: Option 1100mm (43-5/16") Reversible</p> <p>Full door: Standard 1915mm (75-3/8") Reversible</p> <p>Handrail: Standard</p> <p>Cell phone: Option</p> <p>Seat: Option Perch seat</p>
APPLICATION OPTIONS	<p>External gate kit: Option Upper landing gate</p> <p>Rail bracket: Option Landing or void application</p> <p>Rail block: Option Landing or void or hoistway application</p> <p>Landing threshold: Not available</p> <p>Short rail extension kit: Option > 5750mm (226-3/8") < 6900mm (271-5/8")</p> <p>Gripper rod extensions: Option > 6350mm (250") < 6900mm (271-5/8")</p> <p>Long rail extension kit: Option > 6900mm (271-5/8") < 8050mm (316-15/16")</p> <p>Floor insert extension: Not available</p> <p>Mid-level stop kit: Not available</p> <p>Factory cut-down cab: Option Only 100mm (4")</p>	<p>External gate kit: Option Upper landing gate</p> <p>Rail bracket: Option Landing or void application</p> <p>Rail block: Option Landing or void or hoistway application</p> <p>Landing threshold: Not available</p> <p>Short rail extension kit: Option > 5750mm (226-3/8") < 6900mm (271-5/8")</p> <p>Gripper rod extensions: Option > 6350mm (250") < 6900mm (271-5/8")</p> <p>Long rail extension kit: Option > 6900mm (271-5/8") < 8050mm (316-15/16")</p> <p>Floor insert extension: Not available</p> <p>Mid-level stop kit: Not available</p> <p>Factory cut-down cab: Option Only 100mm (4")</p>	<p>External gate kit: Option Upper landing or mid-level gate</p> <p>Rail bracket: Option Landing or void application</p> <p>Rail block: Option Landing or void or hoistway application</p> <p>Landing threshold: Not available</p> <p>Short rail extension kit: Option > 5750mm (226-3/8") < 6900mm (271-5/8")</p> <p>Gripper rod extensions: Option > 6350mm (250") < 6900mm (271-5/8")</p> <p>Long rail extension kit: Option > 6900mm (271-5/8") < 8050mm (316-15/16")</p> <p>Floor insert extension: Not available</p> <p>Mid-level stop kit: Option 3 split levels < 4500mm (177-3/16")</p> <p>Factory cut-down cab: Option Only 100mm (4")</p>	<p>External gate kit: Option Upper landing or mid-level gate</p> <p>Rail bracket: Option Landing or void application</p> <p>Rail block: Option Landing or void or hoistway application</p> <p>Landing threshold: Option Landing or void or hoistway application</p> <p>Short rail extension kit: Option > 5750mm (226-3/8") < 6900mm (271-5/8")</p> <p>Gripper rod extensions: Option > 6350mm (250") < 6900mm (271-5/8")</p> <p>Long rail extension kit: Option > 6900mm (271-5/8") < 8050mm (316-15/16")</p> <p>Floor insert extension: Option Up to maximum 28"</p> <p>Mid-level stop kit: Option 3 split levels < 4500mm (177-3/16")</p> <p>Factory cut-down cab: Not available Only 100mm (4") in the field by dealer</p>
BUILDING	<p>Floor template: Option</p> <p>Shaft lid: Option One included with every order</p> <p>Power supply: Dedicated 240V single phase 15 amp</p> <p>Step-up transformer: Option 3000W to dedicated 110v outlet</p> <p>Floor insert: Not available</p>	<p>Floor template: Option</p> <p>Shaft lid: Option One included with every order</p> <p>Power supply: Dedicated 240V single phase 15 amp</p> <p>Step-up transformer: Option 3000W to dedicated 110v outlet</p> <p>Floor insert: Not available</p>	<p>Floor template: Option</p> <p>Shaft lid: Option One included with every order</p> <p>Power supply: Dedicated 240V single phase 15 amp</p> <p>Step-up transformer: Option 3000W to dedicated 110v outlet</p> <p>Floor insert: Not available</p>	<p>Floor template: Option</p> <p>Shaft lid: One included with every order</p> <p>Power supply: Dedicated 240V single phase 15 amp</p> <p>Step-up transformer: Option 3000W to dedicated 110v outlet</p> <p>Floor insert: Standard Up to maximum 15"</p>
TOOLS	<p>Full installation kit: Required In addition to the tools list in manual</p> <p>Service jumper kit: Option For service technician</p> <p>Rivet nut tool: Option For reversible door hinges</p> <p>Rivet nut tool: Option For reversible door hinges</p> <p>Touch up paint: Option Signal white (9003)</p>	<p>Full installation kit: Required In addition to the tools list in manual</p> <p>Service jumper kit: Option For service technician</p> <p>Rivet nut tool: Option For reversible door hinges</p> <p>Rivet nut tool: Option For reversible door hinges</p> <p>Touch up paint: Option Signal white (9003)</p>	<p>Full installation kit: Required In addition to the tools list in manual</p> <p>Service jumper kit: Option For service technician</p> <p>Rivet nut tool: Option For reversible door hinges</p> <p>Rivet nut tool: Option For reversible door hinges</p> <p>Touch up paint: Option Signal white (9003)</p>	<p>Full installation kit: Required In addition to the tools list in manual</p> <p>Service jumper kit: Option For service technician</p> <p>Rivet nut tool: Not needed Rivet nuts pre-installed</p> <p>Rivet nut tool: Not needed Rivet nuts pre-installed</p> <p>Touch up paint: Option Agate grey (7038)</p>

Please email fully complete order form to orders@stiltzlifts.com

Effective August 1, 2019