

## VI. FAQ:

### i ). The splitter doesn't appear to be functioning.

Firstly, check if the LED lights, if the power supply is in good condition and well connected. Secondly, make sure all cables are in good condition and well connected. Thirdly, make sure the length of the cables is within the maximum supported length of this splitter. Lastly, please try to connect the input source to the display directly to see if it displays normally.

### ii ). If the maximum resolution the two displays supported is not the same, what resolution will be displayed?

The splitter will display at the lower one to both displays.

## VII CONNECTION IMAGE:



## Disclaimer

The product name and brand name may be registered trademark of related manufacturers. TM and ® may be omitted on the user manual. The pictures on the user manual are just for reference, and there may be some slight difference with the real products.

We reserve the rights to make changes without further notice to a product or system described herein to improve reliability, function or design.

# 4KX2K 1X2 HDMI Splitter User Manual



## I . INTRODUCTION

1X2 HDMI splitter distributes 1 HDMI source to 2 HDMI displays simultaneously. It can support 3D HDMI and 4K X 2K HDMI signal. It offers HD video solution for super market; shopping Mall; HDTV, STB, DVD and projector factory; data control center; information distribution; conference room presentation; education and training, corporation show room, luxurious house, etc.

## II . SPECIFICATIONS:

Input Video Signal	0.5 -1.0 volts p-p
Input DDC Signal	5 volts p-p (TTL)
HDMI Resolution	480p/576p/720p/1080i/1080p, 3D(1080p/24Hz)/4KX2K
Bandwidth	Up to 297MHz
EDID Duration	4 seconds
Power supply	DC 5V/1A

## III. CONNECTION AND OPERATION:

i ). Connect the input source and output displays to the HDMI Splitter.

\*Please refer to the Connection Image.


ii ). Connect the DC 5V power supply to the splitter. Please kindly note that power supply with higher voltage may damage the splitter.

iii ). When input source and output displays are connected and turned on, the corresponding LED will light on .

**\*Attention:** In order to protect the splitter and your devices, please make sure the splitter is powered off before you attach in or extract video source and displays. Please insert and extract HDMI cables gently.

## IV. INTERFACE SPECIFICATONS:

Front:



Back:



①Power LED

③HDMI Input

⑤HDMI1 Output

⑦LED of HDMI 2 Output

②Power Supply Socket

④LED of HDMI Input

⑥LED of HDMI 1 Output

⑧HDMI 2 Output

## V. Package contents



4KX2K 1X2 HDMI splitter\*1



User Manual\*1



Power adapter DC5V/1A