

DS-PD2-T12P-WEL

Wireless Outdoor Dual-Tech Detector

DS-PD2-T12P-WEL delivers long range signaling, multi-award-winning two-way wireless technology, heightened false alarm immunity with Dual-Vision Pet Immune detection technology, as well as a host of features that make this a steadfast detector that's quick and easy to install. Offering 90° detection (install between 1.2m), the brand-new DS-PD2-T12P-WEL can provide a maximum detection range of 12m.



AVAILABLE MODEL

DS-PD2-T12P-WEL	Wireless Outdoor Dual-Tech Detector
DS-PDB-EX-Wall bracket	Wall bracket (Need to order separately)
DS-PDB-EX-Adapter	Detector Bracket for Extending coverage angle to 90 degrees (Need to order separately, using together with DS-PDB-EX-Wall bracket)
DS-PDB-EX-Fixed bracket	Fix two external detectors to give added coverage to perimeters (Need to order separately)

*All bracket need to order separately.

MAIN FEATURES

- Microwave + 2 independent PIR
- Detection Range : 12m with Volumetric coverage 90°
- Alarm: Tamper Alarm, Intruder Alarm
- Adjustable PIR/MW range
- Dual-Vision Pet Immune (up to 24kg)
- Anti-Sway Analytics
- Blue Wave Technology
- IP55 Heavy Duty Design

SPECIFICATION

Wireless Outdoor Dual-Tech Detector	
Detection Range	12m, detection angle: 90°
Detection Speed	0.25m/s ~ 2.5m/s
Transmission Range	800m in open space
Animal Immunity	Up to 24kg
Power Supply	2 × 3V 4700mAH Lithium Battery packs, up to 3 years Battery life
Transmission frequency	433/868 MHz
Operation Temperature	-30°C ~ +70°C
Dimension(L*W*H)	188mm*77mm*84mm
Weight	300g (without bracket)
Installation Environment	Outdoor
Installation Height	1-1.5m