

SV 4G PTZ

IP-4G5MPBPTZ

1. Product Pictures



2. Features

5.0 megapixel HD 3G/4G IP camera, maximum resolution 2560x1920;

Support 3G/4G, support AP mode;

Support up to 128G TF card storage;

2.7-13.5mm 5X optical zoom auto focus lens;

Built-in MIC, support voice monitor;

Pan tilt rotation, horizontal:355°&vertical:90°;

Waterproof level IP66;

2 array infrared LEDs, night vision distance 50m;

Support P2P, view & anywhere & anytime;

Elegant outline and easy installation;

Provide android & ios APP and professional CMS PC client software;

3. Specifications

Model		IP-4G5MPBPTZ
Video	Sensor	5.0 megapixel 1/2.8" SONY335 low lux CMOS
	Video resolution	Main stream: 2560x1920@15fps, 2560x1440@15fps Sub stream: 800x600/800x448@25fps, 640x480/640x352@25fps
	Video compression	H.264 / H.265
	Lens	2.7-13.5mm 5X optical zoom auto focus lens
	View angle	96°~26.2°
	Night vision	2pcs array infrared LEDs, night vision distance 50m
Audio	Audio compression	G.726/G.711
	Audio code rate	8Kbps, 16bit
	Audio input	Built-in MIC, support voice monitor
Alarm	Motion detecting alarm	Can set 4 independent detection region (1-100 sensitivity can be set)
	Alarm linkage	Alarm send pictures to the mailbox, Alarm upload pictures and videos to the FTP server, Alarm record pictures and videos to Micro SD card, Alarm mobile phone message push
	Alarm recording	Support Micro SD card and PC client linkage alarm recording
4G	4G standard	FDD-LTE/TDD-LTE
	4G frequency range	B1(2100MHz), B3(1800MHz), B7(2600MHz), B8(900MHz), B20(800MHz), B38(2600MHz), B40(2300MHz), B41(2500MHz)
	Interface type	Micro SIM card, Plug and play, no need to set
Storage	Micro SD card	Support up to 128G micro SD card
	Recording mode	Alarm record, timing record,
	Video playback	Support APP, IE browser, remote client play and download the video
PTZ	Rotation angle	Horizon: 0~300°, Vertical: 0~60°

	Horizontal speed	12°/S
	Vertical speed	12°/S
	Preset	Support 8 preset points
General specification	Power	DC12V 2A
	Operating environment	Environment -20°C ~ +60°C (-4°F ~ +140°F), Humidity 10% ~ 90%, non-condensing
	Shell material	All metal shell
	Waterproof level	IP66
	Product size	150mm×90mm×125mm(L×W×H)
	Product weight	1.0kg
	Package size	225mmx205mmx120mm(L×W×H)
	Package weight	1.3kg
	Reset button	Support