

## HD-IP MINI PTZ DOME: IP-5MP894X

\*2.5" compact size

\* Support audio ( optional)

\*ONVIF2.4;Support P2P function

\*Support H.264 (H.265)compression

\*Pan/Tilt/Zoom, A-B scan, tour available

\* Compatible with HIKVISION ,DAHUA, XM NVR

\*Compatible with Milestone, NUUO and AXXON platform



Specification	
<b>Camera</b>	
Sensor	1/3" CMOS AR0521
Output pixel	592x1944@15fps 2592x1520@22fps
Lens	4X f=2.8~12MM
BLC	Support
AGC	Auto/manual
WB	Auto/manual/indoor/outdoor
S/N Ratio	>50dB
<b>Dome</b>	
Communications Protocol	TCP/IP,HTTP,NTP,IGMP,DHCP,UDP,SMTP,RTP,RTSP,ARP,DDNS,DNS,HTTPS,P2P
Software Control	IE, CMS, Management Platform
Video compression	H.264/H.265/M-JPEG
Mobile View(optional)	Android iPhone
Rotation Range	Pan: 0°~355° , Tilt: 0°~93 °
Rotation Speed	Pan: 0~25°/s , Tilt: 0~20°/s
Auto Flip	Support
Preset Points	220pcs presets ( dwell time 01-60s interval available )
Guard Tours	3 groups ( each group 16 preset、 dwell time and speed selectable)
AB scan range	Support, 0-355°
AB scan speed	1-9 grades
Operating temperature	-15℃~+60℃
Operation menu	English
Auto Control IR LED	PWM
Power	PoE+(1236,4578)
Consumption	≤10W
<b>IR parameters</b>	
Auto Control IR LED	PWM
IR distance	Up to 30meters
LEDs	2 PCS Array IR LED