

# KCE-ND1200D-B

VARIFOCA LENS INDOOR DOME CAMERA

**KCE**  
Korea Communication Electronics

## FEATURE

- 1/3" SONY 960H EXVIEW HAD II CCD
- 0.1 Lux at F1.6
- HIGH RESOLUTION 700TV Line
- 2.8~12mm DC Auto Iris Varifocal Lens
- BUILT-IN OSD CONTROLLER & 2nd BNC CONNECTOR
- DIGITAL NOISE REDUCTION
- 3-AXIS STRUCTURE
- MADE IN KOREA



## SPECIFICATION

DESCRIPTION	NTSC	PAL
Image Device	1/3" Sony 960H Exview HAD II CCD	
Effective Pixels	976(H) x 494(V)	976(H) x 582(V)
Scanning System	2:1 Interlace	
Synchronization	Internal	
Horizontal Resolution	700TV Lines(MAX)	
Video Output	CVBS : 1.0Vp-p, 75Ω composite	
S/N (Y Signal)	52dB (AGC off)	
Min. Illumination	0.1 Lux at F1.6	
IRIS Adjustment	MANUAL/Auto(DC)	
Lens	2.8~12mm DC Auto Iris Varifocal Lens	
OSD	Built-in	
Electronic Shutter	Auto/Manual (1/60~1/10,000sec)	Auto/Manual (1/50~1/10,000sec)
Backlight Compensation	OFF / BLC / HLC	
Auto Gain Control	AUTO / MANUAL	
White Balance	TW / PUSH / USER1 / USER2 / ANTI CR / MANUAL / PUSH LOC	
Day&Night	AUTO / B/W / COLOR / EXT1 / EXT2	
IR OPTIMIZER	OFF/ON(AUTO/ CENTER)	
Privacy Masking	ON/OFF (8 Zones)	
Noise Reduction	2DNR(Y/C)	
WHITE PIXEL DETECTION	ONE PUSH (KEY UP)	
Gamma	0.45	
ATR	OFF/ON(LUMINANCE/CONTRAST)	
Motion	OFF/ON(4ZONE)	
Language	English / 日本語 / German / French / Russian / Portugues / Spanish	
PICT Adjust	Mirror / Brightness / Contrast / Sharpness / Hue /	
IR LED	-	
Input Voltage	DC 12V(±10%)	
Power Consumption	DC : 120mA(MAX)	
Operating Temp. / Hum.	-10°C~ +50°C / MAX 90% RH	
Storage Temp. / Hum.	-20°C ~ +60°C / MAX 90% RH	

## DIMENSION Unit : mm

