

TVI Full HD H.264 Hybrid Network DVR

TVI 1080P + 960H/D1 + IP Camera



TVI 1080P

MAIN FEATURES

- Support TVI up to 3 Megapixel Video Input*
- Support OSD setting over coaxial (UTC)
- Support TVI Analog and IP camera
- Support IP camera with Onvif Profile protocol (V2.4)
- Cross device function for redundant recording
- Perfect for replacement of old system with the benefit of high definition
- Excellent picture quality



Camera Input	8CH TVI Universal
Video Input	TVI: 1080P @ 30/25 fps, 720P @ 60/50 fps, 720P @ 30/25 fps 960H / D1
Video Output	1 HDMI with Audio and 1 VGA (Max. 1920x1080) 1 Main BNC
Audio Input	1 RCA
Audio Output	1 RCA
System	Operating System Embedded Linux OS
SATA Devices	Max. 1 x SATA Device (HDD x 1)
External HDD	N/A
Alarm In /Relay Out	N/A
Serial Interface	RS-485
USB 2.0 Ports	USB2.0 X2
Dimension (mm)	280(w)x51(h)x203(d)
Power Rating	12V 3.33A ,40W
Display Split Screen	1,4, 8, SEQ.
Auto Ch Switching	Switching time : 1 ~ 99 sec
Mode	Zoom, Auto SEQ.
Recording Compression	H.264 High Profile
Main (Recording) Resolution	1920 x 1080, 1280 x 720; 944 x 480 .704 x 480, 352 x 240 (NTSC) / 944 x 576 ,704 x 576, 352 x 288 (PAL)
Sub (Network) Resolution	640 x 360 / 352 x 240, 176 x 120 (NTSC) / 352 x 288, 176 x 144 (PAL)
Picture Quality	10~100 levels for adjustment
Mode	Continuous, Event, Schedule
Record Rate	NTSC 1080p 120fps; 720p 240 fps PAL 1080p 100fps ; 720p 200 fps
Pre-Alarm	1 ~ 5 SEC
Post-Alarm	1 ~ 100 SEC
Playback Search Mode	Date/time, Event
Zoom	*Digital (x2 ~ x5)
Network Network Interface	10/100/1000 Ethernet
Protocol	TCP/IP, SMTP, HTTP, DHCP, PPPoE(ADSL), NTP, DDNS
Application	Windows 7 & 8, Mac OS X
Remote Software	SoCatch, IE Browser, iCMS Pro
Account	1 Admin + 10 Users
Mobile Device	Windows Phone 7.8, iPhone, iPad, Android
Backup Interface	USB or SATA
Audio Backup	YES
Backup Type	Network, ext. USB flash device , SATA optical DVD..etc.
Alarm Motion Detection	Sensitivity: 100 levels for each channel
Area:	Programmable individually
Event Log	Up to the 10000 events (Sensor, Motion, video Loss, power on, remote login, logout, HDD error, HDD full)
DVR Control	Multi-Language Supported
Camera Title	Multi-Language
USB Mouse	YES
Touch Panel	Touch Panel LCD Monitor (USB Interface, EETI Chipset Only)
Remote Controller	IR Remote Control
System Upgrade	USB Flash Drive, iWatch DVR
Pan/Tilt/Zoom Control	Control From RS485 Interface (Pelco P, Pelco D, Samsung, LG, LiLin)
General Operating Temperature:	-10°C ~ +55°C (14°F ~ 131°F)
Operating Humidity:	10%~80%
All specifications are subject to change without notice.	