

Technical data

Sn [kVA]	650 VA	800 VA	1000 VA	1500 VA	2000 VA
Pn [kW] (0 °C ÷ 35 °C)	360 W	480 W	600 W	900W	1200W
Input / output	1/1				

Input	
Mains voltage	177 V - 290 V
Rated frequency	50 / 60 Hz with automatic selection
Mains connection	Cable with plug

Output	
Automatic Voltage Regulation (AVR)	• • • • •
Rated voltage	230 V ±10%
Rated frequency	50/60 Hz
Wave form	Step wave
Protection	Overload, significant discharge and short circuit
Sockets	650-850: 2 x Australian standard 1000-1500-2000: 4 x Australian standard

Batteries	
Type	Sealed lead-acid maintenance free - expected life 3/5 years
Back-up time ⁽¹⁾	15 Min 20 Min 45 Min 55 Min 60 Min

Communication	
Interface	• USB
Local communication software	• Local View
Telephone protection	• NTP data line suppressor

UPS Cabinet	
Dimensions (W x D x H) [mm]	100 x 290 x 145 145 x 345 x 165 mm 145 x 390 x 205 mm
Weight	5.2 kg 6 kg 9.7 kg 11.2 kg 12 kg

Standards	
Safety	AS 62040-1
EMC	AS 62040-2
Product declaration	CE, C-Tick (N876)