# Mini Ball Valves, Brass

### **Technical Features:**

Suitable for domestic water services, heating and airconditioning plants, compressed air systems. Minimum and maximum working temperature -10°C to 110°C

## Materials:

Valve body: C.P. Polished Brass


Handle: ABS

Ball: Hard chrome plated brass

Seal: P.T.F.E Stem: Brass Stem seal: Brass O-Ring: NBR

Type MBVM, Male x Female, Red Lever Handle, BSPP		
PART NUMBER	THREAD	
MBVM18	1/8"	
MBVM14	1/4"	
MBVM38	3/8"	
MBVM12	1/2"	
MBVM34	3/4"	





## **Technical Features:**

Suitable for domestic water services, heating and airconditioning plants, compressed air systems. Minimum and maximum working temperature -10°C to 110°C

# Materials:

Valve body: C.P. Polished Brass

Handle: ABS


Ball: Hard chrome plated brass

Seal: P.T.F.E Stem: Brass Stem seal: Brass O-Ring: NBR



PART NUMBER	THREAD
MBV18	1/8"
MBV14	1/4"
MBV38	3/8"
MBV12	1/2"
MBV34	3/4"





## **Technical Features:**

Suitable for domestic water services, heating and airconditioning plants, compressed air systems. Minimum and maximum working temperature -10°C to 110°C

Available in all sizes from 1/8" up to 3/4"

### **Materials:**

Valve body: C.P. Polished Brass


Handle: ABS

Ball: Hard chrome plated brass

Seal: P.T.F.E Stem: Brass Stem seal: Brass O-Ring: NBR

Type MBV, Female x Female, Black Lever Handle, BSPP		
PART NUMBER	THREAD	
MBV18S	1/8"	
MBV14S	1/4"	
MBV38S	3/8"	
MBV12S	1/2"	
MBV34S	3/4"	





## **Technical Features:**

Suitable for domestic water services, heating and airconditioning plants, compressed air systems. Minimum and maximum working temperature -10°C to 110°C

Available in all sizes from 1/8" up to 3/4"

## Materials:


Valve body: C.P. Polished Brass

Handle: ABS

Ball: Hard chrome plated brass

Seal: P.T.F.E Stem: Brass Stem seal: Brass O-Ring: NBR





Type MBVM, Male x Female, Black Lever Handle, BSPP		
PART NUMBER	THREAD	
MBVM18S	1/8"	
MBVM14S	1/4"	
MBVM38S	3/8"	
MBVM12S	1/2"	
MBVM34S	3/4"	