


Silencers



Coned Brass & Sintered Bronze Silencers




Technical Characteristics

Maximum pressure: 10 bar
 Minimum temperature: -10°C
 Maximum temperature: +80°C
 Filtration threshold: 50 µm

dB = Noise level in (dB) at 6 bar

Code	A	F	B	H	dB
7000-1/8	1/8"	4.5	12.5	21	81
7000-1/4	1/4"	6	15	25	83
7000-3/8	3/8"	8.5	19	34.5	87
7000-1/2	1/2"	8	23	43	90
7000-3/4	3/4"	9	30	50	92 @ 4 bar
7000-1	1"	11	37	60.5	92 @ 4 bar




Technical Characteristics

Maximum pressure: 10 bar
 Minimum temperature: -10°C
 Maximum temperature: +80°C
 Filtration threshold: 50 µm

dB = Noise level in (dB) at 6 bar

Code	A	F	H	CH
7030-M5	M5	4	17	8
7030-1/8	1/8"	6	22	13
7030-1/4	1/4"	7	32	16
7030-3/8	3/8"	8	40	19
7030-1/2	1/2"	9	45	24
7030-3/4	3/4"	10	56	30
7030-1	1"	12	66	36



Technical Characteristics

Maximum pressure: 12 bar
 Minimum temperature: -10°C
 Maximum temperature: +80°C
 Filtration threshold: 36 µm

dB = Noise level in (dB) at 6 bar

Code	A	F	H	CH	dB
7040-1/8	1/8"	6	44	13	76
7040-1/4	1/4"	7	50	16	75
7040-3/8	3/8"	8	54	19	88
7040-1/2	1/2"	9	67	24	89
7040-3/4	3/4"	9	65	30	

