

# Ultra-fast charging 320 kW charging capacity in the power-limited distribution grid



## Charging technology in a new dimension **ChargeBox system**

A charging capacity of up to 320 kW for e-vehicles, without extension of the limited distribution grid – this is provided by the ChargeBox with Booster and Dispenser as a storage-based fast-charging system. Connection of one to two charging stations with 160 or 320 kW capacity.



ChargeBox Dispenser

ChargeBox Booster

### **Big-LinX® Energy ADS-TEC cloud solution for monitoring/control from any location**

- IoT service platform Big-LinX for worldwide access to all energy storage systems
- Administration and management (control and battery monitoring)
- »State of the art« security with software and hardware certificates (smart card)

### **Battery storage systems “Technology for Professionals” Made in Germany**

- Selected cells with minimum ageing effects from renowned manufacturers
- Dedicated tool for cell monitoring over the entire life cycle
- Compliant with current standards and certifications

## HIGHLIGHTS

- Up to 320 kW DC charging power per ChargeBox Dispenser or 160 kW each
- Outdoor installation directly at the power-limited distribution grid
- Extremely compact design as a complete system
- Easy transport, fast IT integration
- Distributed system for easy on-site installation
- Tested for the use in accordance with the latest charging norm IEC 61851-1:2017
- TÜV-certified safety for installation in public domain

### **ChargeBox Booster Battery storage and energy conversion**

- Designed for all voltage levels of on-board traction power systems – downward compatibility for existing e-vehicles from 150 V as well as future-proof compatibility for upcoming vehicles up to 920 V
- Integrated PCS (Power Conversion System), climate control, energy management unit, security/firewall and communication unit mobile radio or ethernet
- Direct AC connection to distribution grids at 400 V level
- OCPP 1.6 (Open Charge Point Protocol)
- Optional: can be installed above ground

### **ChargeBox Dispenser Ultra-fast charging station for e-vehicles**

- Up to 320 kW charging capacity per Dispenser
- Low-noise charging – also ideal for residential areas
- Charging socket positions easily reached thanks to high attachment point of the cable
- Liquid-cooled charging cable
- CCS1 charging plug
- Integrated 10-inch HD touch screen as user interface
- Indoor and outdoor installation possible
- Optional: Energy measurement by means of calibrated DC meter

# ChargeBox system

## Technical data

### ChargeBox Booster (Power amplifier)

<b>Grid</b>	Grid type	3-phase
	Grid frequency	60 Hz
	Grid input power	110 kVA
	Grid input voltage	480 V (+/- 10%)
	Grid input current	max. 160 A
<b>Battery system</b>	Battery performance warranty	up to 10 years*
	Cell chemistry	Lithium-ion
	Battery capacity	140 kWh
	Cooling	Air and liquid-cooled
<b>ChargeBox Booster</b>	Vehicle charging power	2x 160 kW / 1x 320 kW
	Electrical efficiency factor	95 % at nominal output power during charging process**
	Target markets	US - CAN***
	Noise emissions	Low-noise charging
	L x W x H	1.4 x 1.4 x 1.5 yd plus base and underground cabling****
	Weight (total)	3.1 tn. sh. (including cooling medium and batteries)
	Installation option	max. 109 yd from dispenser
Output voltage	150 - 920 V DC (on the output side of the vehicle)	
<b>Communication interfaces</b>	Back-end connection	Fiber optic cable, 4G, Ethernet
	Protocol	OCPP 1.6
<b>Environmental conditions</b>	Temperature range	-22 °F to 122 °F
	Installation option	Outdoor ****
<b>Standards/safety</b>	Safety	Battery safety acc. to IEC 62619 and UL 1973
	Conformity	UL, CE
	EMC	FCC part 15B
	Transport	UN 38.3 test directive for lithium batterie

### ChargeBox Dispenser (Fast charging station)

<b>Dimensions</b>	L x W x H	0.44 x 0.44 yd (floor space) x 2.95 yd
	Weight	375 lbs
<b>System</b>	Screen	10-inch sunlight readable HD touch screen
	Authentication	RFID
	Energy measurement	Optional by means of calibrated DC energy meter
	Vandalism class	IK09
	Noise emissions	Silent, no cooling air outlet
	Installation options	Indoor and outdoor
<b>Charging cable</b>	Cooling	Liquid-cooled
	Plug type	CCS1***
	Functionality	Flexible cable for easy access to charging sockets on the vehicle
	Cable length	4.15 yd, cable not in contact with ground when plugged in

ads-tec Energy Inc.  
5343 Paylor Lane, Suite 200  
Sarasota, FL 34240  
USA  
Phone: +1 941-358-7445  
info-us@ads-tec-energy.com  
[www.ads-tec.com/us/hpc](http://www.ads-tec.com/us/hpc)



Phone : (888) 293-4680  
Address: 24303 Walnut St., Suite F  
Newhall, CA 91321  
Email: [info@payenergy.com](mailto:info@payenergy.com)  
[www.payenergy.com](http://www.payenergy.com)



SCAN TO CONNECT



\* defined warranty within a service contract  
\*\* without auxiliary consumers  
\*\*\* also available in Europe with CCS2  
\*\*\*\* above ground variant approx. 0.65 yd higher  
\*\*\*\*\* depending on approval by local authorities

The content of this data sheet was created with utmost care. However, we shall not be held liable for the accuracy, completeness and topicality of any data and figures obtained in this publication. The contents are subject to modifications and illustrations may vary. All product names are trademarks and registered trademarks, and as such are the property of the respective company owning trademark rights, in each case.



DZ-HAND-93226-1/D ChargeBox datasheet US 07-2022