

# CLIO Universal Mixer – In Wall Body Kit

## IMPORTANT! Read before installation!

! In-wall body kit & Trim kits are supplied in separate boxes. For Trim kit installation, follow the instructions supplied with the suitable Trim kit.

! The front face of the mounting plate or noggin must be parallel to the finished wall/ tile face.

! Brazed connections should NOT be made directly onto the mixer, as excessive heat will cause permanent damage

! All pipework must be thoroughly flushed prior to installation.

! Sealant/ waterproofing materials used to seal the wall penetration must not interfere with the removal of the protective sleeve and installation of the trim components.

! To avoid damaging the product, do not remove the protective sleeve until installing the trim kit.



Hot and cold water inlet pressures must be equal. Static inlet pressure: 150-1000 kPa

*New Regulation: 500 kPa maximum static pressure at any outlet within a building. (AS/NZS 3500.1)*



Maximum hot water temperature :55C.

## Installation

1. Secure mixer in wall body onto a suitable noggin in the wall. When facing the mixers, the connections should be as follows:

Hot water inlet ('H') to the left  
Cold Water Inlet ('C') to the right  
Outlet vertically upwards.

2. Check all connections for leaks and tap for operation. Leave the protective sleeve on until installing the trim kit.
3. Seal the wall penetration between the noggin and the mixer in accordance with AS:3740. Sealant must remain clear of the protective sleeve and the surface it protects.

