

**Safety Data Sheet**  
According to HSNO Regulations

Initial preparation date: 08.6.2018

Page 1 of 14

AMC Green

**SECTION 1: Identification**

**Product identifier**

**Product name:** AMC Green

**Product code:** 42308

**Additional information:** No additional information available.



**Recommended use of the product and restriction on use:**

**Relevant identified uses:** Paints

**Uses advised against:** Not determined or not applicable.

**Reasons why uses advised against:** Not determined or not applicable.

**Manufacturer or supplier details**

**Manufacturer:**

P.O.R. Products  
38 Portman Road  
New Rochelle, NY 10801  
914-636-0700

**Supplier:**

HGLB Holdings  
30 Victoria Street  
Petone 5012  
021 446682  
sales@por15nz.com

**Emergency telephone number:**

**ChemTel Inc.**

+1 813 248 0585

**Poisons Information Center, New Zealand**

0800 764 766

**SECTION 2: Hazards identification**

Classified as a Dangerous Good according to NZS 5433:2012 Transport of Dangerous Goods on Land.

Classified as hazardous according to criteria in the HS (Minimum Degrees of Hazard) Regulations 2017

**HSNO Classification or Subclasses – Physical hazards:**

Class	GHS Category	HSNO Category
Flammable liquids	Category 3	3.1C

**HSNO Classification or Subclasses – Health hazards:**

Class	GHS Category	HSNO Category
Eye irritation	Category 2A	6.4A
Skin irritation	Category 2	6.3A
Skin sensitization	Category 1	6.5B
Aspiration hazard	Category 1	6.1E
Specific target organ toxicity - single exposure	Category 3, central nervous system	6.9B
Specific target organ toxicity - repeated exposure	Category 1	6.9A
Carcinogenicity	Category 2	6.7B
Reproductive toxicity	Category 2	6.8B

**HSNO Classification or Subclasses – Environmental hazards:**

# Safety Data Sheet

According to HSNO Regulations

Initial preparation date: 08.6.2018

Page 2 of 14

AMC Green

Class	GHS Category	HSNO Category
Acute aquatic hazard	Category 3	9.1D
Chronic aquatic hazard	Category 2	9.1B

## GHS classification:

Flammable liquids, category 3  
Eye irritation, category 2A  
Skin irritation, category 2  
Skin sensitization, category 1  
Aspiration hazard, category 1  
Specific target organ toxicity - single exposure, category 3, central nervous system  
Specific target organ toxicity - repeated exposure, category 1  
Carcinogenicity, category 1B  
Reproductive toxicity, category 2  
Acute aquatic hazard, category 3  
Chronic aquatic hazard, category 2

## Label elements

### Hazard pictograms:



**Signal word:** Danger

### Hazard statements and Precautionary statements:

H226 Flammable liquid and vapor.  
H319 Causes serious eye irritation.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H304 May be fatal if swallowed and enters airways.  
H336 May cause drowsiness or dizziness.  
H372 Causes damage to organs through prolonged or repeated exposure.  
H350 May cause cancer.  
H361 Suspected of damaging fertility or the unborn child.  
H402 Harmful to aquatic life.  
H411 Toxic to aquatic life with long lasting effects.  
P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.  
P233 Keep container tightly closed.  
P240 Ground/bond container and receiving equipment.  
P241 Use explosion-proof electrical/ventilating/lighting equipment.  
P242 Use only non-sparking tools.  
P243 Take precautionary measures against static discharge.  
P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P264 Wash skin thoroughly after handling.  
P261 Avoid breathing dust/fume/gas/mist/vapors/spray.  
P272 Contaminated work clothing should not be allowed out of the workplace.  
P271 Use only outdoors or in a well-ventilated area.

# Safety Data Sheet

According to HSNO Regulations

Initial preparation date: 08.6.2018

Page 3 of 14

AMC Green

- P260 Do not breathe dust/fume/gas/mist/vapors/spray.  
P270 Do not eat, drink or smoke when using this product.  
P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P281 Use personal protective equipment as required.  
P273 Avoid release to the environment.  
P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P370+P378 In case of fire: Use appropriate fire extinguishing methods for extinction.  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P337+P313 If eye irritation persists get medical advice/attention  
P321 Specific treatment (see first aid instructions on this label).  
P362 Take off contaminated clothing and wash before reuse  
P302+P352 IF ON SKIN: Wash with plenty of soap and water.  
P332+P313 If skin irritation occurs: Get medical advice/attention  
P362+P364 Take off contaminated clothing and wash it before reuse.  
P363 Wash contaminated clothing before reuse  
P333+P313 If skin irritation or a rash occurs: Get medical advice/attention  
P331 Do NOT induce vomiting.  
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.  
P312 Call a POISON CENTER or doctor/physician if you feel unwell.  
P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.  
P314 Get medical advice/attention if you feel unwell  
P308+P313 If exposed or concerned: Get medical advice/attention  
P391 Collect spillage  
P403+P235 Store in a well ventilated place. Keep cool.  
P405 Store locked up.  
P403+P233 Store in a well ventilated place. Keep container tightly closed.  
P501 Dispose of contents/container according to local regulations.

#### Hazards not otherwise classified:

None known.

### SECTION 3: Composition/information on ingredients

#### Mixture:

Identification	Name	Weight %
CAS number: 64742-48-9	Naphtha (petroleum), hydrotreated heavy	2-5
CAS number: 71-43-2	Benzene	<0.01
CAS number: 1333-86-4	Carbon Black	<0.5
CAS number: 100-41-4	Ethyl Benzene	<0.01

**Safety Data Sheet**  
According to HSNO Regulations

Initial preparation date: 08.6.2018

Page 4 of 14

AMC Green

CAS number: 64742-95-6	Solvent naphtha (petroleum), light arom.	2-5
CAS number: 22464-99-9	Zirconium 2-Ethylhexanoate	<0.5
CAS number: 64742-47-8	Distillates (petroleum), hydrotreated light	<0.5
CAS number: 108-65-6	1-Methoxy-2-propanol acetate	2-5
CAS number: 123-86-4	n-Butyl acetate	<0.5
CAS number: 13463-67-7	Titanium Dioxide	7-10
CAS number: 147-14-8	29H,31H-Phthalocyaninato(2-)- N29,N30,N31,N32 copper	<1
CAS number: 136-52-7	Cobalt bis(2-ethylhexanoate)	<0.5
CAS number: 98-82-8	Cumene	<0.1
CAS number: 108-88-3	Toluene	<0.01
CAS number: 96-29-7	Methyl ethyl ketoxime	<0.5
CAS number: 8052-41-3	Stoddard Solvent	25-30
CAS number: 91-20-3	Naphthalene	<0.01

**Additional information:**

None known

**SECTION 4: First-aid measures**

For advice, contact a Poisons Information Center (e.g. phone Australia 131 126, New Zealand 0800 764 766) or a doctor.

**Description of first aid measures**

**General notes:**

Not determined or not available.

**After inhalation:**

Loosen clothing as necessary and position individual in a comfortable position Maintain an unobstructed airway

Get medical advice/attention if you feel unwell

**After skin contact:**

Rinse affected area with soap and water.

If symptoms develop or persist, seek medical attention.

Take off all contaminated clothing.

Gently blot or brush away excess product.

**Safety Data Sheet**  
According to HSNO Regulations

Initial preparation date: 08.6.2018

Page 5 of 14

**AMC Green**

Wash with plenty of lukewarm, gently flowing water.

Get medical advice if skin irritation occurs or you feel unwell.

**After eye contact:**

Rinse/flush exposed eye(s) gently using water for 15-20 minutes.

If symptoms develop or persist, seek medical attention.

Rinse eyes cautiously with lukewarm, gently flowing water for several minutes, while holding the eyelids open.

Remove contact lenses, if present and easy to do so.

Continue rinsing for 15-20 minutes.

Get medical advice if eye irritation persists.

**After swallowing:**

Rinse mouth thoroughly

Seek medical attention if irritation, discomfort, or vomiting persists

**Most important symptoms and effects, both acute and delayed:**

**Acute symptoms and effects:**

Not determined or not available.

**Delayed symptoms and effects:**

Not determined or not available.

**Immediate medical attention and special treatment:**

**Specific treatment:**

Not determined or not available.

**Notes for the doctor:**

Not determined or not available.

**Workplace Facilities:**

Not determined or not available.

**SECTION 5: Fire-fighting measures**

**Extinguishing media**

**Suitable extinguishing media:**

Use Water (fog only), dry chemical, chemical foam, carbon dioxide, or alcohol-resistant foam.

**Unsuitable extinguishing media:**

Do not use a water stream as an extinguisher.

**Specific hazards during fire-fighting:**

Thermal decomposition can lead to release of irritating gases and vapors.

Vapors can flow to distant ignition sources and flashback

Liquid is volatile and may generate an explosive atmosphere.

**Special protective equipment for firefighters:**

Use typical firefighting equipment, self-contained breathing apparatus, special tightly sealed suit.

**Special precautions:**

Shut off sources of ignition.

Carbon monoxide and carbon dioxide may form upon combustion.

Heating causes a rise in pressure, risk of bursting and combustion.

**Hazchem or Emergency Action Code:**

Not determined or not available.

**Safety Data Sheet**  
According to HSNO Regulations

Initial preparation date: 08.6.2018

Page 6 of 14

AMC Green

**SECTION 6: Accidental release measures**

**Personal precautions, protective equipment and emergency procedures:**

- Ensure adequate ventilation.
- Ensure air handling systems are operational.
- Wear protective eye wear, gloves and clothing.
- Beware of vapors accumulating to form explosive concentrations.
- Vapors can accumulate in low areas.

**Environmental precautions:**

- Should not be released into the environment.
- Prevent from reaching drains, sewer or waterway.

**Methods and material for containment and cleaning up:**

- Wear protective eye wear, gloves and clothing.
- Use spark-proof tools and equipment.
- Absorb with non-combustible liquid-binding material (sand, diatomaceous earth (clay), acid binders, universal binders).
- Dispose of contents / container in accordance with local regulations.

**Reference to other sections:**

- Not determined or not applicable.

**SECTION 7: Handling and storage precautions**

**Precautions for safe handling:**

- Use only with adequate ventilation.
- Avoid breathing mist or vapor.
- Do not eat, drink, smoke or use personal products when handling chemical substances.
- Take precautionary measures against electrostatic discharges.
- Use only non-sparking tools.

**Conditions for safe storage, including any incompatibilities:**

- Keep container tightly sealed.
- Protect from freezing and physical damage.
- Store in a cool, well-ventilated area.
- Store away from all ignition sources (open flames, hot surfaces, direct sunlight, spark sources).

**Safe packaging material**

**Suitable material:**

- Not determined or not applicable.

**Unsuitable material:**

- Not determined or not applicable.

# Safety Data Sheet

According to HSNO Regulations

Initial preparation date: 08.6.2018

Page 7 of 14

AMC Green

## SECTION 8: Exposure controls and personal protection

### Occupational Exposure limit values:

Country (Legal Basis)	Substance	Identifier	Permissible concentration
New Zealand	Benzene	71-43-2	TWA: 1 ppm. TWA: 2.5 mg/m <sup>3</sup>
	Naphthalene	91-20-3	TWA: 10ppm. TWA: 52 mg/m <sup>3</sup> 15-minute STEL: 15ppm. 15-minute STEL: 79 mg/m <sup>3</sup>
	Carbon Black	1333-86-4	TWA: 3 mg/m <sup>3</sup>
	Ethyl Benzene	100-41-4	TWA: 100 ppm. TWA: 434 mg/m <sup>3</sup> 15-minute STEL: 125 ppm. 15-minute STEL: 543 mg/m <sup>3</sup>
	n-Butyl acetate	123-86-4	TWA: 150 ppm. TWA: 713 mg/m <sup>3</sup> 15-minute STEL: 200 ppm. 15-minute STEL: 950 mg/m <sup>3</sup>
	Titanium Dioxide	13463-67-7	TWA: 10 mg/m <sup>3</sup>
	Cumene	98-82-8	TWA: 125 mg/m <sup>3</sup> (25 ppm); STEL: 375 mg/m <sup>3</sup> (175 ppm)
	Toluene	108-88-3	TWA: 50 ppm. TWA: 188 mg/m <sup>3</sup>
	Stoddard Solvent	8052-41-3	TWA: 100 ppm. TWA: 525 mg/m <sup>3</sup>

### Biological limit value:

No biological exposure limits noted for the ingredient(s)

### Information on monitoring procedures:

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls

Biological monitoring may also be appropriate for some substances

### Appropriate engineering controls:

Emergency eye wash fountains and safety showers should be available in the immediate vicinity of use or handling.

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapor and mists below the applicable workplace exposure limits (Occupational Exposure Limits-OELs) indicated above.

Use explosion-proof ventilation equipment.

### Personal protection equipment

#### Eye and face protection:

Safety goggles or glasses, or appropriate eye protection.

#### Skin and body protection:

Select glove material impermeable and resistant to the substance.

Wear appropriate clothing to prevent any possibility of skin contact.

#### Respiratory protection:

If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.

# Safety Data Sheet

According to HSNO Regulations

Initial preparation date: 08.6.2018

Page 8 of 14

AMC Green

## General hygienic measures:

- Avoid contact with skin, eyes and clothing.
- Wash hands before breaks and at the end of work.
- Wash contaminated clothing before reuse.

## SECTION 9: Physical and chemical properties

Appearance	Liquid
Odor	Solvent
Odor threshold	Not determined or not available.
pH	Not determined or not available.
Melting point/freezing point	Not determined or not available.
Initial boiling point/range	Not determined or not available.
Flash point (closed cup)	104°F (40°C)
Evaporation rate	Not determined or not available.
Flammability (solid, gas)	Not determined or not available.
Upper flammability/explosive limit	Not determined or not available.
Lower flammability/explosive limit	Not determined or not available.
Vapor pressure	Not determined or not available.
Vapor density	Not determined or not available.
Density	Not determined or not available.
Relative density	Not determined or not available.
Solubilities	Not soluble in water.
Partition coefficient (n-octanol/water)	Not determined or not available.
Auto/Self-ignition temperature	Not determined or not available.
Decomposition temperature	Not determined or not available.
Dynamic viscosity	Not determined or not available.
Kinematic viscosity	Not determined or not available.
Explosive properties	Not determined or not available.
Oxidizing properties	Not determined or not available.

## Other information

VOC Content	<430 g/L (Theoretical)
-------------	------------------------

## SECTION 10: Stability and reactivity

### Reactivity:

Does not react under normal conditions of use and storage.

### Chemical stability:

Stable under normal conditions of use and storage.

### Possibility of hazardous reactions:

None under normal conditions of use and storage.

### Conditions to avoid:

Avoid heat, sparks, flames or other sources of ignition.

### Incompatible materials:



**Safety Data Sheet**  
According to HSNO Regulations

Initial preparation date: 08.6.2018

Page 9 of 14

AMC Green

None known.

**Hazardous decomposition products:**

None known.

**SECTION 11: Toxicological information**

**Acute toxicity:**

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:** No data available.

**Substance data:**

Name	Route	Result
Ethyl Benzene	inhalation	LCLo - Rat - 4,000 ppm/4 h
Naphthalene	oral	LD50 - Mouse - 316 mg/kg

**Skin corrosion/irritation:**

**Assessment:** Causes skin irritation

**Product data:** No data available.

**Substance data:**

Name	Result
Naphtha (petroleum), hydrotreated heavy	Irritating to the skin.
Cobalt bis(2-ethylhexanoate)	Irritating to the skin.
Zirconium 2-Ethylhexanoate	Irritating to the skin.
Benzene	Irritating to the skin.
Toluene	Irritating to the skin.

**Serious eye damage/irritation:**

**Assessment:** Causes serious eye irritation

**Product data:** No data available.

**Substance data:**

Name	Result
Methyl ethyl ketoxime	Risk of serious damage to the eyes.
Benzene	Irritating effect on the eyes.

**Respiratory or skin sensitization:**

**Assessment:** May cause an allergic skin reaction

**Product data:** No data available.

**Substance data:**

Name	Result
Cobalt bis(2-ethylhexanoate)	May cause sensitization by skin contact.
Methyl ethyl ketoxime	May cause sensitization by skin contact
Cumene	No skin irritation
	No eye irritation

**Carcinogenicity**

**Assessment:** May cause cancer

**Product data:** No data available.

# Safety Data Sheet

According to HSNO Regulations

Initial preparation date: 08.6.2018

Page 10 of 14

AMC Green

**Substance data:**

Name	Species	Result
Stoddard Solvent	Stoddard Solvent	Component may cause cancer.
Naphtha (petroleum), hydrotreated heavy		May cause cancer.
Naphthalene	Not applicable.	Suspected of causing cancer.
Carbon Black	Not applicable.	The carcinogenic classification only applies to airborne, unbound particles of respirable size.
Methyl ethyl ketoxime		May cause cancer.
Solvent naphtha (petroleum), light arom.	Solvent naphtha (petroleum), light arom.	Component may cause cancer.
Benzene	Benzene	Confirmed human carcinogen.
Titanium Dioxide		Airborne, unbound particles of respirable size are known to cause cancer.

**International Agency for Research on Cancer (IARC):**

Name	Classification
Stoddard Solvent	Group 3
Cobalt bis(2-ethylhexanoate)	Group 2B
Ethyl Benzene	Group 2B - Possibly carcinogenic to humans
Naphthalene	Group 2B - Possibly carcinogenic to humans
Distillates (petroleum), hydrotreated light	Group 3 - Not classifiable as to its carcinogenicity to humans
Cumene	Group 2B - Possibly carcinogenic to humans
Benzene	Group 1 - Carcinogenic to humans
Titanium Dioxide	Group 2B
Carbon Black	Group 2B - Possibly carcinogenic to humans
Toluene	Group 3 - Not classifiable as to its carcinogenicity to humans

**National Toxicology Program (NTP):**

Name	Classification
Cobalt bis(2-ethylhexanoate)	Reasonably anticipated to be human carcinogens
Naphthalene	Reasonably anticipated to be human carcinogens
Benzene	Known to be human carcinogens

**Germ cell mutagenicity**

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:** No data available.

**Substance data:**

Name	Result
Stoddard Solvent	May cause genetic defects.
Naphtha (petroleum), hydrotreated heavy	May cause genetic defects.
Solvent naphtha (petroleum), light arom.	May cause genetic defects.
Benzene	May cause genetic defects.

**Reproductive toxicity**

**Assessment:** Suspected of damaging fertility or the unborn child

**Product data:** No data available.

**Substance data:**

# Safety Data Sheet

According to HSNO Regulations

Initial preparation date: 08.6.2018

Page 11 of 14

AMC Green

Name	Result
Toluene	Suspected of damaging fertility or the unborn child.

### Specific target organ toxicity (single exposure)

**Assessment:** May cause drowsiness or dizziness

**Product data:** No data available.

#### Substance data:

Name	Result
Naphtha (petroleum), hydrotreated heavy	Component affects the central nervous system.
Ethyl Benzene	Repeated exposure damages the hearing organs.
Cumene	Component affects the respiratory system.
Benzene	Causes damage to the organs through prolonged or repeated exposure.
n-Butyl acetate	SE May cause drowsiness or dizziness. - Central nervous system
Toluene	Component affects the central nervous system.

### Specific target organ toxicity (repeated exposure)

**Assessment:** Causes damage to organs through prolonged or repeated exposure

**Product data:** No data available.

#### Substance data:

Name	Result
Stoddard Solvent	Causes damage to organs through prolonged or repeated exposure.

### Aspiration toxicity

**Assessment:** May be fatal if swallowed and enters airways

**Product data:** No data available.

#### Substance data:

Name	Result
Stoddard Solvent	May be fatal if swallowed and enters airways.
Naphtha (petroleum), hydrotreated heavy	May be fatal if swallowed and enters airway.
Ethyl Benzene	May be fatal if swallowed and enters airway.
Distillates (petroleum), hydrotreated light	May be fatal if swallowed and enters airway.
Solvent naphtha (petroleum), light arom.	May be fatal if swallowed and enters airway.

### Information on likely routes of exposure:

No data available.

### Symptoms related to the physical, chemical and toxicological characteristics:

No data available.

### Other information:

No data available.

## SECTION 12: Ecological information

### Acute (short-term) toxicity

**Assessment:** Harmful to aquatic life.

**Product data:** No data available.

#### Substance data:

# Safety Data Sheet

According to HSNO Regulations

Initial preparation date: 08.6.2018

Page 12 of 14

AMC Green

Name	Result
Naphthalene	LC50 - Opossum Shrimp - 0.85 mg/L - 96 h
	LC50 - Melanotaenia fluviatilis (Crimson-Spotted Rainbowfish) - 0.213 mg/L - 96 h
Cumene	EC50 - Daphnia magna - 1.4 mg/L - 24 h
	LC50 - Pimephales promelas - 6.32 mg/L - 96 h

### Chronic (long-term) toxicity

**Product data:** No data available.

**Substance data:**

Name	Result
Stoddard Solvent	NOEC Fish: 0.14 mg/L (96 Hr)
Cobalt bis(2-ethylhexanoate)	NOEC - Pimephales promelas - 0.21 mg/L - 34 d

### Persistence and degradability

**Product data:** No data available.

**Substance data:** No data available.

### Bioaccumulative potential

**Product data:** No data available.

**Substance data:** No data available.

### Mobility in soil

**Product data:** No data available.

**Substance data:** No data available.

### Hazard to the ozone layer

**Product data:** No data available.

**Substance data:** No data available.

**Other adverse effects:** No data available.



## SECTION 13: Disposal considerations

### Disposal methods:

It is the responsibility of the waste generator to properly characterize all waste materials according to applicable regulatory entities.

## SECTION 14: Transportation information

### Road/Rail transport: (NZS 5433:1999)

UN number	1263
UN proper shipping name	Paint
UN transport hazard class(es)	3  
Packing group	III
Environmental hazards	Marine Pollutant (Stoddard Solvent)
Special precautions for user	None

# Safety Data Sheet



According to HSNO Regulations

Initial preparation date: 08.6.2018



Page 13 of 14

AMC Green

### International Maritime Dangerous Goods (IMDG)

UN number	1263	
UN proper shipping name	Paint	
UN transport hazard class(es)	3	 
Packing group	III	
Environmental hazards	Marine Pollutant (Stoddard Solvent)	
Special precautions for user	None	
EmS number	F-E, S-E	
Stowage category		
Excepted quantities	E1	
Limited quantity	5L	

### International Air Transport Association Dangerous Goods Regulations (IATA-ICAO)

UN number	1263	
UN proper shipping name	Paint	
UN transport hazard class(es)	3	 
Packing group	III	
Environmental hazards	Marine Pollutant (Stoddard Solvent)	
Special precautions for user	None	
ERG code		
Excepted quantities	E1	
Passenger and cargo		
Cargo aircraft only		
Limited quantity	10L	
Additional Information	No additional data	

Transport in bulk according to Annex II of MARPOL and the IBC Code: No additional data

### SECTION 15: Regulatory information

#### New Zealand Inventory of Chemicals (NZIoC):

64742-48-9	Naphtha (petroleum), hydrotreated heavy	Listed
71-43-2	Benzene	Listed
1333-86-4	Carbon Black	Listed
100-41-4	Ethyl Benzene	Listed
64742-95-6	Solvent naphtha (petroleum), light arom.	Listed
22464-99-9	Zirconium 2-Ethylhexanoate	Listed

# Safety Data Sheet

According to HSNO Regulations

Initial preparation date: 08.6.2018

Page 14 of 14

AMC Green

64742-47-8	Distillates (petroleum), hydrotreated light	Listed
108-65-6	1-Methoxy-2-propanol acetate	Listed
123-86-4	n-Butyl acetate	Listed
13463-67-7	Titanium Dioxide	Listed
147-14-8	29H,31H-Phthalocyaninato(2-)- N29,N30,N31,N32 copper	Listed
136-52-7	Cobalt bis(2-ethylhexanoate)	Listed
98-82-8	Cumene	Listed
108-88-3	Toluene	Listed
96-29-7	Methyl ethyl ketoxime	Listed
8052-41-3	Stoddard Solvent	Listed
91-20-3	Naphthalene	Listed

### HSNO Classification or Subclasses:

Class	GHS Category	HSNO Category
Flammable liquids	Category 3	3.1C
Eye irritation	Category 2A	6.4A
Skin irritation	Category 2	6.3A
Skin sensitization	Category 1	6.5B
Aspiration hazard	Category 1	6.1E
Specific target organ toxicity - single exposure	Category 3, central nervous system	6.9B
Specific target organ toxicity - repeated exposure	Category 1	6.9A
Carcinogenicity	Category 2	6.7B
Reproductive toxicity	Category 2	6.8B
Acute aquatic hazard	Category 3	9.1D
Chronic aquatic hazard	Category 2	9.1B

<b>HSNO Group Standard Name :</b>	<b>HSNO Approval Number:</b>
Surface Coatings and Colourants (Flammable, Toxic [6.7])	HSR002669

### SECTION 16: Other information

**Abbreviations and Acronyms:** None

**Disclaimer:**

The information provided in this SDS is correct, to the best of our knowledge, based on information available. The information given is designed only as a guidance for safe handling, use, storage, transportation and disposal and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials, unless specified in the text. The responsibility to provide a safe workplace remains with the user.

**Initial preparation date:** 08/16/2018

**Revision Date:** New

**End of Safety Data Sheet**