

# Safety Data Sheet

## According to HSNO Regulations

Initial preparation date: 04.24.2018

Page 1 of 11

**Engine Enamel CHRYSLER BLUE**

### SECTION 1: Identification

#### Product identifier

**Product name:** Engine Enamel CHRYSLER BLUE

**Product code:** 42108

**Additional information:** No additional information available.



#### Recommended use of the product and restriction on use:

**Relevant identified uses:** Coating compound/ Surface coating/ Paint

**Uses advised against:** Not determined or not applicable.

**Reasons why uses advised against:** Not determined or not applicable.

#### Manufacturer or supplier details

##### Manufacturer:

P.O.R. Products  
38 Portman Road  
New Rochelle, NY 10801  
914-636-0700

##### Supplier:

HGLB Holdings  
30 Victoria Street  
Petone 5012  
021 446682  
sales@por15nz.com

#### Emergency telephone number:

**ChemTel Inc.**

+1 813 248 0585

**Poisons Information Center, New Zealand**

0800 764 766

### SECTION 2: Hazards identification

**Classified as a Dangerous Good according to NZS 5433:2012 Transport of Dangerous Goods on Land.**

**Classified as hazardous according to criteria in the HS (Minimum Degrees of Hazard) Regulations 2017**

#### HSNO Classification or Subclasses - Physical hazards:

Class	GHS Category	HSNO Category
Flammable liquids	Category 3	3.1C

#### HSNO Classification or Subclasses - Health hazards:

Class	GHS Category	HSNO Category
Eye irritation	Category 2A	6.4A
Skin sensitization	Category 1	6.5B
Specific target organ toxicity - repeated exposure	Category 1	6.9A
Carcinogenicity	Category 1B	6.7A
Reproductive toxicity	Category 2	6.8B

#### HSNO Classification or Subclasses - Environmental hazards:

Class	GHS Category	HSNO Category
Chronic aquatic hazard	Category 2	9.1B

#### GHS classification:

Flammable liquids, category 3

Eye irritation, category 2A

Skin sensitization, category 1

# Safety Data Sheet

## According to HSNO Regulations

Initial preparation date: 04.24.2018

Page 2 of 11

### Engine Enamel CHRYSLER BLUE

Specific target organ toxicity - repeated exposure, category 1  
Carcinogenicity, category 1B  
Reproductive toxicity, category 2  
Chronic aquatic hazard, category 2

#### Label elements

##### Hazard pictograms:



**Signal word:** Danger

##### Hazard statements and Precautionary statements:

H226 Flammable liquid and vapor.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H350 May cause cancer.  
H361 Suspected of damaging fertility or the unborn child.  
H372 Causes damage to organs through prolonged or repeated exposure.  
H411 Toxic to aquatic life with long lasting effects.  
P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.  
P233 Keep container tightly closed.  
P240 Ground/bond container and receiving equipment.  
P241 Use explosion-proof electrical/ventilating/lighting equipment.  
P242 Use only non-sparking tools.  
P243 Take precautionary measures against static discharge.  
P260 Do not breathe dust/fume/gas/mist/vapors/spray.  
P261 Avoid breathing dust/fume/gas/mist/vapors/spray.  
P264 Wash skin thoroughly after handling.  
P270 Do not eat, drink or smoke when using this product.  
P272 Contaminated work clothing should not be allowed out of the workplace.  
P273 Avoid release to the environment.  
P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P281 Use personal protective equipment as required.  
P302+P352 IF ON SKIN: Wash with plenty of soap and water.  
P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P308+P313 If exposed or concerned: Get medical advice/attention  
P314 Get medical advice/attention if you feel unwell  
P321 Specific treatment (see first aid instructions on this label).  
P333+P313 If skin irritation or a rash occurs: Get medical advice/attention  
P337+P313 If eye irritation persists get medical advice/attention  
P362+P364 Take off contaminated clothing and wash it before reuse.  
P363 Wash contaminated clothing before reuse  
P370+P378 In case of fire: Use fire appropriate fire extinguishing methods for extinction.  
P391 Collect spillage  
P403+P235 Store in a well ventilated place. Keep cool.  
P405 Store locked up.  
P501 Dispose of contents/container according to local regulations.

# Safety Data Sheet

## According to HSNO Regulations

Initial preparation date: 04.24.2018

Page 3 of 11

### Engine Enamel CHRYSLER BLUE

#### Hazards not otherwise classified:

None known.

### SECTION 3: Composition/information on ingredients

#### Mixture:

Identification	Name	Weight %
CAS number: 8052-41-3	Stoddard Solvent	32-36
CAS number: 64742-48-9	Naphtha (petroleum), hydrotreated heavy	5-8
CAS number: 13463-67-7	Titanium Dioxide	2-5
CAS number: 64742-95-6	Solvent naphtha (petroleum), light arom.	<0.3
CAS number: 136-52-7	Cobalt bis(2-ethylhexanoate)	<0.3
CAS number: 96-29-7	Methyl ethyl ketoxime	<0.1

#### Additional information:

Not determined or not available.

### SECTION 4: First-aid measures

For advice, contact a Poisons Information Center (e.g. phone Australia 131 126, New Zealand 0800 764 766) or a doctor.

#### Description of first aid measures

##### General notes:

Not determined or not available.

##### After inhalation:

Loosen clothing as necessary and position individual in a comfortable position

Maintain an unobstructed airway

Get medical advice/attention if you feel unwell

##### After skin contact:

Rinse affected area with soap and water

If symptoms develop or persist, seek medical attention

Take off all contaminated clothing

Gently blot or brush away excess product

Wash with plenty of lukewarm, gently flowing water

Get medical advice if skin irritation occurs or you feel unwell

##### After eye contact:

Rinse/flush exposed eye(s) gently using water for 15-20 minutes.

If symptoms develop or persist, seek medical attention.

Rinse eyes cautiously with lukewarm, gently flowing water for several minutes, while holding the eyelids open.

Remove contact lenses, if present and easy to do so.

Continue rinsing for 15-20 minutes.

Get medical advice if eye irritation persists.

##### After swallowing:

Rinse mouth thoroughly

Seek medical attention if irritation, discomfort, or vomiting persists

# Safety Data Sheet

## According to HSNO Regulations

Initial preparation date: 04.24.2018

Page 4 of 11

### Engine Enamel CHRYSLER BLUE

#### Most important symptoms and effects, both acute and delayed:

##### Acute symptoms and effects:

Product is highly flammable and may cause physical injury.

Dermal symptoms may include irritation, redness, pain, inflammation, itching, burning and tearing.

##### Delayed symptoms and effects:

Long term exposure may affect fertility. Symptoms include, but are not limited to: menstrual problems, altered sexual behavior/fertility/ and pregnancy outcome.

Long term exposure may also affect development of the unborn child. Symptoms include, but are not limited to: intrauterine growth retardation, pre-term birth, birth defects and postnatal death.

Suspected of causing cancer. Effects are dependent on exposure (dose, concentration, contact time).

#### Immediate medical attention and special treatment:

##### Specific treatment:

Not determined or not available.

##### Notes for the doctor:

Treat symptomatically.

#### Workplace Facilities:

Not determined or not available.

### SECTION 5: Fire-fighting measures

#### Extinguishing media

##### Suitable extinguishing media:

Use Water (fog only), dry chemical, chemical foam, carbon dioxide, or alcohol-resistant foam.

##### Unsuitable extinguishing media:

Do not use a water stream as an extinguisher.

#### Specific hazards during fire-fighting:

Thermal decomposition can lead to release of irritating gases and vapors.

Vapors can flow to distant ignition sources and flashback

Liquid is volatile and may generate an explosive atmosphere.

#### Special protective equipment for firefighters:

Use typical firefighting equipment, self-contained breathing apparatus, special tightly sealed suit.

#### Special precautions:

Shut off sources of ignition.

Carbon monoxide and carbon dioxide may form upon combustion.

Heating causes a rise in pressure, risk of bursting and combustion.

#### Hazchem or Emergency Action Code:

HAZCHEM Code: •3Y

### SECTION 6: Accidental release measures

#### Personal precautions, protective equipment and emergency procedures:

Ensure adequate ventilation.

Ensure air handling systems are operational.

Wear protective eye wear, gloves and clothing.

Beware of vapors accumulating to form explosive concentrations.

Vapors can accumulate in low areas.

#### Environmental precautions:

Should not be released into the environment.

Prevent from reaching drains, sewer or waterway.

# Safety Data Sheet

## According to HSNO Regulations

Initial preparation date: 04.24.2018

Page 5 of 11

### Engine Enamel CHRYSLER BLUE

#### Methods and material for containment and cleaning up:

Wear protective eye wear, gloves and clothing.

Use spark-proof tools and equipment.

Absorb with non-combustible liquid-binding material (sand, diatomaceous earth (clay), acid binders, universal binders).

Dispose of contents / container in accordance with local regulations.

#### Reference to other sections:

Refer to Section 8 for Personal Protective Equipment and Section 13 for Disposal information.

### SECTION 7: Handling and storage precautions

#### Precautions for safe handling:

Use only with adequate ventilation.

Avoid breathing mist or vapor.

Do not eat, drink, smoke or use personal products when handling chemical substances.

Take precautionary measures against electrostatic discharges.

Use only non-sparking tools.

#### Conditions for safe storage, including any incompatibilities:

Keep container tightly sealed.

Protect from freezing and physical damage.

Store in a cool, well-ventilated area.

Store away from all ignition sources (open flames, hot surfaces, direct sunlight, spark sources).

#### Safe packaging material

##### Suitable material:

Not determined or not applicable.

##### Unsuitable material:

Not determined or not applicable.

### SECTION 8: Exposure controls and personal protection

#### Occupational Exposure limit values:

Country (Legal Basis)	Substance	Identifier	Permissible concentration
New Zealand	Stoddard Solvent	8052-41-3	TWA: 100 ppm. TWA: 525 mg/m <sup>3</sup>
	Titanium Dioxide	13463-67-7	TWA: 10 mg/m <sup>3</sup>

#### Biological limit value:

No biological exposure limits noted for the ingredient(s)

#### Information on monitoring procedures:

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls

Biological monitoring may also be appropriate for some substances

#### Appropriate engineering controls:

Emergency eye wash fountains and safety showers should be available in the immediate vicinity of use or handling.

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapor and mists below the applicable workplace exposure limits (Occupational Exposure Limits-OELs) indicated above.

Use explosion-proof ventilation equipment.

# Safety Data Sheet

## According to HSNO Regulations

Initial preparation date: 04.24.2018

Page 6 of 11

### Engine Enamel CHRYSLER BLUE

#### Personal protection equipment

##### Eye and face protection:

Safety goggles or glasses, or appropriate eye protection.

##### Skin and body protection:

Select glove material impermeable and resistant to the substance.  
Wear appropriate clothing to prevent any possibility of skin contact.

##### Respiratory protection:

If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.

##### General hygienic measures:

Avoid contact with skin, eyes and clothing.  
Wash hands before breaks and at the end of work.  
Wash contaminated clothing before reuse.

### SECTION 9: Physical and chemical properties

<b>Appearance</b>	Blue Colored Liquid
<b>Odor</b>	Solvent-like
<b>Odor threshold</b>	Not determined or not available.
<b>pH</b>	Not determined or not available.
<b>Melting point/freezing point</b>	Not determined or not available.
<b>Initial boiling point/range</b>	>284°F (>140°C)
<b>Flash point (closed cup)</b>	>105°F (>41°C)
<b>Evaporation rate</b>	Not determined or not available.
<b>Flammability (solid, gas)</b>	Not determined or not available.
<b>Upper flammability/explosive limit</b>	Not determined or not available.
<b>Lower flammability/explosive limit</b>	Not determined or not available.
<b>Vapor pressure</b>	Not determined or not available.
<b>Vapor density</b>	Not determined or not available.
<b>Density</b>	0.848-0.945 g/cm <sup>3</sup>
<b>Relative density</b>	Not determined or not available.
<b>Solubilities</b>	Not miscible.
<b>Partition coefficient (n-octanol/water)</b>	Not determined or not available.
<b>Auto/Self-ignition temperature</b>	Product is not self-igniting
<b>Decomposition temperature</b>	Not determined or not available.
<b>Dynamic viscosity</b>	Not determined or not available.
<b>Kinematic viscosity</b>	Not determined or not available.
<b>Explosive properties</b>	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
<b>Oxidizing properties</b>	Not determined or not available.

#### Other information

<b>VOC Content</b>	60-68% (Max - < 430 g/L)
--------------------	--------------------------

### SECTION 10: Stability and reactivity

#### Reactivity:

Does not react under normal conditions of use and storage.

# Safety Data Sheet

## According to HSN0 Regulations

Initial preparation date: 04.24.2018

Page 7 of 11

### Engine Enamel CHRYSLER BLUE

#### Chemical stability:

Stable under normal conditions of use and storage.

#### Possibility of hazardous reactions:

Develops readily flammable gases/fumes.

Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomised.

Can react violently with oxygen rich (oxidizing) materials.

Toxic fumes may be released if heated above the decomposition point.

Used empty containers may contain product gases which form explosive mixtures with air.

#### Conditions to avoid:

Keep away from open flames, hot surfaces and sources of ignition.

Store away from oxidizing agents.

#### Incompatible materials:

Oxidizing agents.

#### Hazardous decomposition products:

CO, CO<sub>2</sub>.

Hydrocarbons.

### SECTION 11: Toxicological information

#### Acute toxicity:

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:** No data available.

**Substance data:** No data available.

#### Skin corrosion/irritation:

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:** No data available.

#### Substance data:

Name	Result
Naphtha (petroleum), hydrotreated heavy	Irritating to the skin.
Cobalt bis(2-ethylhexanoate)	Irritating to the skin.

#### Serious eye damage/irritation:

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:** No data available.

#### Substance data:

Name	Result
Methyl ethyl ketoxime	Risk of serious damage to the eyes.

#### Respiratory or skin sensitization:

**Assessment:** May cause an allergic skin reaction

**Product data:** No data available.

#### Substance data:

Name	Result
Cobalt bis(2-ethylhexanoate)	May cause sensitization by skin contact.
Methyl ethyl ketoxime	May cause sensitization by skin contact

#### Carcinogenicity

**Assessment:** May cause cancer.

**Product data:** No data available.

# Safety Data Sheet

## According to HSN0 Regulations

Initial preparation date: 04.24.2018

Page 8 of 11

### Engine Enamel CHRYSLER BLUE

#### Substance data:

Name	Species	Result
Stoddard Solvent	Stoddard Solvent	Component may cause cancer.
Naphtha (petroleum), hydrotreated heavy		May cause cancer.
Methyl ethyl ketoxime		May cause cancer.
Solvent naphtha (petroleum), light arom.	Solvent naphtha (petroleum), light arom.	Component may cause cancer.
Titanium Dioxide		Airborne, unbound particles of respirable size are known to cause cancer.

#### International Agency for Research on Cancer (IARC):

Name	Classification
Stoddard Solvent	Group 3
Cobalt bis(2-ethylhexanoate)	Group 2B
Titanium Dioxide	Group 2B

#### National Toxicology Program (NTP):

Name	Classification
Cobalt bis(2-ethylhexanoate)	Reasonably anticipated to be human carcinogens

#### Germ cell mutagenicity

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:** No data available.

#### Substance data:

Name	Result
Stoddard Solvent	May cause genetic defects.
Naphtha (petroleum), hydrotreated heavy	May cause genetic defects.
Solvent naphtha (petroleum), light arom.	May cause genetic defects.

#### Reproductive toxicity

**Assessment:** Suspected of damaging fertility or the unborn child

**Product data:** No data available.

**Substance data:** No data available.

#### Specific target organ toxicity (single exposure)

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:** No data available.

#### Substance data:

Name	Result
Naphtha (petroleum), hydrotreated heavy	Component affects the central nervous system.

#### Specific target organ toxicity (repeated exposure)

**Assessment:** Causes damage to organs through prolonged or repeated exposure

**Product data:** No data available.

#### Substance data:

Name	Result
Stoddard Solvent	Causes damage to organs through prolonged or repeated

#### Aspiration toxicity

**Assessment:** Based on available data, the classification criteria are not met.



# Safety Data Sheet

## According to HSNO Regulations

Initial preparation date: 04.24.2018

Page 9 of 11

### Engine Enamel CHRYSLER BLUE

**Product data:** No data available.

**Substance data:**

Name	Result
Stoddard Solvent	May be fatal if swallowed and enters airways.
Naphtha (petroleum), hydrotreated heavy	May be fatal if swallowed and enters airway.
Solvent naphtha (petroleum), light arom.	May be fatal if swallowed and enters airway.

**Information on likely routes of exposure:**

No data available.

**Symptoms related to the physical, chemical and toxicological characteristics:**

No data available.

**Other information:**

No data available.

### SECTION 12: Ecological information

**Acute (short-term) toxicity**

**Assessment:** Harmful to aquatic life.

**Product data:** No data available.

**Substance data:** No data available.

**Chronic (long-term) toxicity**

**Product data:** No data available.

**Substance data:**

Name	Result
Stoddard Solvent	NOEC Fish: 0.14 mg/L (96 Hr)
Cobalt bis(2-ethylhexanoate)	NOEC - Pimephales promelas - 0.21 mg/L - 34 d

**Persistence and degradability**

**Product data:** No data available.

**Substance data:** No data available.

**Bioaccumulative potential**

**Product data:** No data available.

**Substance data:** No data available.

**Mobility in soil**

**Product data:** No data available.

**Substance data:** No data available.

**Hazard to the ozone layer**

**Product data:** No data available.

**Substance data:** No data available.

**Other adverse effects:** No data available.

### SECTION 13: Disposal considerations

**Disposal methods:**

It is the responsibility of the waste generator to properly characterize all waste materials according to applicable regulatory entities.

# Safety Data Sheet

## According to HSNO Regulations


Initial preparation date: 04.24.2018

Page 10 of 11


**Engine Enamel CHRYSLER BLUE**

### SECTION 14: Transportation information


#### Road/Rail transport: (NZS 5433:1999)

<b>UN number</b>	1263	
<b>UN proper shipping name</b>	Paint	
<b>UN transport hazard class(es)</b>	3	
<b>Packing group</b>	III	
<b>Environmental hazards</b>	Marine Pollutant (Stoddard Solvent, Naphtha (petroleum), hydrotreated heavy)	
<b>Special precautions for user</b>	None	

#### International Maritime Dangerous Goods (IMDG)

<b>UN number</b>	1263	
<b>UN proper shipping name</b>	Paint	
<b>UN transport hazard class(es)</b>	3	
<b>Packing group</b>	III	
<b>Environmental hazards</b>	Marine Pollutant (Stoddard Solvent, Naphtha (petroleum), hydrotreated heavy)	
<b>Special precautions for user</b>	None	
<b>EmS number</b>	F-E, S-E	
<b>Stowage category</b>	A	
<b>Excepted quantities</b>	E1	
<b>Limited quantity</b>	5L	

#### International Air Transport Association Dangerous Goods Regulations (IATA-ICAO)

<b>UN number</b>	1263	
<b>UN proper shipping name</b>	Paint	
<b>UN transport hazard class(es)</b>	3	
<b>Packing group</b>	III	
<b>Environmental hazards</b>	Marine Pollutant (Stoddard Solvent, Naphtha (petroleum), hydrotreated heavy)	
<b>Special precautions for user</b>	None	
<b>ERG code</b>	3L	
<b>Excepted quantities</b>	E1	
<b>Passenger and cargo</b>	60L	

# Safety Data Sheet

## According to HSNO Regulations

Initial preparation date: 04.24.2018

Page 11 of 11

### Engine Enamel CHRYSLER BLUE

<b>Cargo aircraft only</b>	220L
<b>Limited quantity</b>	10L
<b>Additional Information</b>	No additional data

**Transport in bulk according to Annex II of MARPOL and the IBC Code:** No additional data

### SECTION 15: Regulatory information

#### New Zealand Inventory of Chemicals (NZIoC):

8052-41-3	Stoddard Solvent	Listed
64742-48-9	Naphtha (petroleum), hydrotreated heavy	Listed
13463-67-7	Titanium Dioxide	Listed
64742-95-6	Solvent naphtha (petroleum), light arom.	Listed
136-52-7	Cobalt bis(2-ethylhexanoate)	Listed
96-29-7	Methyl ethyl ketoxime	Listed

#### HSNO Classification or Subclasses:

Class	GHS Category	HSNO Category
Flammable liquids	Category 3	3.1C
Eye irritation	Category 2A	6.4A
Skin sensitization	Category 1	6.5B
Specific target organ toxicity - repeated exposure	Category 1	6.9A
Carcinogenicity	Category 1B	6.7A
Reproductive toxicity	Category 2	6.8B
Chronic aquatic hazard	Category 2	9.1B

<b>HSNO Group Standard Name :</b>	<b>HSNO Approval Number:</b>
Surface Coatings and Colourants (Flammable, Toxic [6.7])	HSR002669

### SECTION 16: Other information

**Abbreviations and Acronyms:** None

#### Disclaimer:

The information provided in this SDS is correct, to the best of our knowledge, based on information available. The information given is designed only as a guidance for safe handling, use, storage, transportation and disposal and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials, unless specified in the text. The responsibility to provide a safe workplace remains with the user.

**Initial preparation date:** 04.24.2018

**Revision Date:** New

**End of Safety Data Sheet**